MIL-C-14982/18(MU)
15 February 1969

MILITARY SPECIFICATION SHEET

CABLES FOR ATOMIC DEMOLITION CHARGES

W41-AP1E1 CABLE ASSEMBLY

The complete requirements for procuring the cable assembly described herein shall consist of this document and the latest issue of specification MIL-C-14982(MU).

1. SCOPE

1.1 This specification covers detail requirements, quality assurance provisions and preparation for delivery for production and repair parts for Cable Assembly W41-AP-1E1 (Training) for use with Training Atomic Demolition Charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-14982(MU) - Cables for Training Atomic Demolition Charge, General Specification for

STANDARDS

MILITARY

MS 3137 - Connector
MS 3182 - Cap, Protective
MS 15795 - Washer
MS 20470 - Rivet
MS 25281 - Clamp
MS 51025 - Set Screw

FSC 1195

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:18Z
Check the source to verify that this is the current version before use.

DRAWINGS

ORDNANCE CORPS

8823708 - Connector
8838930 - Cap, Protective
8851874 - Molding Compound Polyurethane, Orange-Red
8851878 - Cable, Red 9 Conductor
8851900 - Box, Set-up Paperboard for W41-AP-1(Tng) Cable Assembly
8851901 - Primer Metal to Polyurethane
8851903 - Primer Polyurethane to B.Y.C.
8851983 - Shell, Molding
8852051 - Silk Screen Process Specification
8861465 - Stop, Switch
9216518 - Stop, Switch Assembly
9216789 - Silicone Compound
9216954 - Cable Assembly W41-AP-1E1 (Training)
ET-9216954 - Equipment Tabulation

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements. - Requirements shall be in accordance with MIL-C-14982(MU) and as specified herein.

3.2 Circuit resistance. - The cable assembly circuit resistance shall be in accordance with Table I.

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:18Z
Check the source to verify that this is the current version before use.

Table I

Circuit Resistance (See Dwg 9216954)

From P42-2 Connector Pin	To P5-1 Connector Pin	Ohms Max
A	6	0.2
B	4	0.2
C	12	0.2
D	3	0.2
E	11	0.2
G	1	0.2
L	9	0.2
M	19	0.2
J	5	0.2
K	5	0.2

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. - Sampling and inspection shall be in accordance with MIL-C-14982(MU) and as specified herein.

4.1.1 Sampling and inspection not applicable. - The following classification of defects in MIL-C-14982(MU) is not applicable:

a. 4.3.2.1.4 Bag, packing, ammunition for cable assembly.

4.2 First article inspection.

4.2.1 Quantity to be submitted. - In addition to quantities specified in 4.2.1 MIL-C-14982(MU), 3 sub-assemblies shall be submitted (see dwg 9216954) Cable Assembly W41-AP-1E1 (Training) before potting and molding.

4.3 Classification of characteristics.

4.3.1 Stop, switch (see dwg 8861465 covering a detail of dwg 9216518.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Location of large hole.....Gage
102. Location of countersunk holes... .....Gage

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:18Z
Check the source to verify that this is the current version before use.

103. Small width.....*Measure
104. Diameter of countersunk holes.....Gage
105. Width of projection.....*Measure
106. Large width.....*Measure
107. Length of projection.....*Measure
108. Diameter of large hole.....Gage
109. Length.....*Measure
110. Depth of countersink, min.....Gage
111. Location of tapped hole.....Gage
112. Pitch diameter of tapped hole.....Gage
113. Minor diameter of tapped hole, max.....Gage
114. Thickness, min.....Gage
115. Material (see 3.2 MIL-C-14982(MU).....Visual
116. Objective evidence (see 6.3 MIL-C-14982(MU) available for protective finish in accordance with dwg 8861465.....Visual

*Measure with suitable scale.

Minor:

201. Workmanship (see 3.12 MIL-C-14982(MU).....Visual/Manual

4.3.2 Stop, switch assembly (see dwg 9216518) covering a detail of dwg 9216954.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Material (see 3.2 MIL-C-14982(MU).....Visual
102. Length of tubing.....*Measure
103. Lacing tied.....Visual
104. Knots coated.....Visual

*Measure with suitable scale.

Minor:

201. Workmanship (see 3.12 MIL-C-14982(MU).....Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 202640-18T05:18Z
Check the source to verify that this is the current version before use.

4.3.3 Connector (see dwg 8823708); cap, protective (see dwg 8838930); molding compound polyurethane, orange-red (see dwg 8851874); cable, red 9 conductor (see dwg 8851878); primer metal to polyurethane (see dwg 8851901); primer polyurethane to B.Y.C. (see dwg 8851903); shell, molding (see dwg 8851983); silicone compound (see dwg 9216789); connector (see MS 3107E-19S); cap, protective (see MS 3182-19C); washer (see MS 15795-204); rivet (see MS 20450 C8AD12); clamp (see MS 25281-8W); set screw (see MS 51025-10) covering details of dwg 9216954.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Objective evidence (see 6.3 MIL-C-14982(MU) available for parts in accordance with applicable standard or drawing.....Visual

Minor:

201. Workmanship (see 3.12 MIL-C-14982(MU).....Visual/Manual

4.3.4 Cable assembly W41-AP-1E1 (training) (see dwg 9216954) before potting and molding.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Primer applied to connectors.....Visual
102. Primer applied to cable.....Visual

Minor: None defined.

4.3.5 Cable assembly W41-AP-1E1 (training) (see dwg 9216954).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Length of mold left connector.....*Measure
102. Length from connector to outside of mold left connector.....*Measure

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:18Z
Check the source to verify that this is the current version before use.

103. Angle of left connector.....Gage
104. Large diameter of mold left connector.....Gage
105. Length from connector to outside of mold right connector.....*Measure
106. Clamps tight.....Manual
107. Length.....*Measure
108. Location of key way left connector.....Visual
109. Location of key way right connector.....Visual
110. Alignment of grooves of connector and stop switch assembly.....Gage
111. Length of mold right connector.....*Measure
112. Large diameter of mold right connector.....Gage
113. Marking.....Visual
114. Silicone compound present.....Visual

*Measure with suitable scale.

Minor:

201. Serialization (see 3.5 MIL-C-14982(MU).....Visual/Manual

4.4 Insulation resistance. - The cable assembly insulation resistance shall be tested in accordance with Table II.

Table II

Insulation Resistance (see dwg 9216954)

Positive Potential P5-1 Connector Pin	Negative potsntial to shells and all other pins except P42-2 Connector Pin
6	A
4	B
12	C
3	D
11	E
1	G
9	L
19	M
5	J and K

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:18Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery for production cable assemblies. - Preparation for delivery for production cable assemblies shall be in accordance with MIL-C-14892(MU).

5.2 Preparation for delivery for repair cable assemblies.

5.2.1 Preservation and packaging. - Preservation and packaging shall be as specified in MIL-C-14892(MU).

5.2.1.1 Level A. - The cable assembly shall be packaged in accordance with dwgs 8851900 and 8808362 and as specified in MIL-C-14982(MU).

5.2.1.2 Level C. - The cable assembly shall be packaged in accordance with dwgs 8851900 and 8808362 and MIL-C-14982(MU).

5.2.2 Packing.

5.2.2.1 Levels A and C. - The cable assembly shall be packed in accordance with dwgs 8851900 and 8808362 and MIL-C-14982(MU).

5.2.3 Marking. - Marking shall be as specified in dwgs 8851900 and 8808362 and MIL-C-14982(MU).

6. NOTES

6.1 Notes. - Notes shall be in accordance with MIL-C-14982(MU).

Custodian
Army-MU

Preparing Agency
Army-MU
Project No -1195-A044

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:18Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval No. [illegible]

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve improvement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

[ ] DIRECT GOVERNMENT CONTRACT [illegible]

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

   a. GIVE PARAGRAPH NUMBER AND WORDING

   b. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   [ ] YES [ ] NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:18Z
Check the source to verify that this is the current version before use.