MILITARY SPECIFICATION SHEET
CABLES FOR TRAINING ATOMIC DEMOLITION CHARGES

CABLE ASSEMBLY, T-4132-1

The complete requirements for procuring the cable assembly described herein shall consist of this document and the latest issue of specification MIL-C-14982(MU).

1. SCOPE

1.1 This specification covers detail requirements, quality assurance provisions and preparation for delivery for production and repair parts for Cable Assembly T-4132-1; Training for use with Training Atomic Demolition Charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-14982(MU) - Cables for Training Atomic Demolition Charge, General Specification for

STANDARDS

MILITARY

MS-20470 - Rivet
MS-25281 - Clamp

DRAWINGS

ORDNANCE CORPS

8850777 - Cable Assembly, T-4132-1; Training
8850957 - Connector Plug Electrical
8850958 - Connector
8851861 - Cap and Chain Assembly
8851942 - Box, Set-up, Paperboard for T-4132-1(TNG) Cable Assembly
8881768 - Polyurethane Molding Compound

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

8881769 - Primer, Polyurethane Molding Compound
9207508 - Primer, Polyurethane Compound
EL-8850777 - Equipment List

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-C-14982(MU) and as specified herein.

3.2 Circuit resistance. The cable assembly circuit resistance shall be in accordance with table I.

Table I

Circuit resistance (see dwg 8850777)

From Connector 8850958 Pin	To Connector 8850957 Pin
2	Red banana pin
5	Black banana pin
5	Shell

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-C-14982(MU) and as specified herein.

4.1.1 Sampling and inspection not applicable. The following classification of defects in MIL-C-14982(MU) is not applicable:

a. 4.3.2.1.4 Bag, Packing, ammunition for cable assembly.

4.2 First article inspection.

4.2.1 Quantity to be submitted. In addition to quantities specified in 4.2.1 MIL-C-14982(MU), 3 sub-assemblies shall be submitted (see dwg 8850777 for Cable Assembly, T-4132-1; Training before molding).

4.3 Classification of characteristics.

4.3.1 Rivet (see MS20470-B4-7); Clamp (see MS25281-R6); Connector (see dwgs 8850958, and 8850957); cap and chain assembly (see dwg 8851861); polyurethane molding compound (see dwg 8881768); Primer, polyurethane molding compound (see dwgs 8881769 and 9207508) covering details of dwg 8850777.

Categories	Characteristics	Method of inspection
Critical: None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

Major:
101. Objective evidence (see 6.3 MIL-C-14982(MU)) available for part in accordance with applicable dwg or standard....Visual

Minor:
201. Workmanship (see 3.12 MIL-C-14982(MU))....Visual/Manual

4.3.2 Cable assembly, T-4132-1; training (see dwg 8850777) before molding.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Primer applied to connector....Visual
102. Primer applied to cable....Visual

Minor: None defined.

4.3.3 Cable assembly T-4132-1; training (see dwg 8850777).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Length....*Measure
102. Clamps tight on cable....Manual
103. Objective evidence (see 6.3 MIL-C-14982(MU)) available for cable in accordance with dwg 8850777....Visual
104. Marking....Visual

*Measure with suitable scale

Minor:
201. Paint present....Visual
202. Serialization (see 3.5 MIL-C-14982(MU))....Visual

4.4 Insulation resistance. The cable assembly insulation resistance shall be tested in accordance with table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

Table II

Insulation resistance (see dwg 8850777)

Positive potential applied to	All other pins and connector shells minus potential except pins
Connector 8850958	Connector 8850957
2	red banana pin
5	black banana pin and shell

5.0 PREPARATION FOR DELIVERY

5.1 Preparation for delivery for production cable assemblies. Preparation for delivery for production cable assemblies shall be in accordance with MIL-C-14982(MU).

5.2 Preparation for delivery for repair cable assemblies.

5.2.1 Preservation and packaging. Preservation and packaging shall be as specified in MIL-C-14982(MU).

5.2.1.1 Level A. The cable assembly shall be packaged in accordance with dwgs 8851942 and 8808362 and as specified in MIL-C-14982(MU).

5.2.1.2 Level C. The cable assembly shall be packaged in accordance with dwgs 8851942 and 8808362 and MIL-C-14982(MU).

5.2.2 Packing.

5.2.2.1 Levels A and C. The cable assembly shall be packed in accordance with dwgs 8851942 and 8808362 and MIL-C-14982(MU).

5.2.3 Marking. Marking shall be as specified in dwgs 8851942 and 8808362 and MIL-C-14982(MU).

6.0 NOTES

6.1 Notes. Notes shall be in accordance with MIL-C-14982(MU).

Custodian:
Army - MU

Preparing Agency
Army - MU

Project No. - 1195-A028

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.