MIL-C-14982/20B(MU)
20 May 1970
Superseding
MIL-C-14982/20A(MU)
30 March 1970

MILITARY SPECIFICATION SHEET

CABLES FOR ATOMIC DEMOLITION CHARGES
T-4194 CABLE ASSEMBLY, SPECIAL PURPOSE ELECTRICAL

The complete requirements for procuring the cable assembly described herein shall consist of this document and the latest issue of specification MIL-C-14982(MU).

1. SCOPE

1.1 This specification covers detail requirements, quality assurance provisions and preparation for delivery for production and repair parts for Cable Assembly Special Purpose Electrical T4194 Tng for use with Training Atomic Demolition Charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-50292 - Adapter and Test Plug Assembly: Training
MIL-C-14982(MU) - Cables for Training Atomic Demolition Charge, General Specification for
MIL-P-116 - Preservation, Methods of
MIL-S-60902(MU) - Soldering, Electrical Connections for Nuclear Weapons Systems, Procedure for

STANDARDS

MILITARY

MS 16535 - Rivet Tublar
MS 24347 - Drum, Metal
MS 25281 - Clamp
MS 27183 - Washer

FSC 1195

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:18Z
Check the source to verify that this is the current version before use.

DRAWINGS

ORDNANCE CORPS

8794343 - Seal, Metallic, Assembly, Details and Instructions for Application
8806652 - Marking and Sealing for Cylinderical Containers
8823707 - Connector Plug Electrical
8838937 - Connector Plug Electrical
8850963 - Connector
8851143 - Continuity Plug
8857289 - Cap Protection
8860900 - Drum, Metal, Shipping (Interior)
8864892 - Drum, Metal, Shipping for Cable Assemblies Packing and Marking
8881768 - Polyurethane Molding Compound
8881769 - Primer, Polyurethane Molding Compound
9207508 - Primer, Polyurethane Molding Compound
9227133 - Adapter and Test Plug Assembly Tng
9229265 - Cable Assembly Special Purpose Electrical TW194; Tng
9233454 - Cable Assembly, Training
EL-9229265 - Equipment List

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-C-14982(MU) and as specified herein.

3.2 Circuit resistance. The cable assembly circuit resistance shall be in accordance with Tables I and II.

Table I
Circuit Resistance (see dwg 9233454)

From P1 Pin	To P1 Pin	To P-2 Pin	Ohms Max
A	B	C	0.2
A		B	0.2
B		B	0.2
C		E	0.2
K		A	0.2

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:18Z
Check the source to verify that this is the current version before use.

Table II
Circuit Resistance (see dwg 8851143)

From Pin	To Pin	Ohms Max
E	F	0.2

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-C-14982(MU) and as specified herein.

4.1.1 Sampling and inspection not applicable.

a. 4.3.2.1.4 Bag, packing, ammunition for cable assembly.
b. 4.3.2.1.5 Box set-up paperboard for applicable cable assembly.
c. 4.3.2.1.6 Packing and marking for storage and shipments.

4.2 First article inspection.

4.2.1 Quantity to be submitted. In addition to quantities specified in 4.2.1 MIL-C-14982(MU), 1 sub-assembly shall be submitted before potting or molding (see dwg 9233454).

4.3 Classification of characteristics.

4.3.1 Seal, metallic, assembly, details and instructions for application (see dwg 8794343); connector plug electrical (see dwgs 8838937 and 8823707); connector (see dwg 8850963); cap protection (see dwg 8857289); rivet, tublar (see MS 16535-162); drum, metal (see MS 24347-3); clamp (see MS 25281-F4 and F10); washer (see MS 27183-4) covering details of dwgs 8851143, 8864892, and 9233454 as applicable.

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Objective evidence (see Objective evidence, section 6, MIL-C-14982(MU) available for part in accordance with drawing or specification.....	Visual
Minor:		
201.	Workmanship (see Workmanship, section 3 MIL-C-14982(MU).....	Visual-Manual

4.3.2 Continuity plug (see dwg 8851143 covering a detail of dwg 9233454).

Categories	Characteristics	Method of inspection
Critical: None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:18Z
Check the source to verify that this is the current version before use.

Major:
101. Wiring.....Visual
102. Stamping.....Visual
103. Materials (see Materials, section 3 MIL-C-14982(MU).....Visual

Minor:
201. Workmanship (see Workmanship, section 3 MIL-C-14982(MU).....Visual-Manual

4.3.3 Cable assembly Tng (see dwg 9233454 covering a detail of dwg 9229265).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Length.....*Measure
102. Length of mold connector P1.....*Measure
103. Length of center mold.....*Measure
104. Depth of center mold.....*Measure
105. Width of center mold.....*Measure
106. Distance from center mold to end of connector P2.....*Measure
107. Length of connector P2 mold.....*Measure
108. Clamps tight on cable.....Manual
109. Materials (see Materials, section 3 MIL-C-14982(MU).....Visual
110. Marking.....Visual
111. Potting materials (see Materials, section 3, MIL-C-50288(MU) and process.....Visual

* Measure with suitable scale.

Minor:
201. Serialization (see Serialization, section 3 MIL-C-14982(MU).....Visual
202. Workmanship (see Workmanship, section 3 MIL-C-14982(MU).....Visual-Manual

4.3.4 Cable assembly special purpose electrical T4194; Tng (see dwg 9229265).

Categories	Characteristics	Method of inspection

Critical: None defined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:18Z
Check the source to verify that this is the current version before use.

Major:
101. No component missing.....Visual
102. Objective evidence (see 6.2) for Adapter and Test Plug Assembly (see dwg 9227133) in accordance with MIL-A-50292(MU).....Visual

Minor:
201. Workmanship (see Workmanship, section 3 MIL-C-14982(MU).....Visual-Manual

4.3.5 Drum, metal, shipping, for cable assemblies (see dwg 8864892 and 5.2) before closing cover.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. All components present.....Visual
102. Cable assembled, coiled wrapped and wrapper secured with tape correctly before assembly in bag.....Visual
103. Air exhausted from bag.....Manual
104. Tears, holes, cracks in bag.....Visual
105. Proper heat seal.....Manual
106. Objective evidence (see Objective evidence, section 6 MIL-C-14982(MU) available for heat seal test in accordance with MIL-P-116.....Visual
107. Pad in bottom of drum.....Visual
108. Packaging materials (see Materials, section 3 MIL-C-14982(MU).....Visual

Minor:
201. Workmanship (see Workmanship, section 3 MIL-C-14982(MU).....Visual-Manual

4.3.6 Drum, metal shipping, for cable assemblies (see dwg 8864892 and 5.2).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Contents tight in drum.....Manual
102. Closed and sealed in accordance with dwg 8806652.....Visual-Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:18Z
Check the source to verify that this is the current version before use.

Minor:
201. Marking.....Visual
202. Workmanship (see Workmanship, section 3 MIL-C-14982(MU).....Visual-Manual

4.4 Acceptance inspection equipment. Acceptance inspection equipment shall be in accordance with MIL-C-14982(MU) and EL-9229265.

4.5 Insulation resistance. The cable assembly insulation resistance shall be tested in accordance with Tables IV and V.

Table IV
Insulation Resistance (see dwg 9233454)

Positive Pot to Pin Connector P1	All other pins and shells minus potential except pins: Connector P1	Connector P2
A	B	C and B
C		E
K		A

Table V
Insulation Resistance (see dwg 8851143)

Positive Pot to Pin	All other pins and shell except pins:
E	F

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery for production cable assemblies. Preparation for delivery for production cable assemblies shall be in accordance with MIL-C-14982(MU).

5.2 Preparation for delivery for repair cable assemblies.

5.2.2.1 Level A. The cable assembly shall be preserved and packaged in accordance with dwg 8864892.

5.2.2.2 Level C. The cable assembly shall be preserved and packaged in accordance with dwg 8864892 except that the moisture barrier may be omitted.

5.2.3 Packing.

5.2.3.1 Level A and Level C. The cable assembly shall be packed in accordance with dwg 8864892.

5.2.4 Marking. Marking shall be as specified on dwg 8864892.

6. NOTES

6.1 Notes. Notes shall be in accordance with MIL-C-14982(MU).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:18Z
Check the source to verify that this is the current version before use.

6.2 Identification of changes. The changes were so extensive in this revision no identification of changes has been made. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content.

Custodian:
Army - MU

Preparing Activity
Army - MU

Project No. 1195-A064

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:18Z
Check the source to verify that this is the current version before use.