MIL-C-14982/2A(MU)
15 August 1969
Superseding
MIL-C-14982/2(MU)
15 February 1969

MILITARY SPECIFICATION SHEET

CABLES FOR ATOMIC DEMOLITION CHARGES

W4-1(A)DM CABLE ASSEMBLY

The complete requirements for procuring the cable assembly described herein shall consist of this document and the latest issue of specification MIL-C-14982(MU).

1. SCOPE

1.1 This specification covers detail requirements quality assurance provisions and preparation for delivery for production and repair parts for W4-1(A)DM Cable Assembly Training for use with Training Atomic Demolition Charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

*SPECIFICATIONS

MILITARY

MIL-C-14982(MU) - Cables for Training Atomic Demolition Charge, General Specification for.
MIL-M-60903 - Marking of Electrical Wires and Cables.

*DRAWINGS

ORDNANCE CORPS

8850944 - W4-1(A)DM Cable Assembly Training
8850972 - Connector, Plug, Electrical
8851136 - Field Wire
8851929 - Box, Set-up, Paperboard for W4-1(A)DM (TNG) Cable Assembly
8881768 - Polyurethane Molding Compound
8881769 - Primer, Polyurethane Molding Compound
9207508 - Primer, Polyurethane Molding Compound
EL-8850944 - Equipment List

FSC 1195

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-C-14982(MU) and as specified herein.

3.2 Circuit resistance. The cable assembly circuit resistance shall be in accordance with Table I.

Table I

Circuit Resistance (see dwg 8850944)

From Connector P4-1 Pin	To End of Field Wire	Ohms Max
A	one of either ends	0.2
F	other end	0.2

4. QUALITY ASSURANCE PROVISIONS

*4.1 Quality assurance provisions. Quality assurance provisions shall be in accordance with MIL-C-14982(MU) and as specified herein.

4.1.1 Sampling and inspection not applicable. The following classification of defects in MIL-C-14982(MU) is not applicable:

a. 4.3.2.1.4 Bag, packing ammunition for cable assembly.

4.2 First article inspection.

4.2.1 Quantity to be submitted. In addition to quantities specified in 4.2.1 MIL-C-14982(MU), 3 sub-assemblies shall be submitted (see dwg. 8851094 for W4-1(A)DM Cable Assembly Training before potting or molding).

4.3 Classification of characteristics.

*4.3.1 Connector, plug, electrical (see dwg. 8850972; field wire (see dwg. 8851136); polyurethane molding compound (see dwg. 8881768); primer, polyurethane molding compound (see dwg. 8881769); primer, polyurethane molding compound (see dwg. 9207508); covering details of dwg. 8850944.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Objective evidence (see 6.3 MIL-C-14982(MU) available for part in accordance with applicable drawing.....Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

Minor:
201. Workmanship (see 3.12 MIL-14982(MU).....Visual/Manual

*4.3.3 W4-1(A)DM, Cable Assembly (see dwg. 8850944).

Categories	Characteristics	Method of inspection
Critical:	None defined.	
Major:		
101.	Length of sleeve.....	**Measure
102.	Total length.....	**Meausre
103.	Objective evidence (see 6.3 MIL-C-14982(MU) available for molding ends of field wire in accordance with dwg. 8881770.....	Visual
104.	Cable tied at 10 inch intervals.....	**Measure
105.	End of wire molds removable.....	Manual
106.	Materials (see 3.2 MIL-14982(MU).....	Visual
107.	Marking in accordance with MIL-M-60903.....	Visual

**Measure with suitable scale.

Minor;
201. Serialization (see 3.5 MIL-C-14982(MU).....Visual

4.4 Insulation resistance. The cable assembly insulation resistance shall be tested in accordance with Table II.

Table II

Insulation resistance (see dwg. 8850944)

Positive Potential Connector	All other pins and shell negative potential except Pins
P4-1 pin A F	

5.0 PREPARATION FOR DELIVERY

5.1 Preparation for delivery for production cable assemblies. Preparation for delivery for production cable assemblies shall be in accordance with MIL-C-14982(MU).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

5.2 Preparation for delivery for repair cable assemblies.

5.2.1 Preservation and packaging. Preservation and packaging shall be as specified in MIL-C-14982(MU).

5.2.1.1 Level A. The cable assembly shall be packaged in accordance with dwgs. 8851929 and 8808362 and as specified in MIL-C-14982(MU).

5.2.1.2 Level C. The cable assembly shall be packaged in accordance with dwgs. 8851929 and 8808362 and MIL-C-14982(MU).

5.2.2 Packing.

5.2.2.1 Level A and C. The cable assembly shall be packed in accordance with dwgs. 8851929 and 8808362 and MIL-C-14982(MU).

5.2.3 Marking. Marking shall be specified in 8851929 and 8808362 and MIL-C-14982(MU).

6.0 NOTES

6.1 Notes. Notes shall be in accordance with MIL-C-14982(MU) and as specified herein.

6.2 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship of the last previous issue.

Custodian
Army - MU

Preparing activity
Army - MU

Project No. 1195-A052

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.