MILITARY SPECIFICATION SHEET
CABLES FOR ATOMIC DEMOLITION CHARGES

W143-6 CABLE ASSEMBLY

The complete requirements for procuring the cable assembly described herein shall consist of this document and the latest issue of specification MIL-C-14982(MU).

1. SCOPE

1.1 This specification covers detail requirements, quality assurance provisions and preparation for delivery for production and repair parts for W143-6 Cable Assembly Training for use with Training Demolition Charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-14982(MU) - Cables for Training Atomic Demolition Charge, General Specification for

STANDARDS

MILITARY

MS-20470 - Rivet
MS-25281 - Clamp

DRAWINGS

ORDNANCE CORPS

8850948 - W143-6 Cable Assembly Training
8850963 - Connector
8850964 - Clip
8850965 - Insulator - Red
8850966 - Insulator - Black
8851137 - Cable 2 Conductor

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

8851852 - Molding Compound Polyurethane, Black
8851862 - Cap and Chain Assembly
8851901 - Primer Metal to Polyurethane
8851903 - Primer Polyurethane to B.Y.C
8851950 - Box Set-up, Paperboard for W143-6(TNG) Cable Assembly
8851981 - Molding Shell
EL-8850948 - Equipment List

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-C-14982(MU) and as specified herein.

3.2 Circuit resistance. The cable assembly circuit resistance shall be in accordance with table I.

Table I

Circuit resistance (see dwg 8850948)

From Connector	To Wire	Ohms Max
P143-8 Pin		
A	Red	0.2
B	Black	0.2

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-C-14982(MU) and as specified herein.

4.1.1 Sampling and inspection not applicable. The following classification of defects in MIL-C-14982(MU) is not applicable:

a. 4.3.2.1.4 Bag, packing, ammunition for cable assembly.

4.2 First article inspection.

4.2.1 Quantity to be submitted. In addition to quantities specified in 4.2.1 MIL-C-14982(MU), 3 sub-assemblies shall be submitted (see dwg 8850948 for W143-6 Cable Assembly Training before molding).

4.3 Classification of characteristics.

4.3.1 Clip (see dwg 8850964); insulator-red (see dwg 8850965); insulator black (see dwg 8850966) molding shell (see dwg 8851981); cap and chain assembly (see dwg 8851862); connector (see dwg 8850963); cable 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

conductor (see dwg 8851137); molding compound polyurethane, black (see dwg 8851852); primer metal to polyurethane (see dwg 8851901); primer polyurethane to B.Y.C. (see dwg 8851903); clamp (see MS25281-4W); rivet (see dwg MS20470-B4-7) covering details of dwg 8850948.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Objective evidence (see 6.3 MIL-C-14982(MU) available for part in accordance with applicable dwg or standard.....Visual

Minor:
201. Workmanship (see 3.12 MIL-C-14982(MU).....Visual/Manual

4.3.2 W143-6 cable assembly training (see dwg 8850948) before molding.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Primer applied to connector.....Visual
102. Primer applied to cable.....Visual

Minor: None defined.

4.3.3 W143-6 cable assembly training (see dwg 8850948).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Length.....*Measure
102. Length from mold wire ends to sleeve.....*Measure
103. Clamp tight on sleeve.....Manual
104. Length to end of mold from connector.....*Measure
105. Objective evidence (see 6.2) available for molding in accordance with dwg 8850948.....Visual
106. Marking.....Visual

*Measure with suitable scale.

Minor:
201. Serialization (see 3.5 MIL-C-14982(MU).....Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

4.4 Insulation resistance. The cable assembly insulation resistance shall be tested in accordance with table II.

Table II

Insulation resistance (see dwg 8850948)

Positive Pot Connector 143-8	All other pins, wires and shell except
A	Red wire
B	Black wire

5.0 PREPARATION FOR DELIVERY

5.1 Preparation for delivery for production cable assemblies. Preparation for delivery for production cable assemblies shall be in accordance with MIL-C-14982(MU).

5.2 Preparation for delivery for repair cable assemblies.

5.2.1 Preservation and packaging. Preservation and packaging shall be as specified in MIL-C-14982(MU).

5.2.1.1 Level A. The cable assembly shall be packaged in accordance with dwgs 8851950 and 8808362 and as specified in MIL-C-14982(MU).

5.2.1.2 Level C. The cable assembly shall be packaged in accordance with dwgs 8851950 and 8808362 and MIL-C-14982(MU).

5.2.2 Packing.

5.2.2.1 Level A and C. The cable assembly shall be packed in accordance with dwgs 8851950 and 8808362 and MIL-C-14982(MU).

5.2.3 Marking. Marking shall be as specified in dwgs 8851950 and 8808362 and MIL-C-14982(MU).

6.0 NOTES

6.1 Notes. Notes shall be in accordance with MIL-C-14982(MU).

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 1195-A030

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.