MILITARY SPECIFICATION SHEET
CABLES FOR ATOMIC DEMOLITION CHARGES

W143-7 CABLE ASSEMBLY

The complete requirements for procuring the cable assembly described herein shall consist of this document and the latest issue of specification MIL-C-14982(MU).

1. SCOPE

1.1 This specification covers detail requirements, quality assurance provisions and preparation for delivery for production and repair parts for W143-7 Cable Assembly Training for use with Training Atomic Demolition Charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-14982(MU) - Cables for Training Atomic Demolition Charge, General Specification for

STANDARDS

MILITARY

MS20470 - Rivet
MS25281 - Clamp

DRAWINGS

ORDNANCE CORPS

8850949 - W143-7 Cable Assembly Training

FSC 1195

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.

8850958 - Connector
8851134 - Cable 3 Conductor
8851852 - Molding Compound Polyurethane, Black
8851861 - Cap and Chain Assembly
8851901 - Primer Metal to Polyurethane
8851903 - Primer Polyurethane to B.Y.C.
8851951 - Box Set-up, Paperboard for W143-7 (TNG) Cable Assembly
EL-8850949 - Equipment List

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-C-14982(MU) and as specified herein.

3.2 Circuit resistance. The cable assembly circuit resistance shall be in accordance with Table I.

Table I

Circuit resistance (see dwg 8850949)

From Connector	To Connector	Ohms Max.
P 601 pin	P 301 pin	
2	2	0.2
4	4	0.2
5	5	0.2

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-C-14982(MU) and as specified herein.

4.1.1 Sampling and inspection not applicable. The following classification of defects in MIL-C-14982(MU) is not applicable:

a. 4.3.2.1.4 Bag, packing, ammunition for cable assembly.

4.2 First article inspection.

4.2.1 Quantity to be submitted. In addition to quantities specified in 4.2.1 MIL-C-14982(MU), 3 sub-assemblies shall be submitted (see dwg. 8850949) W143-7 Cable Assembly Training before potting .

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.

4.3 Classification of Characteristics.

4.3.1 Connector (see dwg 8850958); cap and chain assembly (see dwg 8851861); cable 3 conductor (see dwg 8851134); molding compound polyurethane black (see dwg 8851852); primer metal to polyurethane (see dwg 8851901); primer polyurethane to B.Y.C. (see dwg 8851903); clamp (see MS25281-6W); Rivet (see MS20470 B4-7) covering details of dwg 8850949).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Objective evidence (see 6.3 MIL-C-14982(MU) available for part in accordance with applicable dwg. or standard	Visual
Minor:		
201.	Workmanship (see 3.12 MIL-C-14982(MU)	Visual-Manual

4.3.2 W143-7 Cable assembly training (see dwg. 8850949) before potting.

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Primer applied to connectors	Visual
102.	Primer applied to cable	Visual
Minor: None defined.		

4.3.3 W143-7 Cable assembly training (see dwg. 8850949)

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Length	*measure
102.	Diameter of cable	gage
103.	Clamps tight	Manual
104.	Marking	Visual

*Measure with suitable scale

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.

Minor:
201. Serialization (see 3.5 MIL-C-14982(MU).....Visual

4.4 Insulation resistance. The cable assembly insulation resistance shall be tested in accordance with Table II.

Table II

Insulation resistance (see dwg. 8850949)

Connector	All other pins and shells except pins:
P 601	P 301
2	2
4	4
5	5

5.0 PREPARATION FOR DELIVERY

5.1 Preparation for delivery for production cable assemblies. Preparation for delivery for production cable assemblies shall be in accordance with MIL-C-14982(MU).

5.2 Preparation for delivery for repair cable assemblies.

5.2.1 Preservation and packaging. Preservation and packaging shall be as specified in MIL-C-14982(MU).

5.2.1.1 Level A. The cable assembly shall be packaged in accordance with dwgs. 8851951 and 8808362 and as specified in MIL-C-14982(MU).

5.2.1.2 Level C. The cable assembly shall be packaged in accordance with dwgs. 8851951 and 8808362 and MIL-C-14982(MU).

5.2.2 Packing.

5.2.2.1 Level A and C. The cable assembly shall be packed in accordance with dwgs. 8851951 and 8808362 and MIL-C-14982(MU).

5.2.3. Marking. Marking shall be as specified in dwgs. 8851951 and 8808362 and MIL-C-14982(MU).

6.0 NOTES

6.1 Notes. Notes shall be in accordance with MIL-C-14982(MU).

Custodian
Army - MU

Preparing activity
Army - MU
Project No. 1195-A046

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.