MILITARY SPECIFICATION SHEET
CABLES FOR ATOMIC DEMOLITION CHARGES

W143-9 CABLE ASSEMBLY

The complete requirements for procuring the cable assembly described herein shall consist of this document and the latest issue of specification MIL-C-14982(MU).

1. SCOPE

1.1 This specification covers detail requirements, quality assurance provisions and preparation for delivery for production and repair parts for W143-9 Cable Assembly Training for use with Training Atomic Demolition Charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-14982(MU) - Cables for Training Atomic Demolition Charge, General Specification for.

STANDARDS

MILITARY

MS15795 - Washer
MS16535 - Rivet
MS25281 - Clamp

FSC 1195

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.

DRAWINGS

ORDNANCE CORPS

8850951 - W143-9 Cable Assembly Training
8850963 - Connector
8850975 - Connector, Plug, Electrical
8850981 - Molding Shell
8851852 - Molding Compound Polyurethane, Black
8851856 - Cap and Chain Assembly
8851862 - Cap and Chain Assembly
8851901 - Primer Metal to Polyurethane
8851903 - Primer Polyurethane to B. Y. C.
8851953 - Box Set-up, Paperboard for W143-9(TNG) Cable Assembly
8881768 - Polyurethane Molding Compound
8881769 - Primer, Polyurethane Molding Compound
EL-8850951 - Equipment List

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements. - Requirements shall be in accordance with MIL-C-14982(MU), and as specified herein.

3.2 Circuit resistance. - The cable assembly circuit resistance shall be in accordance with Table I.

Table I
Circuit resistance (see dwg 8850951)

From Connector P 143-8 Pin	To Each Connector J 143-8 Pin	Ohms Max.
A	A	0.2
B	B	0.2
C	C	0.2

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. - Sampling and inspection shall be in accordance with MIL-C-14982(MU), and as specified herein.

4.1.1 Sampling and inspection not applicable. - The following classification of defects in MIL-C-14982(MU) is not applicable:

a. 4.3.2.1.4 Bag, packing, ammunition for cable assembly.

4.2 First article inspection.

4.2.1 Quantity to be submitted. - In addition to quantities specified in 4.2.1 MIL-C-14982(MU), 3 sub-assemblies shall be submitted (see dwg. 8850951) W143-9 Cable Assembly Training before molding.

4.3 Classification of Characteristics.

4.3.1 Cap and chain assembly (see dwgs 8851862 and 8851856); molding shell (see dwg. 8851981); connector (see dwgs 8850975 and 8850963); molding compound polyurethane black (see dwg. 8851852); primer metal to polyurethane (see dwg. 8851901); primer polyurethane to B. Y. C. (see dwg. 8851903); polyurethane molding compound (see dwg. 8881768); primer polyurethane molding compound (see dwg. 8881769); clamp (see MS25281); Rivet (see MS16535-160); Washer (see MS15795-204) covering details of dwg. 8850951.

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Objective evidence (see 6.3 MIL-C-14982(MU) available for part in accordance with applicable drawing or standard	Visual
Minor:		
201.	Workmanship (see 3.12 MIL-C-14982(MU)	Visual/Manual

4.3.2 W143-9 Cable Assembly training (see dwg. 8850951) before molding.

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Primer applied to connectors	Visual
102.	Primer applied to cable	Visual
Minor: None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.

4.3.3 W143-9 Cable assembly training (see dwg. 8850951).

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major:		
101.	Length of straight section	*Measure
102.	Length of legs	*Measure
103.	Clamps tight	Manual
104.	Materials (see 3.2 MIL-C-14982(MU)	Visual
105.	Marking	Visual

*Measure with suitable scale

Minor:

201.	Serialization (see 3.5 MIL-C-14982(MU)	Visual

4.4 Insulation resistance. - The cable assembly insulation resistance shall be tested in accordance with Table II.

Table II
Insulation resistance (see dwg 8850951)

Positive Pot. Connector P143-8 Pin	All other pins and shells minus potential except pins: Connectors J143-8 Pins
A	A
B	B
C	C

5.0 PREPARATION FOR DELIVERY

5.1 Preparation for delivery for production cable assemblies. - Preparation for delivery for production cable assemblies shall be in accordance with MIL-C-14982(MU).

5.2 Preparation for delivery for repair cable assemblies.-

5.2.1 Preservation and packaging. - Preservation and packaging shall be as specified in MIL-C-14892(MU).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.

5.2.1.1 Level A. The cable assembly shall be packaged in accordance with dwgs. 8851953 and 8808362 and as specified in MIL-C-14982(MU).

5.2.1.2 Level C. The cable assembly shall be packaged in accordance with dwgs. 8851953 and 8808362 and MIL-C-14982(MU).

5.2.2 Packing.

5.2.2.1 Level A and C. The cable assembly shall be packed in accordance with dwgs. 8851953 and 8808362 and MIL=C-14982(MU).

5.2.3 Marking. Marking shall be as specified in dwgs. 8851953 and 8808362 and MIL-C-14982(MU).

6.0 NOTES

6.1 Notes. Notes shall be in accordance with MIL-C-14982(MU).

Custodian
Army - MU

Preparing activity
Army -MU
Project No. 1195-A031

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.