MILITARY SPECIFICATION SHEET
CABLES FOR ATOMIC DEMOLITION CHARGES

W143-10 CABLE ASSEMBLY

The complete requirements for procuring the cable assembly described herein shall consist of the document and the latest issue of specification MIL-C-14982(MU).

1. SCOPE

1.1 This specification covers detail requirements, quality assurance provisions and preparation for delivery for production and repair parts for W143-10 Cable Assembly Training for use with Training Atomic Demolition Charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-14982(MU) - Cables for Training Atomic Demolition Charge, General Specification for

STANDARDS

MILITARY

MS 15795 - Washer
MS 20470 - Rivet
MS 25281 - Clamp

DRAWINGS

ORDNANCE CORPS

8850952 - W143-10 Cable Assembly
8850958 - Connector
8850973 - Connector
8851858 - Cap and Chain Assembly
8851861 - Cap and Chain Assembly
8851954 - Box Set-up, Paperboard for W143-10 (TNG) Cable Assembly
E1-8850952 - Equipment List

FSC 1195

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.

(Copies of specifications, drawings, standards, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Requirements. - Requirements shall be in accordance with MIL-C-14982(MU) and as specified herein.

3.2 Circuit resistance. - The cable assembly circuit resistance shall be in accordance with Table I.

Table I
Circuit resistance (see dwg 8850952)

From Connector	To Connector	Ohms Max
P601 pin	P13-2 pin	
2	A	0.2
4	B	0.2

4. 4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. - Sampling and inspection shall be in accordance with MIL-C-14982(MU) and as specified herein.

4.1.1 Sampling and inspection not applicable. - The following classification of defects in MIL-C-14982(MU) is not applicable:

a. 4.3.2.1.4 Bag, packing, ammunition for cable assembly.

4.2 First article inspection.

4.2.1 Quantity to be submitted. - In addition to quantities specified in 4.2.1 MIL-C-14982(MU), 3 sub-assemblies shall be submitted (see dwg 8850952) W143-10 Cable Assembly, Training before potting and molding.

4.3. Classification of Characteristics.

4.3.1 Cap and chain assembly (see dwgs 8851858 and 8851861); Connector (see dwgs 8850958 and 8850973); Clamp (see MS25281-R4); Rivet (see MS20470 AD 4-6); Washer (see MS15795-204)covering details of dwg 8850952.

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major:		
101.	Objective evidence (see 6.3 MIL-C-14982(MU) available for part in accordance with applicable specification or drawing.....	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.

Minor:

201. Workmanship (see 3.12 MIL-C-14982(MU).....Manual

4.3.2 W143-10 Cable assembly, training (see dwg 8850952) before potting and molding. -

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major:		
101.	Primer applied to connectors	Visual
102.	Primer applied to cable	Visual
Minor:	None defined	

4.3.3 W143-10 Cable assembly training (see dwg. 8850952).

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major:		
101.	Length	*Measure
102.	Length from connector to end of mold	*Measure
103.	Diameter of mold	*Measure
104.	Marking	Visual
105.	Materials (see 3.2 MIL-C-14982(MU)	Visual
106.	Sleeving tied both ends	Visual
107.	Length of jacket covered by molding compound	*Measure
108.	Wires twisted	Visual
109.	Clamps tight	Manual

*Measure with suitable scale

Minor:

201. Serialization (see 3.5 MIL-C-14982(MU)......Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.

4.4 Insulation resistance. - The cable assembly insulation resistance shall be tested in accordance with Table II.

Table II
Insulation resistance (see dwg 8850952)

Positive Pot. to Connector	All other pins and shells minus potential except pins.
P601	Connector P13-2
Pin	Pin
2	A
4	B

5.0 PREPARATION FOR DELIVERY

5.1 Preparation for delivery for production cable assemblies.- Preparation for delivery for production cable assemblies shall be in accordance with MIL-C-14982(MU).

5.2 Preparation for delivery for repair cable assemblies.

5.2.1 Preservation and packaging. - Preservation and packaging shall be as specified in MIL-C014982(MU).

5.2.1.1 Level A. - The cable assembly shall be packaged in accordance with dwgs 8851954 and 8808362, and as specified in MIL-C-14982(MU).

5.2.2 Packing.

5.2.2.1 Level A and C. - The cable assembly shall be packed in accordance with dwg 8851954 and 8808362 and MIL-C-14982(MU).

5.2.3 Marking. - Marking shall be as specified in dwg 8851954 and 8808362 and MIL-C-14982(MU).

6.0 NOTES

6.1 Notes. - Notes shall be in accordance with MIL-C-14982(MU).

Custodian
Army MU

Preparing activity
Army-MU
Project No. 1195-A047

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.