MILITARY SPECIFICATION SHEET
CABLES FOR ATOMIC DEMOLITION CHARGES

T-4140 CABLE ASSEMBLY

The complete requirements for procuring the cable assembly described herein shall consist of the document and the latest issue of specification MIL-C-14982(MU).

1. SCOPE

1.1 This specification covers detail requirements, quality assurance provisions and preparation for delivery for production and repair parts for T-4140 Cable Assembly, Training for use with Training Atomic Demolition Charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

W-C-440 - Clip, Electrical, Jaw Grip

MILITARY

MIL-C-14982(MU) - Cables for Training Atomic Demolition Charge, General Specification for
MIL-C-23329/4 - Connector, Coaxial, Radio Frequency, Series TNC

STANDARDS

MILITARY

MS21470 - Rivet
MS25281 - Clamp

DRAWINGS

ORDNANCE CORPS

8838904 - Cap with Chain, Dust
8850954 - T-4140 Cable Assembly, Training

FSC 1195

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.

8850972 - Connector, Plug, Electrical
8851943 - Box Set-Up, Paperboard for T-4140 (TNG) Cable Assembly Special Branched
8881768 - Polyurethane Molding Compound
8881769 - Primer, Polyurethane Molding Compound
9207508 - Primer, Polyurethane Molding Compound
EL-8850954 - Equipment List

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-C-14982(MU) and as specified herein.

3.2 Circuit resistance. The cable assembly circuit resistance shall be in accordance with table I.

Table I

Circuit resistance

From Connector P4-1 pin	To Connector P5-2	To Clip	Ohms Max
F	Pin		0.2
A	Shell		0.2
D		Red	0.2
C		Black	0.2

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-C-14982(MU) and as specified herein.

4.1.1 Sampling and inspection not applicable. The following classification of defects in MIL-C-14982(MU) is not applicable:

a. 4.3.2.1.4 Bag, packing, ammunition for cable assembly.

4.2 First article inspection.

4.2.1 Quantity to be submitted. In addition to quantities specified in 4.2.1 MIL-C-14982(MU), 3 sub-assemblies shall be submitted (see dwg 8850954) T-4140 Cable Assembly, Training before potting and molding.

4.3 Classification of characteristics.

4.3.1 Connector, plug, electrical (see dwg 8850972); primer polyurethane molding compound (see dwgs 8881769 and 9207508); polyurethane molding compound (see dwg 8881768); clamp (see MS25281-F2); Rivet (see MS20470B4-7);

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.

Cap with chain, dust (see 8838904); connector (see MS233329/4-04) covering details of dwg 8850954.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Objective evidence (see 6.3 MIL-C-14982(MU) available for part in accordance with applicable dwg or standard...Visual

Minor:
201. Workmanship (see 3.12 MIL-C-14982(MU).....Visual/Manual

4.3.2 T-4140 cable assembly training (see dwg 8850954) before potting or molding.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Primer applied to connectors.....Visual
102. Primer applied to cable.....Visual

Minor: None defined.

4.3.3 T-4140 cable assembly training (see dwg 8850954).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Length between connectors.....*Measure
102. Length of sleeving.....*Measure
103. Length from connector to end of clip.....*Measure
104. Clamps tight.....Manual
105. Objective evidence (see 6.3 MIL-C-14982(MU) available for connector in accordance with MIL-C-23329/4.....Visual
106. Objective evidence (see 6.3 MIL-C-14982(MU) available for clip in accordance with W-C-440.....Visual
107. Materials (see 3.2 MIL-C-14982(MU).....Visual
108. Marking.....Visual

*Measure with suitable scale

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.

Minor:
201. Serialization (see 3.5 MIL-C-14982(MU).....Visual

4.4 Insulation resistance. The cable assembly insulation resistance shall be tested in accordance with table II.

Table II

Insulation resistance (see dwg 8850954)

Positive Pot. to Connector P4-1 Pin	All other pins and shells minus potential except pins or clips:
F	Connector P5-2 pin
A	Connector P5-2 shell
D	Red clip
C	Black clip

5.0 PREPARATION FOR DELIVERY

5.1 Preparation for delivery for production cable assemblies. Preparation for delivery for production cable assemblies shall be in accordance with MIL-C-14982(MU).

5.2 Preparation for delivery for repair cable assemblies.

5.2.1 Preservation and packaging. Preservation and packaging shall be as specified in MIL-C-14982(MU).

5.2.1.1 Level A. The cable assembly shall be packaged in accordance with dwgs 8851943 and 8808362 and as specified in MIL-C-14982(MU).

5.2.1.2 Level C. The cable assembly shall be packaged in accordance with dwgs 8851943 and 8808362 and MIL-C-14982(MU).

5.2.2 Packing.

5.2.2.1 Level A and C. The cable assembly shall be packed in accordance with dwgs 8851943 and 8808362 and MIL-C-14982(MU).

5.2.3 Marking. Marking shall be as specified in dwgs 8851943 and 8808362 and MIL-C-14982(MU).

6.0 NOTES

6.1 Notes. Notes shall be in accordance with MIL-C-14982(MU).

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 1195-A032

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.