MILITARY SPECIFICATION SHEET
CABLES FOR ATOMIC DEMOLITION CHARGES

CABLE ASSEMBLY XM6 ANTENNA

The complete requirements for procuring the cable assembly described herein shall consist of this document and the latest issue of specification MIL-C-14982(MU).

1. SCOPE

1.1 This specification covers detail requirements, quality assurance provisions and preparations for delivery for production and repair parts for Cable Assembly XM6 Antenna for use with Training Atomic Demolition Charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-14982(MU) - Cables for Training Atomic Demolition Charge, General Specification for

STANDARDS

MILITARY

MS15795 - Washer
MS204790 - Rivet

DRAWINGS

ORDNANCE CORPS

8800545 - Bag Packing Ammunition, for Cable Assembly
8850956 - Cable Assembly XM6 Antenna
8851083 - Calmp, Support Cable
8851135 - Coax Cable

FSC 1195

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.

8851666 - Connector
8851901 - Primer Metal to Polyurethane
9214694 - Cover, Electrical
9214703 - Connector, Plug Electrical
EL-8850956 - Equipment List

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-C-14982(MU) and as specified herein.

3.2 Circuit resistance. The cable assembly circuit resistance shall be in accordance with table I.

Table I

Circuit resistance (see dwg 8850956)

From	To	Ohms Max
8851666	9214703	
Pin	Pin	1.0
Shell	Shell	1.0

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-C-14982(MU) and as specified herein.

4.1.1 Sampling and inspection not applicable. The following classification of defects in MIL-C-14982(MU) are not applicable:
a. 4.3.2.1.5 Box. Set-up paperboard for applicable cable assembly.

4.2 First article inspection.

4.2.1 Quantity to be submitted. In addition to quantities specified in 4.2.1 MIL-C-14982(MU), 3 sub-assemblies shall be submitted (see dwg 8850956) Cable Assembly XM6 Antenna before potting.

4.3 Classification of characteristics.

4.3.1 Connector (see dwgs 8851666 and 9214703); cable (see dwg 8851135); cable clamp (see dwg 8851083); cover electrical (see dwg 9214694); primer metal to polyurethane (see dwg 8851901); rivet (see MS20470B6-7); and washer (see MS15975-204) covering details of dwg 8850956.

Categories	Characteristics	Method of inspection
Critical: None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.

Major:
101. Objective evidence (see 6.3 MIL-C-14982(MU)) available for part in accordance with applicable drawing or standard.....Visual

Minor:
201. Workmanship (see 3.12 MIL-C-14982(MU)).....Visual/Manual

4.3.2 Cable assembly XM6 antenna (see dwg 8850956) before potting.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Primer applied to connectors.....Visual
102. Materials (see 3.2 MIL-C-14982(MU)).....Visual
103. Adhesive on collet clamp after combing.....Visual
104. Adhesive application to collet and nut.....Visual

Minor: None defined.

4.3.3 Cable assembly XM6 antenna (see dwg 8850956).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Length.....*Measure
102. Length of mold.....*Measure
103. Length of large diameter of mold.....*Measure
104. Length of tapered diameter of mold.....*Measure
105. Small mold diameter.....Gage
106. Large mold diameter.....Gage
107. Marking.....Visual
108. Clamp tight on cable.....Manual
109. Objective evidence (see 6.3 MIL-C-14982(MU)) available for potting compound in accordance with drawing note.....Visual

*Measure with suitable scale

Minor: None defined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.

4.4 Insulation resistance. The cable assembly insulation resistance shall be tested in accordance with table II.

Table II

Insulation resistance (see dwg 8850956)

Positive Pot. to 8851666 Pin	Negative potential to shells

5.0 PREPARATION FOR DELIVERY

5.1 Preparation for delivery for production cable assemblies. Preparation for delivery for production cable assemblies shall be in accordance with MIL-C-14982(MU).

5.2 Preparation for delivery for repair cable assemblies.

5.2.1 Preservation and packaging. Preservation and packaging shall be as specified in MIL-C-14982(MU).

5.2.1.1 Level A. The cable assembly shall be packaged in accordance with dwgs 8800545 and 8808362 and as specified in MIL-C-14982(MU).

5.2.1.2 Level C. The cable assembly shall be packaged in accordance with dwg 8808362 and MIL-C-14982(MU).

5.2.2 Packing.

5.2.2.1 Level A and C. The cable assembly shall be packed in accordance with dwgs 8800545 and 8808362 and MIL-C-14982(MU).

5.2.3 Marking. Marking shall be as specified in dwgs 8800545 and 8808362 and MIL-C-14982(MU).

6.0 NOTES

6.1 Notes. Notes shall be in accordance with MIL-C-14982(MU).

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 1195-A034

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.