MILITARY SPECIFICATION SHEET

CABLES FOR ATOMIC DEMOLITION CHARGES

CABLE ASSEMBLY FIRING DEVICE

The complete requirements for procuring the cable assembly described herein shall consist of this document and the latest issue of specification MIL-C-14982(MU).

1. SCOPE

1.1 This specification covers detail requirements, quality assurance provisions and preparation for delivery for production and repair parts for Cable Assembly Firing Device for use with Training Atomic Demolition Charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-14982(MU) - Cables for Training Atomic Demolition Charge, General Specification for
MIL-S-60902(MU) - Soldering Electrical Connections for Nuclear Weapons Systems, Procedure for

STANDARDS

MILITARY

MS25036 - Terminal Ring Solderless

DRAWINGS

ORDNANCE CORPS

8800546 - Bag Packing Ammunition for Cable Assembly
8851127 - Cable Assembly Firing Device
8851185 - Connector
EL-8851127 - Equipment List

FSC 1195

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-C-14982(MU) and as specified herein.

3.1.1 Requirements not applicable. The humidity requirement in MIL-C-14982 is not applicable.

3.2 Circuit resistance. The cable assembly circuit resistance shall be in accordance with table I.

Table I

Circuit resistance (see dwg 8851127)

From	To J42-1 Connector Pin	Ohms Max
Black wire terminal	L	0.2
Black wire terminal	K	0.2
Black wire terminal	J	0.2
Black wire terminal	F	0.2
Brown wire terminal	M	0.2
Brown wire terminal	H	0.2
Brown wire terminal	G	0.2
End of orange wire	E	0.2
End of yellow wire	B	0.2

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-C-14982(MU) and as specified herein.

4.1.1 Sampling and inspection not applicable. The following inspections in MIL-C-14982(MU) are not applicable:

a. Quantity to be submitted (see 4.2.1). No subassemblies are required.
b. Inspection and testing to be performed (see 4.2.2). Table I delete Humidity test only.
c. All cables before potting or molding (see 4.3.2.1.1).
d. All cables after potting and molding when potting or molding is required (see 4.3.2.1.2).
e. Box, set-up paperboard for applicable cable assembly (see 4.3.2.1.5).
f. Humidity (see 4.4.6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.

4.2 Classification of characteristics.
4.2.1 Cable assembly firing device (see dwg 8851127).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Length of wire loop	*Measure
102.	Length of black terminal wire	*Measure
103.	Length of brown terminal wire	*Measure
104.	Length of orange wire	*Measure
105.	Length of yellow wire	*Measure
106.	Objective evidence (see 6.3 MIL-C-14982(MU)) available for wire in accordance with dwg 8851127	Visual
107.	Objective evidence (see 6.3 MIL-C-14982(MU)) available for connector in accordance with dwg 8851185	Visual
108.	Objective evidence (see 6.3 MIL-C-14982(MU)) available for terminal in accordance with MS25036-102	Visual
109.	Soldering in accordance with MIL-S-60902(MU)	Visual/Manual

*Measure with suitable scale

Minor:		
201.	Workmanship (see 3.12 MIL-C-14982(MU))	Visual/Manual

4.3 Insulation resistance. The cable assembly insulation resistance shall be tested in accordance with table II.

Table II

Insulation resistance (see dwg 8851127)

Positive Potential to	Negative potential to all other pins, terminals and connector shell except:
Black Wire Terminal	Connector pins F, J, K, L
Brown Wire Terminal	M, H, G
Connector pin E	
Connector pin B	

5.0 PREPARATION FOR DELIVERY

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.

5.1 Preparation for delivery for production cable assemblies. Preparation for delivery for production cable assemblies shall be in accordance with MIL-C-14982(MU).

5.2 Preparation for delivery for repair cable assemblies.

5.2.1 Preservation and packaging. Preservation and packaging shall be as specified in MIL-C-14982(MU).

5.2.1.1 Level A. The cable assembly shall be packaged in accordance with dwgs 8800546 and 8808362 and as specified in MIL-C-14982(MU).

5.2.1.2 Level C. The cable assembly shall be packaged in accordance with dwg 8808362 and MIL-C-14982(MU).

5.2.2 Packing.

5.2.2.1 Levels A and C. The cable assembly shall be packed in accordance with dwgs 8800546 and 8808362 and MIL-C-14982(MU).

5.2.3 Marking. Marking shall be as specified in dwgs 8800546 and 8808362 and MIL-C-14982(MU).

6.0 NOTES

6.1 Notes. Notes shall be in accordance with MIL-C-14982(MU).

Custodian:
Army - MU

Preparing agency:
Army - MU

Project No. 1195-A035

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:16Z
Check the source to verify that this is the current version before use.