INCH-POUND

MIL-D-14978A (AR)
AMENDMENT 4
3 May 89

SUPERSEDING
AMENDMENT 3
24 January 1989

MILITARY SPECIFICATION

DETONATOR, STAB, M55
LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-D-14978A (MU), dated 30 October 1972, and is approved for use within the US Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1 SPECIFICATIONS, MILITARY: Add the following:

"MIL-L-10547 - Liner, case, and sheet, Overwrap, Water Vaporproof or Waterproof, Flexible"

PAGE 2

Paragraph 2.1

Delete: "ET - #8798331 - Equipment Tabulation"

2.1:
DRAWINGS: Add the following:

"8794342 - Seal, Metallic, Assembly, Details and Instructions For Application
8796522 - Marking Diagram and Sealing for Wood Packing Boxes
8799112 - Marking Diagram and Sealing for Interplant or CONUS Shipment of Ammunition Fibreboard Boxes
9258182 - Box, Set-up, Packing, Ammunition, Inner, for Small Explosive Components
9258183 - Box, Set-up, Alternative, Packing, Ammunition, Outer, for Small Explosive Components
9258184 - Box, Alternative, Packing, Ammunition, for Small Explosive Components"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:14Z
Check the source to verify that this is the current version before use.

PUBLICATIONS: Add the following new reference:
"Navy MK95 PD WS 4997"

PAGE 3

3.4.1 Delete this paragraph in its entirety and substitute the following:

"3.4.1 Sensitivity and energy output. The detonators shall function satisfactorily as evidenced by a depression in the steel disc of a minimum depth of 0.010 inch when tested as specified in 4.4.3.2."

PAGE 5

4.2.2.1 Delete this paragraph in its entirety and substitute the following:

"4.2.2.1 Sensitivity and energy output (see 3.4.1). Three hundred fifteen (315) detonator assemblies shall be subjected to this test. If four (4) or more assemblies fail to comply with the applicable requirement, the first article sample shall be rejected. The test shall be performed as specified in 4.4.3.2."

PAGE 7

4.3.2.2 Major defects. Delete "103" in its entirety.

PAGE 8

4.3.2.3 Critical defects. Delete "1. and 4." in their entirety and substitute the following:

"1. Felt cushion missing (not applicable to alternate cork cushion)."

4. Slide cover assembly reversed (not applicable to alternate design)."

PAGE 10

4.3.3.3.1 Delete this paragraph in its entirety and substitute the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:14Z
Check the source to verify that this is the current version before use.

"4.3.3.3.1 Sensitivity and energy output. Major defect (see 3.4.1.) Sampling shall be in accordance with MIL-STD-105, Normal Inspection, Table III-A, using a sampling code letter P and an AQL of 0.40%. The provisions of paragraph 8 of MIL-STD-105, regarding reduced or tightened inspection shall apply. Testing shall be as specified in 4.4.3.2 (Code No. 09001)."

PAGE 11

Paragraph 4.3.4;

Delete: "ET - #8798331 - Equipment Tabulation"

PAGE 12

Add the following new paragraphs:

* 4.4.1.1 Determination of moisture content of lead azide, alternate method (see 4.3.3.1). - The procedure is the same as paragraph 4.4.1 with the following exception. The sample shall be dried in a vacuum oven at a temperature of 95 + 5°C and a pressure of 80 ± 10mm of mercury for 45 minutes.

* 4.4.2.1.1 Moisture content, alternate method (See 4.3.3.2).- The procedure is the same as paragraph 4.4.2.1 with the following exception. The sample shall be dried in a vacuum oven at a temperature of 60 ± 5°C and a pressure of 80 ± 10mm of mercury for 45 minutes.

4.4.3.1 Delete this paragraph in its entirety.

4.4.3.3 Delete this paragraph in its entirety and substitute the following:

"4.4.3.3 Waterproofness. The detonators shall be immersed in water to a depth of not less than two inches but not more than three inches for a period of 48 hours, minimum. Both the water and the detonators shall be within the temperature range of 60° to 80°F throughout the test. Within one hour after removal from the water, the detonators shall be tested according to the test procedure for functioning (see 4.4.3.2)."

PAGE 16

Delete Section 5 in its entirety and substitute the following:

"5. PACKAGING

5.1 Preservation and packaging.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:14Z
Check the source to verify that this is the current version before use.

5.1.1 Level A.

5.1.1.1 Unit package. The detonators shall be preserved and packaged in accordance with dwg 9258182, sheets 1 and 2.

5.1.1.2 Intermediate packaging. The detonators shall be preserved and packaged in accordance with dwg 9258183, sheets 1 and 2.

5.1.2 Level B - same as level A.

5.1.2.1 Unit package. Same as level A.

5.1.2.2 Intermediate package. Same as level A.

5.1.3 Level C - same as level A.

5.1.3.1 Unit package. Same as Level A.

5.1.3.2 Intermediate package. Same as Level A.

5.2 Packing.

5.2.1 Level A. The detonators shall be packed in accordance with dwg 9258184, sheets 1 and 2 except Box, Packing shall be Grade A, Type II, Class 1. A metallic seal (dwg 8794342) in both boxes is mandatory. A caseliner conforming to Type I, Grade A material, Specification MIL-L-10547 is required when cushioning is used between the exterior box and outer set-up boxes. Appropriate size fillers for End, Side, Bottom and Top shall be placed between the caseliner and exterior box. After inserting required number of outer set-up boxes in liner, close and seal in accordance with Specification MIL-L-10547.

5.2.2 Level B - same as level A.

5.2.2.1 Unit pack. Same as Level A.

5.2.2.2 Intermediate pack. Same as Level A.

5.2.3 Level C.

5.2.3.1 Unit package. Unit package shall be in accordance with dwg 9258182.

5.2.3.1.2 Intermediate package. Intermediate package shall be in accordance with dwg 9258184, sheets 1 and 2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:14Z
Check the source to verify that this is the current version before use.

5.2.3.1.3 Alternative. Alternatives No. 1 and No. 2. Exterior Packing shall be in accordance with dwg 9258184, sheets 1 and 2.

5.3 Marking

5.3.1 Level A. Level A shall be marked, stamped and sealed in accordance with dwg 8796522 and instructions shown on dwg 9258184, sheets 1 and 2.

5.3.2 Level B. Same as Level A.

5.3.3 Level C. Box and Alternative Box No. 1 shall be marked and strapped in accordance with dwg 8796522. Box, alternate No. 2 shall be marked and sealed in accordance with dwg 8799112.

5.4 Shipping - When components from more than one lot are shipped as a carload, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing of lots in transit."

PAGE 19

Add the following new paragraphs:

"6.6 Navy procurement orders. Manufactured to Army Spec MIL-D-14978A, additionally incorporating environmental tests required per paragraph 4.2.3, 4.2.4 and figure 3 of the MK95 purchase description WS 4997 with skip lot acceptance modified as follows: Upon successful testing of the initial lot, begin periodic environmental skip lot testing using a group of five lots, and subsequently using groups of nine lots - should a lot fail, reliability must be reestablished by successfully testing two successive lots prior to resumption of skip lot testing as described above.

6.6.1 Detonator identification. Those "Navy" M55 detonators manufactured in accordance with paragraph 6.6 will be specifically identified prior to shipping - method to be determined by manufacturing AAP.

6.6.2 Test report distribution. The "Navy" M55 detonator test reports including lot acceptance tests shall be distributed to: Naval Surface Weapons Center, White Oak, Silver Spring, MD (NSWGWQ) codes G43 and G44, 20907 and to Pacific Missile Test Center, Pt Mugu, CA, code 2141, 93042.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:14Z
Check the source to verify that this is the current version before use.

MIL-D-14978A (AR)
AMENDMENT 4

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1375-A427)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:14Z
Check the source to verify that this is the current version before use.