SUPERSEDING
PA-PD-2295
22 December 1965

MILITARY SPECIFICATION

SETTING DEVICE, TIMER: H4195

1. SCOPE

1.1 This specification covers special requirements not included on the drawings, and provides the quality assurance provisions for the fabrication of parts, assembling, and the preparation for delivery for one type of setting device used to set timer on XM454 and XM455 projectiles and designated as Setting Device, Timer: H4195.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

PPP-B-636 - Box, Fiberboard

MILITARY

MIL-B-117 - Bags and sleeves, interior packaging

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168 - Lot Numbering of Ammunition

DRAWINGS

ORDNANCE CORPS

8808362 - Packing and Marking for Storage and Shipments
8857570 - Setting Device Timer: H4195

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:19Z
Check the source to verify that this is the current version before use.

8864706 - Socket, Allen Type Screw
8864708 - Adapter
8864709 - Wrench Reversible Ratchet

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.2 Assembly. The setting device shall comply with all requirements specified on Drawing (dwg.) 8857570, with all requirements specified herein, and with the requirements of applicable specifications to the extent specified on the drawing and herein.

3.3 Workmanship.

3.3.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristics.

3.3.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.3.3 Burrs. Parts shall be free from burrs.

3.3.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.3.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agents.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection. Not applicable.

4.3 Product acceptance inspection.

4.3.1 Lot formation. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:19Z
Check the source to verify that this is the current version before use.

4.3.1.1 Inspection lot. An inspection lot shall be the quantity of parts, subassemblies, or assemblies from the same lot, which are submitted to inspection for Government acceptance.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table and inspected for all characteristics in the applicable classification. Any characteristic in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Major Characteristic table I		Minor Characteristic table II	
Lot size	Sample size	Lot size	Sample size
1- 155	100% inspection	1- 25	100% inspection
156- 200	155	26- 30	25
201- 250	175	31- 35	26
251- 300	190	36- 40	27
301- 350	200	41- 45	28
351- 400	210	46- 50	29
401- 450	220	51- 55	30
451- 500	225	56- 60	31
501- 550	230	61- 65	32
551- 600	235	66- 70	33
601- 650	240	71- 75	34
651- 700	243	76- 85	35
701- 750	247	86- 95	36
751- 800	250	96- 110	37
801- 900	254	111- 130	38
901-1000	258	131- 156	39
1001-1100	261	157- 190	40
1101-1200	264	191- 240	41
1201-1300	266	241- 340	42
1301-1400	268	341- 520	43
1401-1500	270	521-1120	44
1501-1600	272	1121 and over	45

4.3.2.1 Classification of characteristics. Critical, major, and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Socket, allen type screw (see dwg 8864706), adapter (see dwg 8864708) wrench reversible ratchet (see dwg 8864709) covering details of dwg 8857570.

Categories	Characteristics	Method of inspection
Critical: None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:19Z
Check the source to verify that this is the current version before use.

Major:
101. Objective evidence (see 6.2) available for parts in accordance with applicable drawing.....Visual

Minor:
201. Workmanship (see 3.3).....Visual/Manual

4.3.2.1.2 Setting device, timer: M195 (see dwg 8857570).

Categories	Characteristics	Method of inspection
Critical:		
1.	Direction of wrench drive (see dwg 8864709).....	Manual
Major:		
101.	No part missing.....	Visual
Minor:		
201.	Stamping.....	Visual
202.	Workmanship (see 3.3).....	Visual/Manual

4.3.2.1.3 Carton, packing, ammunition, for fuze setter: M195 (see dwg 8865342 and section 5.)

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Objective evidence (see 6.2 available for packaging materials in accordance with the applicable specification.....	Visual
102.	Item wrapped with wrapper and wrapper secured with tape.....	Visual
103.	Location of bag seal.....	Visual
104.	Heat seal in accordance with MIL-B-117.....	Visual/Manual
105.	Carton sealed in accordance with PPP-B-636.....	Visual
106.	Label waterproofed.....	Visual
Minor:		
201.	Marking.....	Visual
202.	Workmanship (see 3.3).....	Visual/Manual

4.3.2.1.4 Packing and marking for storage and shipments (see dwg 8808362 and section 5).

Categories	Characteristics	Method of inspection
Critical: None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:19Z
Check the source to verify that this is the current version before use.

Major:
101. Gross load weight, max.....*Measure
102. Contents tight in package.....Manual
103. Correctly packed.....Visual/Manual
104. Package material (see 3.1).....Visual

*Determine weight with a suitable scale.

Minor:
201. Marking.....Visual
202. Workmanship (see 3.3).....Visual/Manual

4.3.3 Testing. Not applicable.
4.3.4 Acceptance inspection equipment. Not applicable.
4.4 Test methods. Not applicable.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).
5.1.1 Level A. The setting device shall be packaged in accordance with dwg 8865342 and dwg 8808362 using the specified moisture barrier.
5.1.2 Level C. The setting device shall be packaged in accordance with dwgs 8865342 and 8808362 except that the moisture barrier may be omitted.
5.2 Packing.
5.2.1 Level A and C. The setting device shall be packed in accordance with dwgs 8865342 and 8808362.
5.3 Marking. Marking shall be as specified on dwgs 8865342 and 8808362.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:
a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).
6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 1190-A004

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:19Z
Check the source to verify that this is the current version before use.