MIL-W-14980A (AR)
24 September 1979
SUPERSEDING
MIL-W-14980 (MU)
16 April 1971

MILITARY SPECIFICATION

WARHEAD, GUIDED MISSILE, HE, M224 PARTS FOR

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not covered by the drawings and provides quality assurance provisions for the fabrication of parts, assembly and packing of one type of warhead designated as Warhead, Guided Missile, HE, M224.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents.-The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-5541 - Chemical Films and Chemical Film Materials for Aluminum and Aluminum Alloys
MIL-C-45662 - Calibration System Requirements
MIL-A-48078 - Ammunition Standard Quality Assurance Provisions, General Specification For

FSC: 1336

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

DRAWINGS (see 6.5)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

9216776	- Warhead, GM, HE, M224 Metal Parts Assembly
9226389	- Carton, Packing, Ammunition, for Warhead Section (DRAGON)
8799112	- Marking Diagram and Sealing for Interplant or CONUS Shipment of Ammunition Fiberboard Boxes

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publication.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIAL (ASTM)

ASTM B-117-73	- Salt Spray (Fog) Testing Method of Test For
ASTM D-1002-72	- Strength Properties of Adhesives in Shear by Tension Loading (Metal-to-Metal)

(Applications for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa. 19102).

3. REQUIREMENTS

3.1 Materials.-Materials shall be in accordance with the applicable drawings and specifications.

3.2 Components and assemblies.-The components and assemblies shall comply with all requirements specified on drawing (dwg.) 9216776 and associated drawings and with all requirements specified in applicable standards and specifications.

3.3 Airtightness of warhead metal parts assembly (dwg 9216776.-The explosive cavity of the warhead metal parts assembly shall be airtight and shall show no observable drop in pressure level for a period not less than 10 seconds (sec.) in duration, at an internal pressure within the cavity of 5.0 pounds per square inch gage (psig) $\pm$ 0.5 psig when tested as specified in 4.5.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

3.4 Cone-body cleaning process qualification.-The cone-body cleaning process shall be qualified when a simulated cone-body joint exhibits the capability of producing an adhesive joint with an individual shear strength of 300 psi, min. and an average shear strength of 500 psi, min.

3.5 Protective finish.-The protective finishes of the Warhead Body and the attendant test panels shall comply with the requirements of dwg. 9261777 and the associated specifications.

3.6 Data requirements.-The contractor shall generate data in accordance with the requirements of the data description cited in 6.4.

3.7 First article inspection.-This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.8 Workmanship.-The parts and assemblies shall be free from chips, burrs, sharp and chipped edges, cracks, dents, gouges, tool marks, warpage, rust, dirt, grease and other foreign matter that might impair proper functioning. The cleaning method used shall not be injurious to any of the parts nor shall the parts be contaminated by cleaning solutions. Surface coatings shall be continuous except for scratches not exposing base metal.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions.-Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections.-The following types of inspection shall be conducted on this item.

a. First article inspection

b. Quality conformance inspection

4.3 First article inspection

4.3.1 Submission.-The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

Part Description	Drawing	Quantity
Warhead Metal Parts Assembly	9216776	10
Warhead Body	9216777	6
Warhead Body - Protective Finish Chromate Film Test Panels	--	12
Warhead Cone	9216779	6
Closure Cup	9298830	6
Carton, Packing, Ammunition for Warhead Section (DRAGON)	9226389	3
Marking Diagram and Sealing for Interplant or CONUS Shipment of Ammunition Fiberboard Boxes	8799112	3

4.3.2 Inspections to be performed.-See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection.-See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-14980A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
	Warhead Metal Parts and Assembly				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cone, Warhead (Dwg. 9216779				
	Examination of Defects	6		3.2	4.4.2.1
	Wall Thickness Variation (3 transverse planes between Datums A and B)	6		3.2	4.5.2
	Body, Warhead (Dwg. 9216777)				
	Examination for Defects	6		3.2	4.4.2.2
	Body interior protective finish	3		3.5	4.5.5
	Chromate finish test panels	12 (a)		3.5	4.5.5
	Warhead, M224, Metal Parts Assembly (Dwg. 9216776)				
	Examination for Defects	10		3.2	4.4.2.3
	Air Leakage Test - Cone to Body Seal	10		3.3	4.5.3
	Pull Test - Test Panels	10		3.4	4.5.4
	Closure Cup (Dwg. 9298830)				
	Examination for Defects	6		3.2	4.4.2.4
	Carton, Packing, Ammunition for Warhead Section (DRAGON) prior to Sealing (Dwg. 9226389)				
	Examination for Defects	3		3.2	4.4.2.5

NOTES:

(a) Acceptance Plan (10-0-1), withhold 2 samples from test for comparisons.

Source: https://assist.dla.mil - Downloaded: 2020-10-07 09:07:52
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-14980A (AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
	Warhead, Metal Parts and Assembly				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Marking Diagram and Sealing for Inter-plant or CONUS Shipment of Ammunition Fiberboard Boxes (Dwg. 8799112)				
	Examination for Defects	3		3.2	4.4.2.6

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation.-Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination.-See MIL-A-48078.

a. Sampling plans.-Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-14980A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Cone, Warhead	1 OF 1	9216779
			NEXT HIGHER ASSEMBLY: 9216776

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	Wall thickness variation (3) transverse planes between Datums A and B		100%	3.2	Gage (4.5.2)
102.	Wall thickness between Datums A and B		0.25%	3.2	Gage
103.	Apex Wall Thickness		0.25%	3.2	Gage
104.	Wall straightness between Datums A & B		0.25%	3.2	Gage
105.	Body mating diameter		0.25%	3.2	Gage
106.	Total runout of body mating diameter with Datums A and B		0.25%	3.2	Gage
107.	Perpendicularity, flange face to Datums A and B		0.25%	3.2	Gage
108.	Roundness of body mating diameter		0.25%	3.2	Gage
Minor					
201.	Length of mating surface		0.65%	3.2	Gage
202.	Flange outside diameter		0.65%	3.2	Gage
203.	Finish improper		0.40%	3.2	Gage
204.	Identification missing or illegible		0.65%	3.2	Visual
205.	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-14980A (AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.2	Body, Warhead		9216777
			NEXT HIGHER ASSEMBLY 9216776

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Inside diameter, Cone Seat		0.25%	3.2	Gage
102.	Large body inside diameter		0.40%	3.2	Gage
103.	Nose crush switch mounting diameter		0.25%	3.2	Gage
104.	Roundness, cone mounting diameter		0.25%	3.2	Gage
105.	Length, cone mounting surface		0.40%	3.2	Gage
106.	Length, ogive mounting surface		0.40%	3.2	Gage
107.	Inside diameter, S&A device seat		0.40%	3.2	Gage
108.	Boattail thread size		0.40%	3.2	Gage
109.	Wall thickness, shroud (See Note **)		0.25%	3.2	Gage
110.	Location of wireway hole in shroud		0.25%	3.2	Gage
111.	Hole pattern, location of missile mounting holes in shroud		0.25%	3.2	Gage
112.	Diameter, missile mounting holes		0.25%	3.2	Gage
113.	Shroud mounting area not free of paint		0.40%	3.2	Gage
114.	True position, S&A locating pin hole		0.40%	3.2	Gage
115.	Chromate finish test panels		(a)	3.5	Test (4.5.5)
Minor					
201.	Overall length, front face to shroud base		0.65%	3.2	Gage
202.	Overall length, front face to S&A recess face		0.65%	3.2	Gage

NOTES: ** Wall thickness of shroud shall be measured by longitudinal traverse and rotation all around at tangent point to radius at bottom.

(a) 5 test panels per lot (5-0-0)

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 2 OF 2	DRAWING NUMBER
4.4.2.2 (Cont'd)	Body, Warhead		9216777
			NEXT HIGHER ASSEMBLY
			9216776

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
203.	Wall thickness, warhead body		0.65%	3.2	Gage
204.	Wall thickness, boattail (min. 3 places)		0.65%	3.2	Gage
205.	Boattail large datum location		0.65%	3.2	Gage
206.	Boattail small datum location		0.65%	3.2	Gage
207.	Wireway hole diameter		0.65%	3.2	Gage
208.	Shroud outside diameter, total runout		0.65%	3.2	Gage
209.	Length, missile mounting surface (shroud)		0.65%	3.2	Gage
210.	Finish improper or damaged		0.65%	3.2	Gage
211.	Protective finish, inadequate, scratched or damaged		0.65%	3.2	Visual
212.	Identification missing or illegible		0.65%	3.2	Visual
213.	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER 9216776
4.4.2.3	Warhead, GM, HE, M224, Metal Parts Assembly		NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	Total runout, body inside diameter to cone datum diameters A and B		0.25%	3.2	Gage
102.	Total runout, S&A seat diameter to cone datum diameters A and B		0.25%	3.2	Gage
103.	Total runout, shroud O.D. to cone datum diameters A and B		0.25%	3.2	Gage
104.	Perpendicularity, end of S&A seat to cone datum diameters		0.25%	3.2	Gage
105.	True position, ogive mounting holes		0.25%	3.2	Gage
106.	Diameter, ogive mounting holes		0.25%	3.2	Gage
107.	Excess bonding adhesive in body cavity		0.25%	3.2	Gage
108.	Functional fit - Warhead to missile		100%	3.2	Gage
109.	Diameter, hole for S&A locating pin		0.25%	3.2	Gage
110.	Air Leakage Test - Cone to Body Seal		100%	3.2	Test (4.5.3)
111.	Cone - body pull test panels	10*			Test (4.5.4)
Minor					
201.	Parts defective, missing or loose		0.65%	3.2	Manual/Visual
202.	Depth, hole for S&A locating pin		0.65%	3.2	Visual
203.	Identification missing or illegible		100%	3.2	Visual
204.	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES: * Acceptance Plan - One failure rejects lot (10-0-1). If First Article Test has been successfully completed, this test is not required.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Cup, Closure	1 OF 1	9298830
			NEXT HIGHER ASSEMBLY: 9216776

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major	None defined.				
Minor					
201.	Large inside diameter		0.40%	3.2	Gage
202.	Small inside diameter		0.40%	3.2	Gage
203.	Height		0.40%	3.2	Gage
204.	Thickness		0.40%	3.2	Gage
205.	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DSDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Carton, Packing, Ammunition for Warhead Section (DRAGON) Prior to Sealing	1 OF 1	9226389
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	Configuration and fit incorrect		0.40%	3.2	Dummy Warhead
102.	Dryness of material improper		0.40%	3.2	Visual
103.	Components missing		0.40%	3.2	Visual
Minor					
201.	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Marking Diagram and Sealing for Interplant or CONUS Shipment of Ammunition Fiberboard Boxes	1 OF 1	8799112
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	Marking missing, incorrect or illegible		0.40%	3.2	Visual
102.	Contents loose when tilted		0.40%	3.2	Manual
103.	Sealing strips missing broken or loose		0.40%	3.2	Visual/Manual
Minor					
201.	Evidence of poor workmanship		100%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.-Testing is described in the First Article and Quality Conformance inspection tables.

4.4.4 Inspection equipment.-The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Test methods and procedures

4.5.1 Materials, components and processes.-Compliance with all requirements of Section 3 of this specification shall be ascertained by current and continuing examination of inspections and test data to determine that all components (parts, subassemblies, and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed.

4.5.1.1 Visual and mechanical inspection.-The visual, manual and mechanical inspections and tests shall verify compliance with the requirements of Sections 3 and 5 of this specification in accordance with 4.4.2 herein and Table I.

4.5.2 Wall thickness variation of warhead cone (see dwg 9216779.-Each warhead cone shall be examined for wall thickness and variation in wall thickness in a minimum of three (3) transverse planes located between the datums specified on dwg. 9216779, using test equipment as specified in 4.4.4. Defects shall be removed from the lot.

4.5.3 Airtightness of warhead metal parts assembly (see dwg. 9216776).-The warhead metal parts assembly explosive charge cavity shall be subjected to an internal pressure of 5 $\pm$ 0.5 psig of dry air or nitrogen. Upon reaching the prescribed pressure, the pressure shall be stabilized, the supply shut-off and observations made for leaks. The pressure level shall be constant for a minimum of 10 seconds. The pressure gage shall have a sensitivity of at least $\pm$ .01 psi. Retests shall be permissible if a leak is believed attributable to defective test equipment seal. Defects shall be removed from the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

4.5.4 Cone-body cleaning process qualification.-This test shall be performed as specified in Test Method ASTM D-1002-72 with the exception that the test panel shall consist of .110 mils thick copper sheet stock, composition as specified on dwg. 9216779. The joint shall be heat-cured at 250°F for 45 minutes, max. and then cooled to room temperature. Panels shall meet the specified requirements when tested.

4.5.5 Protective finishes on warhead body (see dwg. 9216777).- Warhead bodies and test samples shall be coated in accordance with MIL-C-5541. Production units and test samples shall be coated during the same application and under the same conditions. The test samples, including the first article warhead bodies, shall be conditioned as prescribed by ASTM Test Method B-117-73 for 100 hours. After exposure to the above conditions, the test surfaces shall be examined for corrosion. No test panel shall exhibit more than 2 small isolated pits of corrosion. No spots of corrosion shall be permitted on the First article warhead bodies.

5. PACKAGING

5.1 Packaging requirements.-The warhead shall be packaged in accordance with dwg. 9226389.

5.2 Sealing and marking.-Sealing and marking of the packing carton shall be in accordance with dwg. 8799112.

6. NOTES

6.1 Intended use.-The warhead metal parts assembly covered by this specification is a major component of the DRAGON Warhead Section, Guided Missile, HE, M225, which is designed to contain the explosive charge of the missile and to receive by suitable means of attachment, the fuze components for its detonation.

6.2 Ordering data.-See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval.- See MIL-A-48078. Submit equipment designs as required to Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, New Jersey 07801.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

6.4 Data requirements.-Deliverable data required by this specification is cited in the following paragraph:

Paragraph	Data Requirement	Applicable DID
4.5.3	Quality Inspection Defect Report	DI-R-1721
4.5.3	Quality Inspect Test, Demonstration and Evaluation Report	DI-R-1724 (tailored)

(Copies of data item descriptions required by the contractors in connection with specific functions should be obtained from the procuring activity or as directed by the contracting officer).

6.5 Drawings.-Drawings listed in Section 2 of this specification under the heading US Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 1336-A321

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
US ARMY ARMAMENT RESEARCH & DEVELOPMENT COMMAND
ATTN: DRDAR-QAR
DOVER, NJ 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-W-14980A Warhead,Guided Missiel, HE, M224 Parts For

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. *GIVE PARAGRAPH NUMBER AND WORDING*

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 78 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:15Z
Check the source to verify that this is the current version before use.