MILITARY SPECIFICATION

CRADLE, ATOMIC WEAPON, CASE SECTION: H4142

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of support and handling fixture entitled Cradle, Atomic Weapon, Case Section H4142 which is used with the Honest John warhead section.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-T-5021 - Tests; Aircraft Welding Operators Certification.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1168 - Lot Numbering of Ammunition.

DRAWINGS

ORDNANCE CORPS

8800869 - Cradle, Atomic Weapon, Case Section: H4142.
8808362 - Container, Packing, Ammunition, for Domestic (CONUS) Shipments of Special Weapons Items, Packing and Marking.
8824944 - Carton, Packing, Ammunition, for Cradle, Case Section, Atomic Weapon: H4142.
8824949 - Box, Packing, Ammunition, for Cradle, Atomic Weapon, Case Section: H4142.
EL-8856518 - Equipment List.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The cradle shall comply with all requirements specified on the drawing (dwg) 8800869, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 Static load. The cradle shall be capable of supporting a 2,600 pound load without evidence of permanent distortion, cracked welds, torn or other physical damage as could be experienced by the rubber pad and adhesive when tested as specified in 4.3.1

3.4 Welding. Welds shall be reasonably smooth and free of craters. They shall exhibit characteristics of good welding practice on the part of the operator. All welding fluxes, scale, weld spatter, guide, and basic solution shall be removed prior to application of any finish coat.

3.4.1 Welding operators. All fusion welding shall be performed by operators who are currently certified as class "B" welders in accordance with MIL-T-5021.

3.5 Workmanship.

3.5.1 Plastic and matal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.5.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.5.3 Burrs. Parts shall be free from burrs.

3.5.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.5.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection

4.2.1 Lot formation.

4.2.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.2.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.2.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table I and Table II), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

Table I
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table II
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

4.2.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.2.2.1.1 Cradle, case section, H4142 (see dwg 8800869).

Categories	Characteristics	Method of Inspection
Critical:		
	1. Crack in weld	Visual
	2. Improper welding (see 3.4)	Visual
	3. Any part cracked or loose	Visual/Manual
Major:		
	101. Cradle contour incorrect	Visual
	102. Rubber pad improperly secured	Visual/Manual
	103. Objective evidence relating to material missing or improper (see 3.1)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

Minor:

201. Protective finish damaged to the extent of exposing base material.....Visual
202. Evidence of poor workmanship (see 3.5).....Visual

4.2.2.1.2 Carton, packing, ammunition, for cradle, case section, H4142, prior to sealing top (see dwg 8824944).

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:

101. Cradle incorrectly positioned.....Visual
102. Support missing or incorrect.....Visual
103. Insufficient filler material.....Visual/Manual
104, Packing material not thoroughly dry.....Visual/Manual

Minor: None defined.

4.2.2.1.3 Carton, packing, ammunition, for cradle, case section, H4142 (see dwg 8824944) .

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:

101. Sealing strip incorrect.....Visual
102. Carton sealed inadequately.....Visual/Manual

Minor:

201. Marking missing, incorrect or unidentifiable.....Visual
202. Evidence of poor workmanship (see 3.5).....Visual

4.2.2.1.4 Box, packing, ammunition, for cradle, case section: H4142, prior to closing (see dwg 8824949).

Categories	Characteristics	Method of Inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

Critical: None defined.

Major:

101. Box incorrect.....Visual
102. Filler material inadequate.....Visual/Manual

Minor: None defined.

4.2.2.1.5 Box, packing, ammunition, for cradle, case section H4142 (see dwg 8824949).

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:

101. Box sealed inadequately.....Visual/Manual
102. Strapping loose or incorrectly positioned.....Visual/Manual
103. Contents loose.....Manual

Minor:

201. Marking missing or incorrect.....Visual
202. Car seal missing.....Visual
203. Evidence of poor workmanship (see 3.5).....Visual

4.2.2.1.6 Container, packing, ammunition for domestic (CONUS) shipment of special weapons items, packing, and marking (see dwg 8808362).

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:

101. Marking missing, incorrect or mislocated.....Visual
102. Packing material visibly wet.....Visual
103. Evidence of poor workmanship (see 3.5).....Visual
104. Contents loose.....Visual

Minor: None defined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

4.2.3. Testing. All tests shall be performed. Tests shall be performed in the order specified below:

Test	Test classification
a. Static load	Major

This test is not considered destructive and samples so tested may be returned to the lot.

4.2.3.1 Static load. Each cradle in the lot shall be tested in accordance with 4.3.1. If any item fails to comply with 3.3, the item shall be rejected and removed from the lot.

4.2.4 Acceptance inspection equipment.

4.2.4.1 Critical and major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL) (See EL-8856518). When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "part or Identifying Number" column on the EL (see 6.1.2).

4.2.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELS. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.3 Test methods The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufactuter shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.3.1 Static load. A 2,600 pounds static weight with a radius curvature of 15.00 inches shall be applied parallel to the face of the rubber pad on the cradle. The cradle shall be supported at the supports at both ends (25.00 inches apart). The weight shall be applied for 1 minute and then removed.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The cradle shall be packaged in accordance with dwg 8824944 using the specified moisture barrier.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

5.1.2 Level C. The cradle shall be packaged in accordance with dwg 8824949 except that the moisture barrier may be omitted.

5.2 Packing.

5.2.1 Level A and C. The cradle shall be packed in accordance with dwg 8824949 for overseas and 8808362 for CONUS shipments.

5.3 Marking. Marking shall be as specified in accordance with dwg 8824949 or 8808362 as applicable.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.2.4.1). Data specified in 4.2.4.1 will be delivered as identified on a numbered DD Form 1664 when required on s DD Form 1432 incorporated in the contract.

6.2 Ovjective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.2.4.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-N-I.

6.4 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-1993 dated 30 August 1961

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No. 1190-A069

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.