INCH-POUND

MIL-F-50945D (AR)
AMENDMENT 4
27 August 1990

SUPERSEDING
AMENDMENT 3
25 April 1990

MILITARY SPECIFICATION

FUZE, PD, M567/XM935 (M935) LESS BOOSTER

This Amendment forms a part of Military Specification MIL-F-50945D (AR), dated 8 September 1982 and is approved for use within the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title: Add "(M935)" after "M567/XM935"; and wherever it appears in the specification.

Title: Add "/M936" after "(M935)"; and where applicable.

PAGE 2

2.1.2, Add to title of 9272193, "or Body Assembly, Front, M935."

Add to title of 9272194, "or Body Assembly, Front, M935."

PAGE 10

4.3.1.2: Delete "Cap, Shipping...9255255...10."

PAGE 18

TABLE I, First article inspection: Delete "Cap, Shipping, Dwg. 9255255, Examination for defects."

PAGE 33

4.4.2.6 and 4.4.2.6.1, Add Major 113 which reads as follows:

"113 Lubrication missing or improperly applied...0.40%... 3.2...Visual."

AMSC N/A

FSC 1390

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.

PAGE 43

4.4.2.13, Add Major 106 wich reads as follows:

"106 Lubrication missing or improperly applied...0.40%... 3.2...Visual."

PAGE 44

4.4.2.14, Add Major 109 which reads as follows:

"109 Lubrication missing or improperly applied...0.40%... 3.2...Visual."

PAGE 45

4.4.2.15, Delete Major 104 in its entirety.

PAGE 62

4.4.2.26, Add Major 105 which reads as follows:

"105 Lubrication missing or improperly applied...0.40%... 3.2...Visual."

PAGE 72

* 4.4.2.35, Delete major 105 in its entirety and substitute the following:

"Major 105 Tensile test...(b)...3.1...Gage"

* Major 106 Add new CD as follows:

"Major 106 Wrap test...(b)...3.1...Gage"

* Note (b): Add at end of note the following:

"Test per MIL-STD-105D, inspection level S-4, AQL 1.0 percenttt for wrap test and level S-1, AQL 1.5 percent for the tension test. Examination of wrap test samples shall utilize 4 X magnification."

PAGE 83

4.4.2.42, Add new Major 109 as follows:

"109 Presence of tape over rear face of body assembly... 0.40%...3.2...Visual."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.

PAGE 83

4.4.2.42, Major 106: Delete in its entirety.

PAGE 85

4.4.2.44: Delete in its entirety.

PAGE 87

4.4.2.46, Add Major 103 and Note (h) which reads as follows:

"103 Lubrication missing or improperly applied...12...(h) ...3.2...Visual.

(h) Same 12 samples after being used for the Jolt and Jumble Test shall be disassembled to examine for missing or improperly applied lubrication/grease (components to be checked are striker, setback pin, setback spring, slider detent, safety latch and selector cap O-ring). If one or more samples are classed defective, the lot shall be rejected."

PAGE 88

4.4.2.46, Major 102 and Major 104, Delete "15" sample size and substitute "5."

4.4.2.46, Under sample units, Delete "166" and substitute "146."

PAGE 89

4.4.2.47, Add Major 103 and Note (h) which reads as follows:

"103 Lubrication missing or improperly applied...12...(h) ...3.2...Visual.

(h) Same 12 samples after being used for the Jolt and Jumble Test shall be disassembled to examine for missing or improperly applied lubrication/grease (components to be checked are striker, setback pin, setback spring, slider detent, safety latch and selector cap O-ring). If one or more samples are classed defective, the lot shall be rejected."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.

PAGE 90

4.4.2.47, Major 102 and Major 104, delete "15" sample size and substitute "5."

4.4.2.47, Under sampling units, delete "166" and substitute "146."

PAGE 91

4.4.2.48, Add to title: "or Body Assembly, Front, M935."

PAGE 92

4.4.2.49, Add to title: "or Body Assembly, Front, M935."

PAGE 93

4.4.2.50, Delete Major 101 in its entirety.

PAGE 98

4.5.10, Delete "the shipping cap (dwg. 9255255) shall be removed and"

PAGE 104

6.7.2, Under quantity column, delete "15" and substitute "5."

NOTE: The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-A700)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.