INCH-POUND

MIL-P-48606B(AR)
29 March 1991
SUPERSEDING
MIL-P-48606A(AR)
30 September 1980

MILITARY SPECIFICATION

POWER SUPPLY ASSEMBLY (UNIT 2): 11748133

This specification is approved for use by the U. S. Army Armament, Munitions and Chemical command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 scope. This specification covers the Power Supply Assembly (Unit 2) used with the System Tester, Radar AN/VPM-2, 11748124 (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-F-13926 - Fire Control Materiel, Manufacture and Inspection, General Specification for
MIL-I-45607 - Inspection Equipment, Acquisition, Maintenance and Disposition of

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 1240

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-810 - Environmental Test Methods and Engineering Guidelines
MIL-STD-2000 - Standard Requirements for Soldering Electrical and Electronic Assemblies

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS (See 6.4)

Us. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

11748133 - Power Supply Assembly (Unit 2): 11748133

SPECIAL PACKAGING INSTRUCTION

PS11748133 - packaging of Power Supply Assembly (Unit 2): 11748133

(Copies of drawings, publications, and other Government documents required by contractors In connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of conflict between the text of this specification and the references cited herein the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and" regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on Drawing 11748133, all associated drawings, and with all requirements specified in applicable specifications and standards. Where applicable, the power supply assembly shall meet the requirements of MIL-F-13926 as follows:

a. Dimensions and tolerances.
b. Inorganic protective surface finishings.
c. Part identification and marking.
d. Workmanship.

3.3 Environmental service conditions.

3.3.1 Vibration. The power supply assembly shall not suffer damage and shall meet the requirements of 3.4 and 3.5 after exposure to sinusoidal vibrations, in each of three mutually perpendicular axes, as follows:

Frequency Range	Amplitude
10 to 15 hertz	0.06 inches double amplitude
15 to 25 hertz	0.04 inches double amplitude
25 to 55 hertz	0.02 inches double amplitude

The frequency of vibration shall be swept logarithmically.
The cycling time shall be 120 minutes per axis.
The sweep rate shall be 3.75 minutes ± 10% per decade.
The 10-55-10 hertz sweep time is 3 minutes 45 seconds ± 10%.

3.3.2 Altitude.

3.3.2.1 Operating. The power supply assembly shall meet the requirements of 3.4 and 3.5 during and after exposure to barometric pressure encountered at 10,000 feet above sea level (20.6 inches of Hg).

3.3.2.2 Non-operating. The power supply assembly shall meet the requirements of 3.4 and 3.5 after exposure for not less than 10 minutes to barometric pressure encountered at 40,000 feet above sea level (5.5 inches of Hg).

3.3.3 Temperature.

3.3.3.1 0perating The power supply assembly shall meet the requirements of 3.4 and 3.5 when stabilized thermally at any temperature between -40 degrees F and +155 degrees F.

3.3.3.2 Non-operating (storage). The power supply assembly shall not suffer permanent damage when subjected to the constant temperature extremes of -60 degrees F for a period of 24 hours and +160 degrees F for a period of 4 hours (after temperature stabilization), and shall meet the requirements of 3.4 and 3.5 when returned to room ambient.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.

3.3.4 Humidity (non-operating) The power supply assembly shall meet the requirements of 3.4 and 3.5 after exposure to an atmosphere with a relative humidity in excess of 95 percent for a period of 10 days.

3.3.5 Immersion (non-operating) The power supply assembly shall meet the requirements of 3.4 and 3.5 and shall have no evidence of water penetration within the case after being immersed in water and subjected to a positive pressure equivalent to 3 head-feet of water (approximately 1.3 psi) for a period of two hours. The power supply assembly shall be immersed with its case closed, an equivalent dummy load, and a sealed plug in place of the pressure release valve.

3.4 Electrical. Each conductor shall be electrically continuous as specified on the schematic diagram of the power supply assembly.

3.5 Performance.

3.5.1 Initial voltage adjustments. The power supply assembly shall produce the following output voltages and currents as shown in Table I (Power supply output voltage) when operating from a primary power source of 24 ± 1 Vdc.

TABLE 1. Power supply output voltages.

POWER MODULE	VOLTAGE SETTING	CURRENT (+/-5%)	LOAD PINS
11748127-1	+28.00 ± 0.1 Vdc	1.30 Amp	C(+) TO D(RET)
11748127-2	+15.00 ± 0.1 Vdc	0.625 Amp	E(+) to F(RET)
11748127-2	-15.00 ± 0.1 Vdc	0.180 Amp	G(-) to F(RET)
11748128	+5.00 ± 0.05 Vdc	0.850 Amp	A(+) to B(RET)

NOTE: The voltages shall be initially adjusted to the requirements of Table I and shall not require further adjustment during any subsequent performance and/or environmental tests unless specifically indicated.

3.5.2 Power drain.The power supply assembly shall require no more than 14 amps (steady state) from the primary power source when operating under loads that produce the maximum load currents specified in Table II and minimum primary input voltage of 18.1 ± 0.1 Vdc.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.

TABLE II. Power supply load currents.

POWER MODULE	LOAD PINS	MIN LOAD CURRENT (+5%)	NOM LOAD CURRENT (+5%)	MAX LOAD CURRENT (+5%)
11748127-1 (+28)	C(+) to D	0.300A	1.300A	1.800A
11748127-2 (+15)	E(+) to F	0.375A	0.625A	0.875A
11748127-2 (-15)	G(-) to F	O.110A	0.180A	0.250A
11748128 (+5)	A{+) to B	0.500A	0.850A	1.200A

3.5.3 OutPut short circuit Protection. With nominal primary input voltage 24.0 ± 1 Vdc applied, and with a short circuit (less than 0.5 ohms) applied to each output voltage terminal for a minimum of 30 seconds, the voltage shall return to the values listed in Table I when the short circuit is removed. It may be necessary to turn the primary voltage off and on.

3.5.4 Regulation. The line effect, load effect and temperature effect regulation of each output in the power supply assembly shall meet the requirements as delineated in the formulas below:

3.5.4.1 Line effect regulation. With loads applied to produce the nomninal load currents as specified in Table II, the power supply output voltages shall not vary more than ±0.5% when the primary power source is varied from 18.1 ± 0.1 Vdc to 29.9 ± 0.1 Vdc.

3.5.4.2 Load effect regulation. with primary power source at 24.0 ± 1 Vdc, the power supply assembly output voltages shall not vary more than ±0.5% as the load currents are varied from the minimum to the maximum values as specified in Table IX.

3.5.4.3 Temperature effect on regulation. An additional ±0.03% per degree Celsius variation of the above values shall be permitted for all tests conducted at other than ambient conditions.

3.5.5 Ripple voltage. The ripple voltage for all outputs with loads applied to produce the maximum load currents as specified in Table II and minimum primary voltage of 18.1 ± 0.1 Vdc applied, shall not exceed 300 mV P-P, 25 mV RMS from +77 degrees F to +155 degrees F and 130 mV P-P, 40 mV RMS from +40 degrees F to +77 degrees F when measured with an oscilloscope which has a bandwidth of 25 MHz and a true-RMS AC voltmeter.

3.6 Environmental Stress Screening (ESS). ESS shall be performed on each new power supply assembly produced and shall consist of two non-operating screening procedures. The power Supply assembly shall meet the requirements of 3.4 and 3.5 at standard ambient conditions after each procedure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.

3.6.1 Screening procedures.

3.6.1.1 Temperature Cycling. The power supply assembly shall be exposed to 3 temperature cycles between -60 degrees F and +160 degrees F with a minimum change rate of 5.5 degrees F per minute and a minimum dwell time of 60 minutes at each extreme in the cycle. The first cycle shall start at standard ambient conditions and the first extreme shall be +160 degrees F. It shall take 3.33 hours to complete 1 cycle, 10 hours total. If the minimum change rate is exceeded, the dwell times shall be equally increased accordingly.

3.6.1.2 Vibration. The power supply assembly shall be exposed to vibrations using the same conditions as 3.3.1 except that the cycling time shall be reduced to 20 minutes per axis.

3.6.2 Failures after a screening procedure. Each failure shall be recorded, categorized, and corrected as follows:

3.6.2.1 Workmanship failures. Workmanship failures shall be corrected without repeating the screening procedure that caused the failure.

3.6.2.2 Power module failures. Power module failures shall be corrected by replacing the failed module with a new module that has been screened up to the procedure at which the failure occurred. The screening procedure that caused the module failure shall then be repeated on the power supply assembly.

3.7 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection in accordance with the technical provisions herein (see 4.3).

3.8 Soldering. All soldering shall be in accordance with the general requirements of MIL-STD-2000 in addition to detail requirement (tasks)A, C and D of paragraph 1.2 of MIL-STD-2000.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. all items shall meet all requirements of Sections 3 and 5. The inspections set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 General provisions. The component and subassembly inspection requirements of MIL-F-13926 form a part of the quality assurance provisions of this specification. Reference shall be made to MIL-STD-109 to define quality assurance terms used herein.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Special sampling inspection (see 4.5).

4.2.1 Inspection conditions. Unless otherwise specified, all examinations and tests shall be conducted at the following standard ambient conditions:

a.	Temperature	+50 degrees to +90 degrees F
b.	Relative humidity	90% RH max.
c.	Pressure	28 to 32 inches of Hg

4.3 First article inspection.

4.3.1 First article submission. The contractor shall submit a first article sample as designated by the contracting officer consisting of three (3) Power Supply Assemblies for inspection in accordance with 4.3.2.

4.3.2 Inspections to be Performed. First article assemblies, components and test specimens may be subjected by the Government to any or all of the examinations and tests specified in Table I (Functional Test) and Table II (Special Sampling) herein and to any or all requirements of the applicable drawings.

4.3.3 Rejection. If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of any of the stated requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. The term "inspection lot" is defined as a homogeneous collection of units of product from which a representative sample is drawn or which is inspected 100 percent to determine conformance with applicable requirements. Units of product selected for inspection shall represent only the inspection lot from which they are drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of inspection procedure which is being applied to determine conformance with requirements.

4.4.2 Examinations and tests.

4.4.2.1 Components, assemblies and subassemblies. All components, assemblies and subassemblies shall be inspected in accordance with the inspection provisions contained in this specification and the Quality Assurance Provisions (QAP) listed in the Technical Data Package (TDP). In the absence of QAPs, the applicable quality assurance provisions of MIL-F-13926 shall apply.

4.4.2.2 Final acceptance Inspection. subsequent to first article approval, examinations and tests related to Section 3 herein shall be performed in accordance with the sampling plans specified in 4.4.2.3 herein. Examination and test for packaging and marking shall be in accordance with Section 5 herein. The tabulated classification of defects in 4.4.2.3 shall constitute the minimum inspection to be performed by the contractor after first article approval and prior to Government acceptance or rejection by item or lot l

4.4.2.3 Functional tests. The tests in Table III shall be performed on a 100% basis.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.

TABLE III. Functional tests (100 percent inspection).

CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
Critical:	None	N/A
Major		
101. Electrical	3.4	4.7.2
102. Performance	3.5	4.7.3
103. ESS	3.6	4.7.4
Minor:	None	N/A

4.5 Special sampling. One power supply assembly out of the first 50 produced and one out of each 100 produced thereafter shall be selected at random. The sample shall have met the requirements and tests of Table III and shall then meet the tests in Table IV. Unless otherwise specified in the contract, the items shall be returned to the lot upon successful completion of testing.

TABLE IV. Special sampling.

CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
Critical:	None	N/A
Major:		
104. Vibration	3.3.1	4.7.1.1
105. Altitude	3.3.2	4.7.1.2
106. Temperature	3.3.3	4.7.1.3
107. Humtdlty	3.3.4	4.7.1.4
108. Immersion	3.3.5	4.7.1.5
Minor:	None	N/A

4.5.1 Failure of sample. should any one item of a special sampling fail to meet any of the specified test requirements, acceptance of the product shall be suspended by the Government until necessary corrections to all production since the last test as well as to current production has been accomplished in accordance with the provisions of the contract.

4.6 Inspection equipment.

4.6.1 Government-furnished inspection equipment. Where the contract provides for Government-furnished test equipment, supply and maintenance of test equipment shall be in accordance with the applicable requirements of MIL-I-45607.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.

4.6.2 Contractor-furnished inspection equipment.

4.6.2.1 Government design. Unless otherwise specified in the contract, all inspection equipment identified by drawing number in specifications or QAPs forming a part of the contract shall be supplied by the contractor in accordance with the design specified. The contractor may, however, propose alternatives to Government designs for approval in accordance with 6.3.

4.6.2.2 Contractor design. The contractor shall design and supply inspection equipment compatible with the "Methods of Inspection" specified in 4.7 of this specification and with the component inspection procedures specified in "Examination" and "Test Facilities" requirements of MIL-F-13926 whenever Government designs are not specified (see 4.6.2.1). Since tolerance of test equipment is normally considered to be within 10 percent of the product tolerance for which it is intended, this inherent error in the test equipment design must be considered as part of the prescribed product tolerance limit. Thus, concept, construction, materials, dimensions, and tolerances used in the design of test equipment shall be so selected and controlled as to ensure that the test equipment will reliably indicate acceptability of a product which does not exceed 90 percent of the prescribed tolerance limit and permit positive rejection when nonconforming. Construction shall be such as to facilitate routine calibration of test equipment. Contractor inspection equipment designs shall be submitted for approval in accordance with 6.3.

4.6.2.3 Test Equipment. In conjunction with 4.6.2.1 and 4.6.2.2, the test equipment listed in Table V (Test equipment list) shall be used in the performance of the applicable test methods and procedures as specified in 4.7.

TABLE V. Test equipment list.

ITEM NUMBER		DESCRIPTION
1.	Power Supply	SCR regulated DC output DC Output Voltage: 0 V to 30 V minimum DC Output Current: 25 A minimum Hewlett Packard model 6434B or equivalent
2.	Digital Multimeter	5 1/2 digits minimum, true-RMS AC, 20Hz to 50 kHz
3.	Current Probe	Clamp-on, DC or AD DC Current Ranges: 20 A and 200 A DCA Accuracy: +/-2% of range Fluke model Y8100 or equivalent

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.

TABLE V. Test equipment list. (continued)

ITEM NUMBER	DESCRIPTION
4. Oscilloscope	Dual channel, 25 MHz Bandwidth Philips model PM3212 or equivalent
5. Load Resistors	Various values and wattages as needed to produce load currents per Tables I and II.

4.7 Methods of inspection.

4.7.1 Environmental. Environmental tests shall be conducted in accordance with the test conditions, general test performance guidance and individual test methods of MIL-STD-810, except as specified herein. Test facilities, chambers and apparatus used in conducting the tests contained in this specification shall be capable of meeting the conditions required.

4.7.1.1 Vibration. The test shall be performed as specified in Method 514, Category 8, Procedure I, of MIL-STD-810 as modified by 3.3.3 herein. In Step 1 of Procedure I, only steps 4 through 8 of paragraph II-2.1 apply. The power supply assembly shall be attached to the vibration generator directly or with a fixture, and securely held by its normal means of attachment. After vibration, the power supply assembly shall be tested as specified in 4.7.2 and 4.7.3 herein to determine compliance with 3.3.1.

4.7.1.2 Altitude (operating and non-operating). This test shall be performed as specified in Procedures II and III, Method 500 The operational checkout shall be as specified in 4.7.2 and 4.7.3 for compliance with 3.3.2.

4.7.1.3 Temperature.

4.7.1.3.1 High (operating and non-operating). This test shall be performed as specified in procedures I and II, Method 501 of MIL-STD-810 with constant temperature extremes as specified in 3.3.3. The operational checkout shall be as specified in 4.7.2 and 4.7.3 for compliance with 3.3.3.

4.7.1.3.2 Low (operating and non-operating). This test shall be performed as specified in Procedures I and II; Method 502 of MIL-STD-810 with constant temperature extremes as specified in 3.3.3. The operational checkout shall be as specified in 4.7.2 and 4.7.3 for compliance with 3.3.3.

4.7.1.4 Humidity (non-operating). This test shall be performed in accordance with Procedure III, Method 507 of MIL-STD-810 except that in Step 7, Checkout shall be performed at the conclusion of the test only, with the item at standard ambient conditions. The operational checkout shall be as specified in 4.7.2 and 4.7.3 for compliance with 3.3.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.

4.7.1.5 Immersion (non-operating). This test shall be performed as specified in Procedure I, Method 512 of MIL-STD-810 as modified by 3.3.5 herein. The operational checkout shall be as specified in 4.7.2 and 4.7.3 for compliance with 3.3.5.

4.7.2 Electrical. Continuity shall be inspected by standard measuring equipment and visual examination for compliance with 3.4.

4.7.3 Performance. The power supply assembly shall be tested as follows using the DMM (Item 2, Table V) except when other test equipment is specified.

4.7.3.1 Initial voltage adjustments. Using power supply (item 1, Table V) apply an input voltage of +24.0 ± 1 Vdc between pins I(+) and H(RET). Using lead resistors (item 5, Table V) to produce the load currents delineated in Table I, adjust the power modules using the internal adjustment potentiometers to the voltages shown in Table I. Subsequent performance testing shall require no readjustment of the power modules.

4.7.3.2 Power drain. With the input voltage set to 18.1 +/- 0.1 Vdc and using load resistors to produce the maximum load currents as specified in Table II, use the current probe (item 3. Table V) in conjunction with the DMM to verify that the input current does not exceed 14 amps steady state as required in 3.5.2.

4.7.3.3 Output short circuit protection. With the input voltage set to 24.0 +/-1 Vdc and using load resistors to produce the load currents as specified in Table I. place a short circuit across each output for at-least 30 seconds. Verify that the output voltage returns to the values specified in Table I when the short circuit is removed as required in 3.5.3.

4.7.3.4 Regulation.

4.7.3.4.1 Line effect regulation. With the input voltage initially set to 24.0 +/- 1 Vdc and using load resistors to produce the nominal load currents as specified in Table II, verify that the output voltages do not change more than +/- 0.5% when the input voltage is adjusted to 18.1 +/- 0.1 Vdc and then adjusted to 29.9 +/-0.1 Vdc as required by 3.5.4.1.

4.7.3.4.2 Load effect regulation. With the input voltage set to 24.0 +/- 1vdc and initially using load resistors to produce the nominal load currents as specified In Table II, verify that the output voltages do not change more than +/- 0.5% when the load resistors are changed to values that produce the minimum load currents per Table II and then changed to values that produce the maximum load currents per Table II as required by 3.5.4.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.

4.7.3.4.3 Temperature effect on regulation. The variation in output voltages shall be within the limits specified in 3.5.4.3 for all tests conducted at other than ambient conditions.

4.7.3.5 Ripple voltage. With the input voltage set to 18.1 +/- 0.1 Vdc and using load resistors to produce the maximum load currents as specified in Table II, use the oscilliseope (item 4, Table V) to measure the peak to peak value at a bandwidth of 25 MHz and the DMM to measure the true RMS value, verify that the ripple voltages for all outputs do not exceed the limits specified in 3.5.5.

4.7.4 Environmental Stress Screening (ESS). The power supply assembly shall be tested as specified in 4.7.2 and 4.7.3 after each screening procedure for compliance with 3.6. After completing both ESS procedures, perform the voltage adjustments as specified In 4.7.3.1.

4.7.4.1 Temperature Cycling. This screening procedure shall be performed as specified in 3.6.1.1.

4.7.4.2 Vibration. This screening procedure shall be performed as specified in 3.6.1.2.

4.8 Soldering. Soldering processes shall be inspected by certified inspectors to the requirements and acceptance criteria of MIL-STD-2000 to be specified is paragraph 3.8.

5. PACKAGING

5.1 General. Preservation, packing and marking shall be in accordance with Special Packaging Instruction PS11748133.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The power supply assembly is used to convert the primary power to DC voltages necessary to operate the AN/VPM-2, Radar System Tester.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.
b. Applicable stock number.
c. First article sample requirements.
d. packaging requirements, if other than specified in Section 5.
e. Serialization requirements, if applicable.
f. Certificate of conformance for each lot or shipment of product.
g. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1).

6.3 Submission of contractor inspection equipment designs for approval. Submit two copies of designs as required to: Commander, U.S. Army AMCCOM, Attn: AMSMC-QAF-I(D), Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament Research, Development and Engineering Center (ARDEC), may also include drawings prepared by, and identified as, U.S. Army Armament Research and Development Command (ARRADCOM), Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under cognizance of ARDEC.

6.5 Subject term (key word) listing.

Environmental Stress Screening (ESS)
System Tester, Radar AN/VPM-2

6.6 Changes from previous issue. Asterisks (or vertical lines) are not used in this revision to identify changes with respect to the previous issue due to the extensivenss of-the changes;

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1240-A924)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-P-48606B (AR)	29 March 1991

3. DOCUMENT TITLE: POWER SUPPLY ASSEMBLY (UNIT 2) : 11748133

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
US ARMY ARDEC STANDARDIZATION OFFICE	(1) Commercial (201) 724-6674	(2) AUTOVON 880-6674
ADDRESS (Include Zip Code) ATTN: SMCAR-BAC-S PICATINNY ARSENAL, NJ 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.

INCH-POUND

MIL-P-48606B (AR)
AMENDMENT 1
27 August 1992

MILITARY SPECIFICATION

POWER SUPPLY ASSEMBLY (UNIT 2): 11748133

This amendment forms a part of MIL-P-48606B (AR), dated 29 March 1991, and is approved for use by the US Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1.1: Add the following military specification:

"MIL-T-28800 - Test Equipment for use with Electrical and Electronic Equipment, General Specification for"

PAGE 2

2.1.1: Delete the following military standard:

"MIL-STD-2000 - Standard Requirements for Soldering Electrical and Electronic Assemblies"

2.1.2: Add the following drawing:

"12950877 - Requirements for Soldering Electrical and Electronic Assemblies"

PAGE 3

3.3.1: Delete in its entirety and substitute the following:

"3.3.1 Vibration. The power supply assembly shall not suffer damage and shall meet the requirements of 3.4 and 3.5 after exposure to sinusoidal vibrations, in each of three mutually perpendicular axes, as specified in MIL-T-28800 for Type I, Class 2, Style A test equipment."

DISTRIBUTION STATEMENT A.- Approved for public release; distributuion is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.

3.3.2, 3.3.2.1 and 3.3.2.2: Delete in their entirety and substitute the following:

"3.3.2 Altitude operating. The power supply assembly shall meet the requirements of 3.4 and 3.5 during and after exposure to barometric pressure encountered at 10,000 feet above sea level (20.6 inches of Hg)."

PAGE 6

3.8: Delete in its entirety and substitute the following:

"3.8 Soldering. All soldering shall be in accordance with the requirements of Note 2 of Drawing 12950877."

PAGE 11

4.7.1.1: Delete in its entirety and substitute the following:

"4.7.1.1 Vibration. This test shall be performed as specified in MIL-T-28800 for Type I, Class 2, Style A test equipment with the exception that Step 4.c Resonance Dwell does not apply. The power supply assembly shall be attached to the vibration generator directly or with a fixture, and securely held by its normal means of attachment. After vibration, the power supply assembly shall be tested as specified in 4.7.2 and 4.7.3 herein to determine compliance with 3.3.1."

4.7.1.2: Delete in its entirety and substitute the following:

"4.7.1.2 Altitude operating. This test shall be performed as specified in Procedure II, Method 500, of MIL-STD-810. The operational checkout shall be as specified in 4.7.2 and 4.7.3 for compliance with 3.3.2."

PAGE 13

4.8: Delete in its entirety and substitute the following:

"4.8 Soldering. Soldering processes shall be inspected by certified inspectors to the requirements and acceptance criteria of Note 2 of Drawing 12950877 as specified in paragraph 3.8."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1240-AB35)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.