MIL-S-81271(OS)
Amendment 2
15 May 1973

Superseding
Amendment 1
16 November 1966

MILITARY SPECIFICATION

SQUIB, ONE AMPERE, NO FIRE

This amendment forms a part of Military Specification MIL-S-81271(OS), 11 May 1965, and has been approved by the Naval Ordnance Systems Command, Department of the Navy.

By this amendment the basic Specification MIL-S-81271(WP) is designated as MIL-S-81271(OS).

1. Page 1, FSC block, delete: "FSC 1375" and substitute: "FSC 1340".

2. Page 2, paragraph 2.2, delete: "Interstate Commerce Commission" and remainder of the paragraph, and substitute:

"CODE OF FEDERAL REGULATIONS

49 CFR 171-190 Hazardous Materials Regulations, Department of Transportation

(Applications for copies of the above publication should be addressed to Superintendent of Documents, Government Printing Office, Washington, D.C. 20402.)"

3. Page 3, paragraph 3.1, lines 2 and 3 Delete "technical requirements of the contract" and substitute "requirements of this specification".

4. Page 3, paragraph 3.3.1: Add to end of last sentence: "as described in 3.5.3."

5. Page 4, paragraph 3.4.2: Delete and substitute:

"3.4.2 No-fire current. The squib shall not fire when a current of 1.0 ampere is applied to the squib circuit for not less than one minute."

6. Page 5, paragraph 3.5.3: Delete and substitute:

"3.5.3 Squib compositions. The three squib compositions employed in the manufacture of the squib shall have the following nominal weights and minimum calorific outputs:

FSC 1340

Source: https://assist.dla.mil -- Downloaded: 202610-23T05:08Z
Check the source to verify that this is the current version before use.

Charge	Nominal Weight, mg	Minimum Output (calories/gram)	Ingredients	Nominal Parts by Weight
Bead	5	650	PbSCN, $KClO_3$, Binder	36, 44, 4
Booster	55	550	PbSCN, $KClO_3$, C, Binder	32, 40, 18, 2
Main Case	45	1050	Zr-Ni, $KClO_4$	68, 32

7. Page 9, paragraph 4.7.3: Delete and substitute:

"4.7.3 Visual examinations.

4.7.3.1 Squib. A sample of squibs selected from the lot in accordance with Table I shall be visually examined to determine conformance with 3.6.

4.7.3.2 Container. Visually examine each container in a lot for conformance with Section 5."

8. Page 9, following paragraph 4.7.3.2, add new paragraph 4.7.4:

"4.7.4 Dimensional examination. A sample of squibs selected from the lot in accordance with Table I shall be examined to determine conformance with 3.3.3."

9. Page 11, paragraph 6.3, add:

"(g) That the safety precaution requirements of the Contractor's Safety Manual for Ammunition, Explosives and Related Dangerous Material, DOD 4145.26M, are applicable.

NOTE: When this specification is used as part of the description of work to be accomplished by a Government activity, the safety precaution requirements of Ammunition Ashore, OP 5, should be made applicable."

10. Page 12, Table I, under Quality Conformance: Add two lines as follows:

"Workmanship	3.6	105	II	1.0	4.7.3.1
Dimensional	3.3.3	105	II	1.0	4.7.4"

Preparing Activity
Navy - OS
Project No. 1340-N398

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:08Z
Check the source to verify that this is the current version before use.