INCH-POUND

MIL-C-11693/7D
AMENDMENT 3
21 September 1992
SUPERSEDING
AMENDMENT 2
13 November 1989

MILITARY SPECIFICATION SHEET

CAPACITORS, FEED THROUGH, RADIO-INTERFERENCE REDUCTION, DC
(HERMETICALLY SEALED IN METAL CASES)
ESTABLISHED AND NON-ESTABLISHED RELIABILITY
STYLES CZ23, CZ24, CZR23 AND CZR24

This amendment forms a part of MIL-C-11693/7D, dated 8 June 1984, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* FIGURE 1, following MS35335-34, add: "see note 6".

PAGE 2

* FIGURE 1, following MS35335-34, add: "see note 6".

* Following note 4, add:

"5. Recommended mounting torque: 10 pound-inches.
6. Lockwasher shall not be cadmium plated."

PAGE 4

Following moisture resistance, add:

"Solderability: Applicable for styles CZ23, CZ24, CZR23, and CZR24."

The margins of this amendment are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - EA, MI
Air Force - 99
DLA - ES

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5910-1824)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:51Z
Check the source to verify that this is the current version before use.