MIL-T-11727B(ME)
15 November 1973
SUPERSEDING
MIL-T-11727A
24 July 1952

MILITARY SPECIFICATION

TOBOGGAN, CARGO-CARRYING (TOWED TYPE, 28 INCHES BY 8 FEET)

1. SCOPE

1.1 This specification covers a towed type toboggan for transporting supplies and equipment.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

PPP-C-650	- Crates, Wood, Open and Covered.

Military

MIL-P-116	- Preservation-Packaging, Methods of.

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-1363	- Measurement of Wood Moisture Content.

FSC 3920

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:54Z
Check the source to verify that this is the current version before use.

DRAWINGS

ME

TA13220E0992 - Toboggan, Cargo-Carrying.

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Tariff Order Section, 1616 P Street, NW, Washington, DC 20036.)

NATIONAL BUREAU OF STANDARDS

Handbook H28 - Screw-Thread Standards for Federal Services.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

3. REQUIREMENTS

3.1 Description. The toboggan shall be in accordance with Top Assembly TA13220E0992 and as specified herein. The toboggan shall consist of a

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:54Z
Check the source to verify that this is the current version before use.

plywood platform and hardwood parts, plywood runners, wire rope handrails, a fixed wire rope towing hitch and a fixed type lunette coupler. The overall dimensions of the toboggan shall be 8 feet long by 28 inches wide, and shall weigh approximately 120 pounds.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Any data (e.g. shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the supplier or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 First article.

3.2.1 Preproduction model. The supplier shall furnish a toboggan for examination and test within the time frame specified (see 6.2) to prove, prior to starting production, that his production methods will produce toboggans that comply with the requirements of this specification. Examination and tests shall be as specified in section 4 and shall be subject to surveillance and approval by the Government (see 6.3).

3.3 Material. Material shall be as specified on the applicable drawings.

3.3.1 Moisture content. Moisture content of all plywood and hardwood specified on the drawings shall be conditioned to a moisture content of not less than 8 percent nor more than 12 percent.

3.3.2 Hardware. All hardware for the toboggan shall conform to TA13220E0992. All nuts shall be drawn tight. Machine screws shall be of correct length to assure full thread in the nut. All threaded fasteners shall be in accordance with Handbook H28.

3.4 Identification marking. The toboggan shall be identified in accordance with MIL-STD-130. Special marking for the toboggan shall be applied as specified and at the location shown on TA13220E0992

3.5 Workmanship. All parts, components, and assemblies of the toboggan including castings, forgings, molded parts, stampings, seals, and machined surfaces shall be clean and free from sand, dirt, fins, pits, sprues, and

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:54Z
Check the source to verify that this is the current version before use.

other harmful extraneous material. The toboggan shall withstand any operation specified herein without deformation, breakage of connections or malfunction caused by incorrect workmanship. Edges and surfaces exposed to operating and maintenance personnel shall be smooth and rounded to the extent that a hazardous surface does not exist.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Acceptability criteria. Toboggans which conform to all requirements in sections 3 and 5 of this specification and pass all applicable examinations and tests in section 4 of this specification will be considered acceptable by the Government.

4.1.2 Component and material inspection. The supplier is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications, standards, and drawings.

4.1.3 Disassembly inspection. Failure of any test by the preproduction model shall be cause for disassembly, in the presence of a Government representative, of the preproduction model to the extent necessary to determine the cause of the failure. Each disassembled part shall be examined in detail for compliance with this specification and referenced drawings in regard to materials, dimensions, tolerances, and workmanship. Parts not complying with such requirements shall be rejected. Reassembly with accepted parts and retesting shall be the responsibility of the supplier.

4.2 Classification of inspection. Inspection shall be classified as follows:

(a) In-process inspection (see 4.3).
(b) Preproduction inspection (see 4.4).
(c) Quality conformance inspection (see 4.5).
(d) Inspection of preparation for delivery (see 4.7).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:54Z
Check the source to verify that this is the current version before use.

4.3 In-process inspection.

4.3.1 Moisture content, wood. At the time of fabrication of toboggans, each lot of wood shall be tested in accordance with MIL-STD-1363. Non-conformance to 3.3.1 shall be cause for rejection of the lot from which the sample was taken.

4.4 Preproduction inspection.

4.4.1 Examination. The preproduction toboggan shall be examined as specified in 4.6.1. Presence of one or more defects shall be cause for rejection.

4.4.2 Tests. The preproduction toboggan shall be tested as specified in 4.6.2. Failure of the test shall be cause for performing the inspection specified in 4.1.3 or shall be cause for rejection.

4.5 Quality conformance inspection.

4.5.1 Sampling. Sampling for examination shall be in accordance with MIL-STD-105, level II.

4.5.2 Examination. Samples selected in accordance with 4.5.1 shall be examined as specified in 4.6.1. AQL shall be 2.5 for major, and 6.5 for total defects, expressed in terms of defects per hundred units.

4.6 Inspection procedure.

4.6.1 Examination. The toboggan shall be examined as specified herein for the following defects:

Major

101. Material not as specified.
102. Components missing or not as specified.
103. Runner shows crack, delamination, blister, or uneven bottom surface.
104. Runner ends not correctly beveled.
105. Plywood and hardwood not as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:54Z
Check the source to verify that this is the current version before use.

106. Identification or special marking missing or illegible.
107. Hardware (U-bolts, nuts, washers, hooks, D-rings, plates and clips), broken, stripped, fractured, or otherwise damaged.
108. Plating of hardware (where required), not as specified.
109. Dimensions not as specified.

Minor

201. Color not as specified.
202. Workmanship shoddy, not free of burrs, slivers, sharp edges; not clean or free of other harmful extraneous material such as rust or corrosion.
203. Fastening devices not secured.

4.6.2 Tests.

4.6.2.1 Performance. Load the toboggan with 200 pounds of weight equally distributed over length of the toboggan and pull the weighted toboggan over snow or loose sand a distance of 200 feet using two single-trace type harnesses. Repeat the test using one double-trace harness. Evidence of permanent deformation, damage or breaking of any component or failure of the toboggan to complete the test shall constitute failure of this test.

4.7 Inspection of preparation for delivery.

4.7.1 Preproduction pack inspection.

4.7.1.1 Examination. The preproduction pack shall be examined for the defects specified in 4.7.2.2. Presence of one or more defects shall be cause for rejection.

4.7.2 Quality conformance inspection of pack.

4.7.2.1 Sampling. Sampling for inspection shall be in accordance with MIL-STD-105.

4.7.2.2 Examination. Samples selected in accordance with 4.7.2.1 shall be examined for the following defects. AQL shall be 2.5 percent defective.

110. Preservation and packaging not as specified.
111. Packing not as specified.
112. Strapping not class B for level A packing.
113. Marking illegible, incorrect, or incomplete.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:54Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preproduction pack. The supplier shall furnish a preproduction pack for examination within the time frame specified (see 6.2), to prove prior to starting production packaging and packing, that the applied preservation, packaging, packing, and marking comply with the preparation for delivery requirements of this specification. Examination shall be as specified in section 4 and shall be subject to surveillance and approval by the Government (see 6.4). The preproduction pack may be accomplished utilizing either the preproduction model toboggan or a production toboggan. If the preproduction model toboggan is utilized, any preservation, packaging, and packing shall be removed by the supplier at no expense to the Government, when requested by the Government to facilitate comparison between the preproduction model toboggan and production toboggans.

5.2 Preservation and packaging. Preservation and packaging shall be level A or C, as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Unprotected surfaces. Unpainted or otherwise unprotected exterior metal surfaces or components, such as bolts, nuts, pins, exposed threads or any other unprotected exterior metal surfaces not specified herein requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with type P-1 preservative.

5.2.1.2 Wire rope. The wire rope shall be pulled tight and folded back over on the toboggan body and secured to prevent movement.

5.2.1.3 Technical publications. Technical publications shall be individually preserved, method IC-1, and securely fastened to the body of the toboggan.

5.2.2 Level C. The toboggan and technical publications shall be preserved and packaged to afford adequate protection against damage during shipment from supply source to the initial destination.

5.3 Packing. Packing shall be level A or C, as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:54Z
Check the source to verify that this is the current version before use.

5.3.1 Level A. The toboggans, preserved and packaged as specified in 5.2, shall be packed in a close-fitting wood crate conforming to PPP-C-650, style A, type optional, in quantities as specified (see 6.2), not to exceed the weight and dimensional limitations of the crate specification. The toboggans shall be arranged in horizontal stacks with blocking between stacks when applicable. Blocking between toboggans within each stack shall rest on the center and rear cross members and shall be of sufficient thickness so that any superimposed load will not be supported by the ends of the toboggan or the eyebolts. Anchoring of the contents shall be in accordance with the appendix to the crate specification. All strapping shall be class B. The contents of the crate shall be covered by a shroud in accordance with the appendix to the crate specification.

5.3.2 Level C. The toboggans shall be packed to assure carrier acceptance and safe delivery to destination at lowest rates in compliance with Uniform Freight Classification rules or National Motor Freight Classification rules.

5.4 Marking. In addition to any special marking required by the contract or order, marking for identification and shipment shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The toboggan is intended for use in carrying various types of cargo over snow and ice covered terrain.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Time frame required for submission of preproduction model (see 3.2.1).
(c) Time frame required for submission of preproduction pack (see 5.1).
(d) Level of preservation and packaging and level of packing required (see 5.2 and 5.3).
(e) Number of toboggans to be packed together (see 5.3.1).

6.3 Preproduction model. Any changes or deviations of production toboggans from the approved preproduction model during production will be subject to the approval of the contracting officer. Approval of the preproduction model will not relieve the supplier of his obligation to furnish toboggans conforming to this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:54Z
Check the source to verify that this is the current version before use.

6.4 Preproduction pack. Any changes or deviations of production packs from the approved preproduction pack will be subject to the approval of the contracting officer. Approval of the preproduction pack will not relieve the supplier of his obligation to preserve, package, pack, and mark the toboggans in accordance with this specification.

6.5 Data requirements. The contracting officer should include requirements for such data as technical publications, instructional materials, illustrated parts lists, and supplier's maintenance and operation manual to be furnished with each toboggan.

6.6 Provisioning. The contracting officer should include provisioning requirements for repair parts and maintenance tools as necessary (including any special tools), and instructions on shipment of toboggans.

Custodian:

Army - ME

Preparing activity:

Army - ME

Project No. 3920-0096

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:54Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION MIL-T-11727B(ME) -Toboggan, Cargo-Carrying (Towed Type, 28 Inches By 8 Feet

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1426
11 Oct 72 (Rev)

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:54Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. ARMY MOBILITY EQUIPMENT
RESEARCH, DEVELOPMENT
CENTER
FORT BELVOIR, VIRGINIA 22060

OFFICIAL BUSINESS
AMSME-RZD-S

POSTAGE AND FEES PAID
DOD-314

COMMANDER
U. S. ARMY MOBILITY EQUIPMENT
RESEARCH, DEVELOPMENT CENTER
ATTN: AMSME-RZD-S
FORT BELVOIR, VIRGINIA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T21:54Z
Check the source to verify that this is the current version before use.