DD-S-720a
APRIL 4, 1960
SUPERSEDING
Int. Fed. Spec. DD–S–00720 (GSA–FSS)
January 14, 1959 and
Fed. Spec. DD–S–722a (in Part)
April 23, 1953

FEDERAL SPECIFICATION

STOPCOCK, LABORATORY APPARATUS, TAPER-GROUND

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope.—This specification covers interchangeable taper-ground glass stopcocks for ordinary laboratory and industrial work.

1.2 Classification.

1.2.1 *Types.* — Interchangeable taper-ground glass stopcocks shall be furnished in the following types, as specified:

Type I.—Single straight-bore.

Type II.—Single oblique-bore.

Type III.—Double oblique-bore (so-called 3-way).

Type IV.—T-bore.

Type V.—120° bore.

1.2.2 *Compositions and grades.* — Interchangeable taper-ground glass stopcocks shall be furnished in the following compositions and grades of glass, as specified:

Composition 1.—Borosilicate glass.

Grade A.

Grade B.

Note.—When low thermal expansion is required, grade A should be used; when high chemical durability is required, especially in alkaline solutions, grade B should be used.

Composition 2.—Soda-lime glass.

2. APPLICABLE SPECIFICATIONS, STANDARDS, AND OTHER PUBLICATIONS

2.1 Specifications and standards.—The following specifications and standards, of the issues in effect on date of invitation for bids, form a part of this specification:

Federal Specifications:

DD–G–541—Glass (Laboratory).

PPP–B–30—Bags, Shipping, Cushioned.

PPP–B–585—Boxes; Wood, Wirebound.

PPP–B–591—Boxes, Fiberboard, Wood-Cleated.

PPP–B–601 — Boxes, Wood-Cleated-Plywood.

PPP–B–621 — Boxes, Wood, Nailed and Lock-Corner.

PPP–B–636—Box, Fiberboard.

Federal Standards:

Fed. Std. No. 102 — Preservation, Packaging, and Packing Levels.

Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications, Standards, and Handbooks and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a sub-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.

scription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington 25, D. C.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, Seattle, and Washington, D. C.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications, Standards, and Handbooks from established distribution points in their agencies.)

Military Specifications:

MIL–B–138 — Boxes, Wood, Fiberboard-Lined for Overseas Shipment.

MIL–L–10547 — Liners, Case, Waterproof.

Military Standards:

MIL–STD–105 — Sampling Procedures and Tables for Inspection by Attributes.

MIL–STD–129 — Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications.—The following U. S. Department of Commerce publication forms a part of this specification. Unless otherwise specified, the issue in effect on date of invitation for bids shall apply.

CS21–58 — Interchangeable Taper-Ground Joints, Stopcocks, Stoppers, and Spherical-Ground Joints.

(Copies may be obtained upon application, accompanied by money order, coupon, or cash to the Superintendent of Documents, Government Printing Office, Washington 25, D. C. Price 15 cents each.)

3. REQUIREMENTS

3.1 Material.—The stopcocks shall be made of borosilicate or soda-lime glass conforming to the requirements of type I, class A or B, or type II of Federal Specification DD–G–541, as specified. A certificate of compliance shall be furnished as required in Federal Specification DD–G–541.

Note.—Type I, class A or B and type II of Federal Specification DD–G–541 are the same as composition 1, grade A or B and composition 2, respectively, of this specification (see 1.2.2).

3.2 Dimensional requirements.—The designations, dimensions, and tolerances for the stopcocks shall be in accordance with the requirements of Commercial Standard CS21–58.

3.3 Identification marking.—The marking on the stopcocks shall be in accordance with Commercial Standard CS21–58.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Supplier responsibilities for inspection.—Unless otherwise specified herein, the supplier is responsible for the performance of all inspection requirements prior to submission for Government inspection and acceptance. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order.

4.2 Sampling. — Sampling for visual and dimensional inspection of the stopcocks shall be in accordance with 4.2.1 and 4.2.2.

4.2.1 *Sampling for inspection.*—A random sample of items shall be taken from each inspection lot offered for Government inspection for visual and dimensional characteristics in accordance with Military Standard MIL–STD–105.

4.2.1.1 *Lot.*—All items of the same grade and size, presented at one time, shall be considered a lot for purposes of acceptance inspection and tests.

4.2.2 *Sampling for continuous production.*—Where there is continuous production for

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.

the Government, and inspection lots include at least 200 items, sampling for Government inspection shall be conducted in accordance with Military Standard MIL–STD–105 at inspection level I.

4.3 Inspection.

4.3.1 *Visual and dimensional examination.*—Each of the sample items selected in accordance with 4.2.1 and 4.2.2 shall be visually and dimensionally examined by the Government inspector to verify compliance with the requirements of this specification. The AQL shall be 2.5 percent defective. Any departures from requirements as listed in this specification, Commercial Standard CS21–58, and Federal Specification DD–G–541 are classified as defects. Any item in the sample containing one or more visual or dimensional defects shall be classified defective. Rejected lots may be offered again for Government inspection provided the contractor has repaired or removed all nonconforming items. The Government inspector shall again select and examine samples from such resubmitted lots to verify compliance with the specification requirements.

4.3.2 *Packaging and packing.*—Failure of any container to conform to the requirements of this specification or the applicable requirements of the referenced container specifications shall be cause for its rejection. Containers which have been rejected may be reworked or replaced to correct defects and resubmitted for acceptance. Before resubmission, full particulars concerning previous rejections and the action taken to correct the defects found in the original containers shall be furnished. Containers rejected after reinspection shall not be resubmitted without the specific approval of the procuring agency.

4.4 Tests. — Tests shall be performed as necessary to satisfy the requirements of 3.1

5. PREPARATION FOR DELIVERY

For civil agency procurement the definitions and applications of the levels of packaging and packing shall be in accordance with Federal Standard No. 102.

5.1 Packaging.

5.1.1 *Level A.*—The stopcocks shall be individually wrapped in a good quality tissue paper and protected by wrapping in flexible corrugated fiberboard. Wrapping and cushioning material shall be secured by tying with cord or sealing with gummed paper tape. Alternately, the stopcocks may be individually packaged in a cushioned shipping bag conforming to Federal Specification PPP–B–30. All packaging shall be accomplished in such a manner as to insure against marring, scratching, or other physical damage to the unit.

5.1.1.1 *Intermediate package.* — Twelve stopcocks, packaged as specified in 5.1.1, shall be overpackaged in an intermediate container conforming to Federal Specification PPP–B–636, type I or II, class 1 or 2, style RSC. The fiberboard shall have a minimum bursting strength of not less than 200 pounds. Box closure and sealing shall be in accordance with the appendix to the box specification.

5.1.2 *Level C.* — The stopcocks shall be packaged as specified in 5.1.1.1.

5.2 Packing.

5.2.1 *Level A.*—The stopcocks, packaged as specified in 5.1.1.1, shall be packed in a snug-fitting wood-cleated fiberboard, wood-cleated plywood, nailed wood, wirebound wood, fiberboard, or fiberboard-lined box conforming to Federal Specification PPP–B–591, PPP–B–601, PPP–B–621, PPP–B–585, or PPP–B–636, or Military Specification MIL–B–138, respectively. The containers shall be fitted with a sealed waterproof case liner conforming to Military Specification MIL–L–10547, type I, grade B, class 2, and appendix thereto. The gross weight shall not exceed 150 pounds.

5.2.2 *Level B.*—The stopcocks, packaged as specified in 5.1.1.1, shall not require overpacking.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.

5.2.3 *Level C.*—The stopcocks, packaged as specified in 5.1.1.1, shall not require overpacking.

5.3 Marking.

5.3.1 *Civil agencies.*—In addition to any special marking required by the contract or order, marking shall be in accordance with Federal Standard No. 123.

5.3.2 *Military agencies.*—In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with Military Standard MIL–STD–129.

6. NOTES

6.1 Ordering data.—Purchasers should exercise any desired options offered herein, and procurement documents should specify the following:

(*a*) Title, number, and date of this specification.

(*b*) Type, composition, grade, and size required (see 1.2 and 3.2).

(*c*) Selection of the applicable levels of packaging and packing (see 5.1 and 5.2).

6.2 Transportation description.—Transportation description applicable to this item is:

Glassware, chemical laboratory.
Carload minimum weight 18,000 pounds, subject to Rule 34, Uniform Freight Classification.
Glassware, laboratory.
Motor volume minimum weight 18,000 pounds.

Notice. — When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded, by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

MILITARY INTERESTS:
Army—C O
Navy—Md
Air Force.

Copies of this specification may be purchased for 5 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.