EE-E-911G
December 1, 1971
SUPERSEDING
Fed. Spec. EE-E-911f
August 2, 1966

FEDERAL SPECIFICATION

EXTRACTS, FLAVORING: AND FLAVORS

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers the requirements for flavoring extracts and flavors for use by agencies of the Federal Government.

1.2 Classification.

1.2.1 Types and styles. Flavoring extracts and flavors shall be of the following types and styles as specified (see 6.1):

Type A - Lemon

Style:

1 - Extract
2 - 4X strength extract
3 - Terpeneless extract
4 - Flavor, nonalcoholic

Type B - Vanilla

Style:

1 - Extract
2 - 4X strength extract
3 - Extra concentrated extract
4 - Flavor, imitation

Type C - Orange

Style:

1 - Extract
2 - Terpeneless extract
3 - Flavor, nonalcoholic

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.

Type D - Maple flavoring, imitation
Type E - Rum flavoring, imitation
Type F - Peppermint, extract
Type G - Banana flavoring, imitation
Type H - Cherry flavoring, imitation
Type I - Pineapple flavoring, imitation
Type J - Brandy flavoring, imitation
Type K - Sherry flavoring
Type L - Black walnut flavoring, imitation

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

PPP-C-96 - Cans, Metal, 28 Gage and Lighter.
PPP-G-460 - Glass Containers, One Gallon Capacity and Smaller, for Other than Medicinal Products; Packaging and Packing of.

Federal Standard:

FED-STD-123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks, as outlined under General Information in the Index of Federal Specifications, and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers, at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

MilitarySpecification:

MIL-L-35078 - Loads, Unit: Preparation of Nonperishable Subsistence.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.

Military Standards:

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-668	-	Sanitary Standards for Food Plants.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

U.S. Department of Health, Education and Welfare

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

U.S. Department of Agriculture

United States Standards for Grades of Maple Sirup

United States Standards for Condition of Food Containers

(Application for copies should be addressed to the Information Division, Consumer and Marketing Service, U.S. Department of Agriculture, Washington, D.C. 20250.)

Association of Official Analytical Chemists

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, P.O. Box 540, Benjamin Franklin Station, Washington, D.C. 20044.)

National Research Council

Food Chemicals Codex

(Application for copies should be addressed to the Office of Director, National Academy of Sciences, National Research Council, Washington, D.C. 20418.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.

The United States Pharmacopoeial Convention, Inc.

Pharmacopoeia of the United States

(Application for copies should be addressed to the United States Pharmacopoeial Convention, Inc., 46 Park Avenue, New York, N.Y. 10016.)

3. REQUIREMENTS

3.1 Material.

3.1.1 Extracts. The product shall conform in name to the plant used as its flavoring principle and shall produce a flavor and aroma of desirable quality for food purposes. Whenever reference to oil of lemon or oil of orange (excluding terpeneless oils of lemon, orange or peppermint) is made in this specification, products meeting the requirements of the Food Chemical Codex shall be used.

3.1.2 Cottonseed oil. Cottonseed oil shall be thoroughly refined, winterized, sweet, neutral, and free from sediment, off-flavors, and odors. It shall remain clear after being held for 5 hours at 32°F., and shall have a free fatty acid content not to exceed 0.05 percent when tested as specified in 4.3.2.

3.1.3 Alcohol. Alcohol shall comply with purity requirements of the U.S.P.

3.2 Description of types and styles.

3.2.1 Type A, lemon. The end product shall be clear, transparent, and free of sediment, at a temperature of 65-75°F.

3.2.1.1 Style 1, extract. Style 1 shall be prepared from oil of lemon and ethyl alcohol of proper strength. It shall contain not less than 80 percent by volume of ethyl alcohol and not less than 5 percent by volume of oil of lemon.

3.2.1.2 Style 2, 4X strength extract. Style 2 shall be prepared from oil of lemon and ethyl alcohol of proper strength and shall contain not less than 20 percent by volume of oil of lemon. As specified (see 6.1), stronger extracts, not to exceed 60 percent oil of lemon, are acceptable under this specification.

3.2.1.3 Style 3, terpeneless extract. Style 3 shall be prepared by shaking oil of lemon with dilute ethyl alcohol, or by dissolving terpeneless oil of lemon of proper strength in dilute ethyl alcohol. The product shall contain not less than 0.2 percent by weight of citral derived solely from oil of lemon. The product shall contain not less than 45 percent by volume of ethyl alcohol.

3.2.1.4 Style 4, flavor nonalcoholic. Style 4, shall be a mixture prepared in the proportion of 20 volumes oil of lemon diluted to 100 volumes with the cottonseed oil specified in 3.1.2. Preservatives (antioxidants) suitable for food use may be added. The finished product shall be free from rancidity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.

3.2.2 Type B, vanilla. The end product shall be light brown to brown-black and free of sediment. Vanilla extract, is the solution in aqueous ethyl alcohol of the savory and odorous principles extractable from vanilla beans. Vanilla extract may contain one or more optional ingredients such as glycerine, propylene glycol, sugar (including invert sugar), dextrose and corn sirup (including dried corn sirup).

3.2.2.1 Style 1, extract. Style 1 shall be prepared, without added flavoring or coloring, from properly cured vanilla beans. The product shall contain, in 100 milliliters (ml), the soluble material from not less than 10 grams (g) of vanilla beans, based on a maximum of 25 percent moisture, shall contain not less than 35 percent by volume of ethyl alcohol, and shall show a Wichmann lead number not less than 0.70. The strength of the extract in respect to the vanillin and vanilla resins, which shall be derived solely from the beans used, shall be not less than 0.17 percent for vanillin and not less than 0.10 percent for vanilla resins.

3.2.2.2 Style 2, 4X strength extract. Style 2 shall be prepared, without added flavoring or coloring, from properly cured vanilla beans. The product shall contain, in 100 ml, the soluble material from not less than 40 g of vanilla beans and shall contain not less than 35 percent by volume of ethyl alcohol. When one part by volume of the product is diluted with three parts by volume of dilute alcohol (40 percent by volume) the resulting mixture shall comply with the requirements specified in 3.2.2.1 for vanilla extract except in regard to alcohol content.

3.2.2.3 Style 3, extra concentrated extract. Style 3 shall be prepared, without added flavoring or coloring, from properly cured vanilla beans. The product shall contain, in 100 ml, the soluble material from not less than 100 g of vanilla beans and shall contain not less than 35 percent by volume of ethyl alcohol. When one part by volume of the product is diluted with nine parts by volume of dilute ethyl alcohol (40 percent by volume), the resulting mixture shall comply with the requirements specified in 3.2.2.1 for vanilla extract, except in regard to ethyl alcohol content.

3.2.2.4 Style 4, flavor, imitation. Style 4 shall contain not less than 2.8 g of vanillin, or 0.94 g of ethyl vanillin, or alternatively, a blend of 1.4 g of vanillin and 0.47 g of ethyl vanillin, per 100 ml. Alcohol, glycerine, propylene glycol, or any combination of these shall be used in an amount necessary so that the vanillin or ethyl vanillin will not crystallize out when the finished product is subjected to a temperature of 32°F. for 8 hours. The product shall be artificially colored with caramel. No preservative shall be added. The product shall have a pleasant flavor and odor. The vanillin, ethyl vanillin, glycerine, and propylene glycol, shall comply with purity requirements specified in the U.S.P.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:43Z
Check the source to verify that this is the currentversion before use.

3.2.3 Type C, orange. The end product shall be clear, transparent, and free sediment when at a temperature of 65-75°F.

3.2.3.1 Style 1, extract. Style 1 shall be prepared from oil of orange and ethyl alcohol of proper strength. It shall contain not less than 80 percent by volume of ethyl alcohol and not less than 5 percent by volume of oil of orange.

3.2.3.2 Style 2, terpeneless extract. Style 2 shall be prepared by shaking oil of orange with dilute ethyl alcohol, or by dissolving terpeneless oil of orange of proper strength in dilute ethyl alcohol. The product shall correspond in flavoring strength to orange extract. A solution of not less than 45 percent ethyl alcohol shall be used for the extraction.

3.2.3.3 Style 3, flavor, nonalcoholic. Style 3 shall be a mixture prepared in the proportion of 20 volumes of oil of orange diluted to 100 volumes with the cottonseed oil specified in 3.1.2. Preservatives (antioxidants) suitable for food use may be added. The finished product shall be clear and free from sediment and rancidity.

3.2.4 Type D, maple imitation. The imitation flavoring maple and coloring ingredients, shall be stable products of such quality that when a sirup is made from not less than 3-7/8 pounds of sugar dissolved in 1 quart of boiling water and flavored with 1/2 ounce of the imitation flavor, the resulting sirup shall have a flavor characteristic of the flavor of maple and shall not have a bitter, flat, weak, or medicinal flavor. The color of the sirup shall be not lighter than light amber nor darker than medium amber as represented by the color standards for maple sirup in U.S. Standards for Grades of Maple Sirup.

3.2.5 Type E, rum flavoring, imitation. Imitation rum flavoring shall be a homogeneous solution composed of a blend of organic compounds such as extractives, ethers, esters, aldehydes, ketones, vanillin, sugar, certified color in edible solvents, e.g., propylene glycol and water. It shall be the flavor of rum and contain not less than 35 percent alcohol by volume.

3.2.6 Type F, peppermint, extract. Peppermint oil in the extract shall be of the natural plant, Mentha piperita origin, conforming to the requirements of 3.1.1. The extract shall contain oil of peppermint, water and not less than 89 percent alcohol by volume. The extract shall possess a characteristic flavor and aroma of peppermint.

3.2.7 Type G, banana flavoring, imitation. The imitation banana flavoring shall contain amyl acetate, or its equivalent other artificial flavors, certified color and water. The extract shall have a characteristic banana flavor and aroma.

3.2.8 Type H, cherry flavoring, imitation. Imitation cherry flavoring shall contain, oil of bitter almonds, esters, aldehydes, certified color and water. Substitution of essential ingredients may be made if they produce the desired cherry flavor and aroma characteristics.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.

3.2.9 Type I, pineapple flavoring, imitation. Imitation pineapple flavoring shall contain esters, aldehydes, ketones, pineapple extract, certified color, propylene glycol and water. It shall not contain less than 42 percent alcohol by volume. The extract shall possess a characteristic flavor and aroma of pineapple.

3.2.10 Type J, brandy flavoring, imitation. Imitation brandy flavoring shall contain esters, essential oils, vanillin, propylene glycol, sugar, certified color and water. It shall not contain less than 35 percent alcohol by volume. The extract shall possess a characteristic flavor and aroma of brandy.

3.2.11 Type K, sherry flavoring. Sherry flavoring shall contain concentrated sherry wine and sugar. It shall not contain less than 12 percent alcohol by volume. The extract shall possess a flavor and aroma characteristic of sherry wine.

3.2.12 Type L, black walnut flavoring, imitation. Imitation black walnut flavoring shall contain esters, aldehydes, essential oils, caramel color and water. It shall not contain less than 45 percent alcohol by volume. The substitution of essential ingredients may be made if they produce the desired flavor and aroma characteristic of black walnut.

3.3 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act, and regulations promulgated thereunder.

3.4 Workmanship. The product shall be prepared, processed and packaged under modern sanitary conditions and in accordance with good commercial practices. For military agencies, the product shall be processed in establishments meeting the requirements of MIL-STD-668.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling. Samples of finished products covered by this specification and samples of any materials, components, or constituents entering into the preparation of the finished products may be taken at any time by the Government inspector to determine compliance with the requirements.

4.2 Inspection.

4.2.1 General. Inspection shall be made by the procuring agency or a duly authorized representative, at the time and place designated by the procuring agency. It may be made at the site of manufacture, both during and after processing, at any suitable point in transit, or after delivery to the point of destination.

Source: https://assist.dla.mil -- Downloaded: 20261O-26T11:43Z
Check the source to verify that this is the currentversion before use.

4.2.2 Factory inspection. The passing as satisfactory of any detail of processing or materials shall not relieve the contractor of responsibility f faulty workmanship or materials which may be discovered at any time prior to final acceptance.

4.2.3 Final inspection. Unless otherwise specified, final inspection shall be made after delivery to the point of destination (see 6.4 and 6.5).

4.2.4 Condition inspection of containers. When inspection of product for quality and condition is performed by the U.S. Department of Agriculture, the United States Standards for Condition of Food Containers shall apply. (For criteria governing inspection of containers for the military agencies, (see 4.2.7.3)).

4.2.5 Responsibility for inspection. The supplier is responsible for meeting all the provisions of the specification prior to submission of supplies to the Government for acceptance. Unless otherwise specified in the contract or order, the supplier is required to perform the examination and tests prescribed herein, using his own or any other inspection facilities and services acceptable to the Government.

4.2.5.1 Inspection records of the examination and tests shall be complete and made available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2.6 Preacceptance inspection (plant sanitation inspection) for military agencies. Product shall be rejected if produced in plants not meeting the requirements of 3.4.

4.2.7 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.2.7.1 Component and material inspection. In accordance with 4.2.5 and 4.2.5.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification.

4.2.7.1.1 Examination of ingredients. Conformance of ingredients to specific quality standards (i.e. Food Chemical Codex or U.S.P.), shall be ascertained by examination of pertinent labels, invoices or other valid documents. In addition, cottonseed oil shall be examined to determine conformance to requirements for flavor, odor and sedimentation. The sample unit for examination shall be 1 pint of oil extracted from a primary container. The sample size shall be five. In the event a lot consists of less than five containers, a sample shall be extracted from each container in the lot. Nonconformance shall indicate an unacceptable ingredient and use of such shall be cause for rejection of the involved finished product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.

4.2.7.1.2 Testing of caps and cottonseed oil. Testing of bottle caps and cottonseed oil shall be in accordance with table I. Test requirements shall be average requirements. A test failure shall indicate an unacceptable component and use of such shall be cause for rejection of the involved end item.

TABLE I. Testing of caps and cottonseed oil

Component	Sample unit	Lot size expressed in	Inspection level	Characteristics	Results reported	Test ref and rqmt para
Caps	6 caps	Cap	S-1	Tinplate	Nearest 0.01 lb/ base box	5.1.1 4.3
Cottonseed oil	1 pint composite 1/	Pounds	S-1	Free fatty acids	Nearest 0.01 percent	3.1.2 4.3
				Cold test	Pass or fail	

1/ The composite shall be derived from the number of containers indicated by the inspection level.

4.2.7.2 Process examination. Unless otherwise specified, (see 6.1) examination shall be performed to determine conformance to formulation requirements as concerns kinds of ingredients. Formulation records shall be maintained. Nonconformance shall be cause for rejection of the involved finished product.

4.2.7.3 Examination of end item. Examination shall be in accordance with tables III through VI, 4.2.7.3.1 and 4.2.7.3.2. Sampling plans shall be in accordance with table II. The acceptable quality levels (AQLs) shall be expressed as defects per hundred units for tables III and V and percent defective for tables IV and VI.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.

TABLE II. Sampling plans

Table	Sample unit	Lot size expressed in	Inspection level	AQLs Major A	Major B	Minor	Total
III	1 filled and closed bottle	Bottles	I	0.25	1.5	-	4.0
IV	1 filled bottle	Bottles	S-3	-	-	2.5	-
V	1 filled bottle	Bottles	S-2	-	1.5	-	-
VI	1 labeled bottle	Bottles	S-2	-	-	2.5	-

TABLE III. Examination of bottles

Category			Defects
Major A	Major B	Minor	
	151		Not style specified
101			Leakers, broken or cracked
	152		Checked, chipped
		201	Not clean
	153		Label missing
		202	Label not hard sized or varnished
		203	Label insecure
	154		Nomenclature on label missing, incorrect or illegible
		204	Other required label information missing, incorrect or illegible
	155		Cellulose band or plastic film adhesive for use on screw cap missing, not tightly securing cap to bottle, split or cracked (level A bottle)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.

TABLE III. Examination of bottles (cont'd)

Category			Defects
Major A	Major B	Minor	
		205	Overlap of plastic film adhesive less than 1-inch, or width of plastic film adhesive less than 3/4 inch (level A bottle)
	156		Cap loose 1/
	157		Cap not coated outside and inside with enamel, or enamel incomplete or easily abraded with fingertip (level A bottle)
	158		Cap rusty 2/
	159		Liner or facing material in caps missing (level A bottle)

1/ For determining tightness of closure, the following is applicable; condition container to 65-75°F. Place the container upright on top of a filled and closed fiberboard box. Grasp the sides of the cap firmly with fingertips and turn cap gently counter-clockwise with a minimum of downward pressure for one complete revolution. If cap turns and the container remains stationary, a defect shall be scored.

2/ Rust that can be removed with a soft cloth shall not be considered pitted rust.

TABLE IV. Examination for net volume of containers 1/

Category	Defect
Minor	
201	Volume more than 5 percent under specified volume (containers required to have not more than 16 ounces) 2/
202	Volume more than 2 percent under specified volume (containers required to have more than 16 ounces) 3/

1/ Lot shall be rejected if the sample data indicates a lot average volume less than the specified volume. Product shall be at 65-75°F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.

2/ Volume shall be reported to nearest ml for containers required to have 2 ounces; nearest 1/16 ounce for 8-ounce containers and nearest 1/8 ounce for 16 ounce containers.

3/ Volume shall be reported to nearest 1/4 ounce.

TABLE V. Examination of product 1/

Category		Defects
Major B	Minor	
	Type A 2/	
151		Not clear, transparent and free of sediment
152		Style 4 rancid
	Type B	
153		Not light brown to brown - black in color
154		Not free of sediment
155		Style 4 not a pleasant flavor and odor
	Type C 2/	
156		Not clear, transparent and free of sediment
157		Not equal in flavor strength to type C, style 1
158		Style 3 rancid
	Type D 3/	
159		Lighter than light amber or darker than medium amber - as represented by color standards
160		Not a characteristic flavor of maple
161		Bitter, flat, weak, or medicinal flavor
	Type E	
162		Not a homogeneous solution
163		Not a characteristic rum flavor
	Types F through L	
164		Not characteristic flavor and aroma of pertinent type

1/ Presence of foreign material (e.g. dirt, filth, glass, wood, metal, insect, paint, etc.) shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.

2/ Product shall be at 65-75°F.

3/ Prepare a solution of sirup as specified in 3.2.4. Prepare one solution per sample unit.

TABLE VI. Examination of label adhesion 1/

Category	Defect
Minor	
201	Displacement of label

1/ Applicable only to labeled glass containers packed for overseas shipment.

4.2.7.3.1 Examination of packing, marking and shipping containers. Examinations shall be in accordance with the quality assurance provisions for the end item as contained in PPP-G-460.

4.2.7.3.2 Examination of unit loads. Unit loads shall be examined in accordance with the quality assurance provisions of MIL-L-35078.

4.2.7.4 Testing of finished product. The finished product shall be tested for the analytical requirements specified for the pertinent type or style of product. Test procedures shall be as specified in 4.3. In addition, type B, style 4 product shall be submitted to the cold test specified in 3.2.2.4 to determine the presence of crystals. The sample for testing shall be an 8-ounce composite of product derived from the number of primary containers indicated by inspection level S-2. Lot size shall be expressed in primary containers. Test results shall be reported to the same unit or decimal place as specified for the pertinent requirement, except that the cold test for crystalization of type B, style 4 product shall be reported as pass or fail. A test failure shall be cause for rejection of the lot.

4.3 Test methods. Examination and test procedures which differ from those specified herein, unless otherwise excepted, may be used by the supplier if they provide a quality assurance equivalent to that specified. If the Government contracting officer determines that such procedures and controls do not provide, as a minimum such quality assurance, the supplier will use the procedures set forth herein. In case of dispute as to examination or test results, the procedures specified herein will govern.

4.3.1 Examination procedures.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.

4.3.1.1 Examination of label adhesive for water-resistance. The label adhesive shall be examined for water-resistance as follows:

Submerge glass container with label affixed into water, at room temperature for 4 hours.

Remove from water and remove excess water by blotting with paper towels.

Press finger firmly against the label (in an area where adhesive has been applied) and;

Move finger (still pressed against the label) towards the bottom of bottle.

Displacement of the label indicates failure to meet the requirements.

4.3.2 Test procedures.

4.3.2.1 Chemical analysis. Chemical analysis shall be made in accordance with the following methods from the Official Methods of Analysis of the Association of the Official Analytical Chemists:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.

Chapter and section	Test and method	Type A, styles 1,2,3,4	Type B, styles 1,2,3,4	Type C styles 1,2,3	Type E	Type F	Type I	Type J	Type K	Type L
Flavors; extracts, section:										
Lemon, orange, lime, or peppermint extracts and flavors	Alcohol	X X		X X	X	X	X	X	X	X
	Citral	X		X						
	Oils of lemon and orange in extracts	X X X		X X X						
	Oils of lemon, orange, lime, or peppermint in oil base flavors by distillation	X		X		X				
Flavoring extracts, section:										
Vanilla extract and its substitutes	Vanilla resins, quantitive methods		X X X							
	Vanillin, ethyl vanillin, and coumarin, chromatographic separation method		X X X X							
	Lead number (Wichmann)		X X X							
	Alcohol		X X X							
Oils, fats, waxes, section:										
Cottonseed oil	Halphen	X		X						
Oils, fats, waxes, section:										
Free fatty acids in crude and refined oils	Free fatty acid (as oleic) National Cottonseed Association method (official)	X		X						

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:13:37Z
Check the source to verify that this is the current version before use.

4.3.2.2 Tin plate. Tin plate of caps shall be determined by any method specified in PPP-C-96.

5. PREPARATION FOR DELIVERY

5.1 Packaging. The product shall be packaged in accordance with level A or C, as specified (see 6.1).

5.1.1 Level A. As specified (see 6.1), the product in quantities specified in table VII shall be filled into an amber or flint glass bottle. The closure shall be made with a tightly-applied, knurled, screwcap with curled edge made from commercial 0.25 pound electrolytic tinplate. The cap shall be fitted with a liner and facing material suitable for the product. The cap shall be coated outside with a corrosion-resistant lacquer or enamel and inside with an enamel suitable for the product. The cap shall be secured in position with a shrunk-on cellulose band or a pressure-sensitive, plastic film, adhesive tape, 3/4 inch in width. The tape shall overlap itself a minimum of 1-inch.

TABLE VII. Quantities to be packaged (in fluid ounces)

Item	2	4	8	16	32
Extract, lemon	X	X	X		X
Extract, 4X strength lemon		X		X	X
Extract, terpeneless, lemon		X		X	X
Nonalcoholic flavor, lemon			X	X	X
Extract, vanilla	X	X	X		X
Extract, 4X strength, vanilla		X		X	X
Extract, extra conc., vanilla	X	X	X		X
Imitation, artifically flavored, and colored vanilla			X	X	X
Extract, orange	X	X	X		
Extract, terpeneless, orange		X		X	X
Flavor, nonalcoholic, orange			X	X	X
Flavor, maple, imitation			X	X	X
Flavor, rum, imitation				X	X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.

TABLE VII. Quantities to be packaged (in fluid ounces) (cont'd)

Item	2	4	8	16	32
Extract, peppermint			X	X	
Flavor, banana, imitation			X	X	
Flavor, cherry, imitation			X	X	
Flavor, pineapple, imitation			X	X	
Flavor, brandy, imitation			X	X	
Flavor, sherry			X	X	
Flavor, black walnut, imitation			X	X	

5.1.2 Level C. Unless otherwise specified, commercial packaging is acceptable.

5.2 Packing. The bottles of extract shall be packed in accordance with level A, B or C requirements of PPP-G-460, as specified (see 6.1).

5.3 Unit loads. The product, packed as specified in 5.2, shall be arranged in unit loads in accordance with MIL-L-35078, for the type and class of load specified (see 6.1).

5.4 Labeling and marking.

5.4.1 Civil agencies.

5.4.1.1 Bottles. Unless otherwise specified, any labeling which complies with the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder is acceptable. Labels shall clearly indicate the strength of type A, style 2, and type B, styles 2 and 3 product (see 3.2.1.2, 3.2.2.2, and 3.2.2.3), and label of type B, style 2, shall indicate that the product is approximately four times the strength of regular vanilla extract (style 1).

5.4.1.2 Shipping containers. Shipping containers shall be marked in accordance with FED-STD-123 and PPP-G-460.

5.4.2 Military agencies.

5.4.2.1 Bottles. Bottles shall be labeled as specified in 5.4.1.1. The information shall be printed on a hard-sized or varnished label, affixed to bottle with a water-resistant adhesive (see 4.3.1.1).

5.4.2.2 Shipping containers. Shipping containers shall be marked in accordance with MIL-STD-129 and PPP-G-460.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:43Z
Check the source to verify that this is the current version before use.

5.4.2.3 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type and style of product required (see 1.2.1).
(c) If stronger extract than that specified for type A, style 2 is desired (see 3.2.1.2).
(d) When chemical analysis is required (see 4.3.2.1).
(e) Quantity of product to be packaged (see 5.1.1, 5.1.2, and table VII).
(f) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
(g) When specified, type and class of unit load required (see 5.3).

6.2 If samples with bids are necessary, they should be specifically asked for in the invitation for bids, and the particular purpose to be served by the bid sample should be definitely stated.

6.3 Federal specifications do not include all types, classes, grades, etc., of the commodities indicated by the titles of the specifications, or which are commercially available, but are intended to cover the types, etc., which are suitable for Federal Government requirements.

6.4 Supplier's inspection. The supplier should be required to assure that the product conforms with the specification prior to submission to the Government for final inspection.

6.5 Destination inspection (civil agencies). When finished product has been inspected and passed at point other than destination, the contract should require that the product be inspected at destination for identity, condition, and quantity only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.

MILITARY CUSTODIANS:

Army - GL
Navy - SA
Air Force - 45

Review activities:

Army - MD
Navy - MC, MS
DP - SS

Preparing activity:

Army - GL

CIVIL AGENCY INTEREST:

GSA
VA
AGR
HEW

Orders for this publication are to be placed with the General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 20 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

Extracts, Flavoring: and Flavors EE-E-911G

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. Army Natick Laboratories
Natick, Massachusetts 01760

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding General
U. S. Army Natick Laboratories
ATTN: AMXRES-BQS
Natick, Massachusetts 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.