EE-P-002152A(Army-GL)
May 29, 1985
SUPERSEDING
EE-P-002152(Army-GL)
June 30, 1982

INTERIM FEDERAL SPECIFICATION

APPLE DESSERT, TRAY PACK

This interim Federal specification was developed by the U.S. Army Natick Research and Development Center, Natick, MA 01760-5014, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for change to the preparing activity at the address shown above.

1. SCOPE

1.1 Scope. This specification covers apple dessert in tray pack cans.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

TT-C-495 - Coatings, Exterior, for Tinned Food Cans
PPP-B-636 - Boxes, Shipping, Fiberboard

(Activities outside the Federal Government may obtain copies of Federal specifications, standards, and commercial item descriptions as outlined under General Information in the Index of Federal Specifications, Standards and Commercial Item Descriptions. The index, which includes cumulative bi-monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

FSC 8940

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:44Z
Check the source to verify that this is the current version before use.

(Single copies of this specification, and other Federal specifications, and commercial item descriptions required by activities outside the Federal Government for bidding purposes are available without charge from General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Houston, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA.

(Federal Government activities may obtain copies of Federal standardization documents, and the Index of Federal Specifications, Standards and Commercial Item Descriptions from established distribution points in their agencies.)

Military Specification:

MIL-L-1497 - Labeling of Metal Cans for Subsistence Items.
MIL-L-35078 - Loads, Unit: Preparation of Nonperishable Subsistence Items; General Specification for

Military Standards:

MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-900 - Bacterial Standards for Starches, Flours, Cereals, Alimentary Pastes, Dry Milks and Sugars used in the Preparation of Thermostabilized Foods for the Armed Forces.

(Copies of Military specification and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Laws and Regulations:

U.S. Department of Health and Human Services

Federal Food, Drug and Cosmetic Act and Regulations Promulgated Thereunder

(21 CFR PARTS 1-199)

Definition and Standards of Identity for Oleomargarine and Margarine

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:44Z
Check the source to verify that this is the currentversion before use.

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

U.S. Department of Agriculture

U.S. Standards for Grades of Canned Apple Juice

U.S. Standards for Grades of Canned Apples

(Application for copies should be addressed to the Chief, Processed Products Branch, Fruit and Vegetable Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

U.S. Standards for Condition of Food Containers

(Application for copies should be addressed to the Director, Market Research and Development Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

Environmental Protection Agency (EPA)

National Interim Primary Drinking Water Regulations

(Application for copies should be addressed to the Office of Drinking Water WH550, Environmental Protection Agency, Washington, DC 20460.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

Association of Official Analytical Chemists (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

National Academy of Sciences

Food Chemicals Codex

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:44Z
Check the source to verify that this is the currentversion before use.

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 First article. When specified, a sample shall be subjected to the first article inspection (see 4.3, 6.1 and 6.3).

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, off-odors, off-flavors, and off-colors.

3.2.1 Apples, canned, sliced, or apples fresh. Sliced canned apples shall be U.S Grade A of the U.S. Standards for Grades of Canned Apples. Fresh apples shall be any variety suitable for canning. They shall not be overripe and shall be free from decay, worm holes, freeze injury and internal breakdown. If fresh apples are used, the requirements for absence of defects shall be equal or better than that specified for U.S. Grade A of the U.S. Standards for Grades of Canned Apples.

3.2.2 Juice, apple, canned. Canned apple juice shall be U.S. Grade A of the U.S. Standards for Grades of Canned Apple Juice. The apple juice shall be Style I (clear).

3.2.3 Sugar, granulated. Sugar shall be white, refined, sucrose, granulated cane or beet, or a combination of both and shall comply with MIL-STD-900.

3.2.4 Water. Water used for formulation, ice making and washing shall conform to the National Interim Primary Drinking Water Regulations.

3.2.5 Margarine. The margarine shall conform to the Food, Drug and Cosmetic Act, Standard of Identity for Margarine. The margarine shall have a sweet pleasing taste and aroma free from rancidity or other objectionable flavors and odors. It shall have a medium yellow color and a smooth body and texture free of crumbliness, graininess, grittiness, oiliness or droplets of free moisture. The margarine shall be in excellent condition, free from mold, slime or discoloration.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:44Z
Check the source to verify that this is the currentversion before use.

3.2.6 Starch, waxy maize, modified. The starch shall be white, odorless, finely pulverized, modified waxy maize starch for use in canned foods. The modified starch shall demonstrate initial viscosity development in the temperature range of 140° - 170°F and a typical viscosity (be fully hydrated) at common retort temperatures. It shall resist breakdown at low pH, under sheer stress, and conditions of cold storage. The starch shall be bland with essentially no cereal or starch taste and shall comply with MIL-STD-900.

3.2.7 Juice, lemon. Lemon juice shall be prepared from the unfermented juice, obtained from fresh sound mature and thoroughly cleaned fruit of one or more of the high acid varieties of the species Citrus limon (limonia). Such lemon juice may be canned or frozen, single strength or concentrated.

3.2.8 Salt. Salt shall be non-iodized, white, refined sodium chloride, with or without anti-caking agents.

3.2.9 Cinnamon, ground. Ground cinnamon shall be the dried bark of Cinnamomum burmanii Blume, commonly known as "Korintz Cinnamon". The cinnamon shall contain not less than 1.5 mL of volatile oil per 100 grams and be of such size that not less than 95 percent shall pass through a U.S. Standard No. 30 sieve.

3.2.10 Nutmeg, ground. The ground nutmeg shall be derived from dried seeds of Myristica fragrams Houtt. The nutmeg shall have a dull brown color. It shall contain not less than 7.5 mL of volatile oil per 100 grams and be of such size that not less than 95 percent shall pass through a U.S. Standard No. 20 sieve.

3.2.11 Spices, ground. Ground spices shall be uniformly ground spice typical of its varieties and it shall have color, taste, or pungency typical of the product.

3.2.12 Preblended spice and seasoning mixture. Preblended spices and seasonings may be used. The spices and seasonings in the mixture shall comply with the requirements of this specification. The containers used for the spice and seasoning blend shall be labeled with each ingredient and the percentage of each ingredient in the blend. The ingredients shall be in the same proportions as specified in the ingredient formulation.

3.3 Preparation and processing.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:44Z
Check the source to verify that this is the currentversion before use.

3.3.1 Fresh apple preparation. The apples shall be washed thoroughly to remove foreign material and chemical sprays and shall be sorted to remove any which are diseased and otherwise damaged. The sound apples shall be peeled and cored. The peeled apples shall be examined and excess skin, worm holes, blemishes and dark bruises shall be removed. The apples shall be handled rapidly and in such a manner to prevent discoloration prior to slicing. Slicing shall be done to cut the apples into 8 to 12 approximately equal segments. The apple segments shall be immediately washed to remove the apple fines and chips, and blanched to inactivate the enzymes and to remove occluded air. The apple segments shall be thoroughly drained.

3.3.2 Canned apple preparation. Canned apple slices shall be thoroughly drained and the liquid shall be reserved for further use in the formulation of the apple dessert.

3.3.3 Preparation of the dessert. The apple dessert shall be formulated as follows:

Ingredients	Percent by Weight
Apple segments	60.5
Drained liquid and apple juice 1/	14.6
Sugar	14.1
Water	5.9
Margarine	2.2
Starch, modified	1.8
Juice, lemon	0.6
Salt	0.1
Cinnamon, ground	0.1
Nutmeg, ground	0.1

1/ When fresh apple segments are used, canned apple juice shall be used.

a. The drained liquid or apple juice, sugar and salt shall be mixed and heated to 212°F and held until the sugar is completely dissolved.

b. The lemon juice, margarine and apple slices shall be added and gently blended into the mixture and the contents heated to 185°-190°F.

c. A thin slurry of the water, starch, cinnamon and nutmeg shall be prepared and added to the mixture. The entire contents shall be heated to 185°-190°F and held for five minutes in this temperature range.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:44Z
Check the source to verify that this is the currentversion before use.

d. The volume of the final mixture shall be adjusted with water to compensate for evaporation loss during heating and holding.

3.4 Tray pack filling and sealing. Each tray pack can (see 5.1.1.) shall be filled with 98 ounces of product such as to conform to the finished product requirements and to the following requirements.

a. The temperature of the product at the time of filling shall be not less than 190°F.

b. The cans shall be hermetically sealed under minimum of ten inches (Hg) vacuum immediately after filling.

c. The cans shall be inverted immediately after sealing and rapidly cooled to 100°F or less.

3.5 Tray pack thermoprocessing. The filled and sealed cans may be retorted in lieu of hot filling in the following manner:

a. The temperature of the product at time of filling shall be not less than 150°F.

b. The filled and sealed tray pack cans shall be thermostabilized by retorting at 220°F or below to an internal product temperature of 190°-200°F. The product shall be immediately cooled to 100°F or less.

3.6 Finished product requirements. The finished product shall comply with the following requirements.

a. There shall be no foreign material, such as but not limited to dirt, insects, insect parts, hair, wood, paper, paint, glass or metal.

b. There shall be no foreign odor or flavor, such as but not limited to burnt, scorched, stale, sour, rancid, musty, moldy or sulfurous.

c. There shall be no color foreign to the product.

d. The average net weight shall be not less than 98 ounces.

e. No individual can shall weigh less than 96 ounces.

f. The salt content shall be not greater than 0.25 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:44Z
Check the source to verify that this is the current version before use.

g. No individual can shall have a drained weight of less than 60.0 ounces of apples.

h. The apple segments shall not be mushy, hard or rubbery.

i. The sauce shall be glossy and moderately thick.

j. The pH shall be between 3.0 to 4.0, inclusive.

3.6.1 Palatability. The finished product shall be equal to or better than the preproduction sample (see 6.1) in palatability and overall appearance.

3.7 Plant qualification. The product shall be prepared, processed, and packaged in establishments meeting the requirements of Title 21, Code of Federal Regulations, Part 110, "Current Good Manufacturing Practice in Manufacturing, Processing, Packaging or Holding of Human Foods", and the plant sanitation requirements of the appropriate Government inspection agency.

3.8 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this specification. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of supervision necessary to assure compliance with the requirements of this specification.

4.3 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this specification and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this specification or any appearance or palatability failure shall be cause for rejection of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:44Z
Check the source to verify that this is the current version before use.

an ordinary calibration of the tank, or by a mathe-

4.4 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified, or qualified in this document or other applicable purchase specification.

4.4.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, or compliance be evident by examination of pertinent labels, markings, U.S. Grade Certificates, certificates of analyses, or other such supplier-furnished valid documents acceptable to the insepction agency. In addition, prior to use, each ingredient shall be examined organoleptically as necessary to determine conformance to the condition requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.5 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, can interior coating, filling, sealing and packing requirements. Any nonconformance revealed by actual examination or by review or records of time, temperature, and formulation or of other valid documents shall be cause for rejection of the involved product.

4.6. Tray pack inspection. The inspection lot shall include only tray packs produced in one workshift. The USDA reserves the right to separate the inspection lot into smaller inspection lots.

4.6.1 Net weight inspection. Randomly select 30 filled and sealed tray pack cans from the inspection lot and weigh separately. Subtract the average tare weight (determined by randomly selecting and weighing 30 of the empty tray pack cans and lids used in preparing the product and dividing by 30) from the weight of each tray pack in the sample. The results shall be reported to the nearest 1.0 ounce. If the average net weight is less than 98 ounces or if the net weight of any individual can is less than 96 ounces, the lot shall be rejected.

4.6.2 Product inspection. The sample size shall be as indicated by the double sampling plan specified in table I. The tray pack cans shall be selected at random from the lot. The tray pack cans shall be opened and inspected for the defects listed in table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:44Z
Check the source to verify that this is the current version before use.

TABLE I. Double sampling plan for product inspection. 1/

Lot size (cans)	Sample size (No. of cans)	Cumulative sample	Acceptance number	Rejection number
0-3200	8	—	0	2
	8	16	1	2
3201-35000	13	—	0	3
	13	26	3	4

1/ a. If no defects are found in the first sample, the lot shall be accepted.

b. If the number of defects found in the first sample equals or exceeds the rejection number, the lot shall be rejected.

c. If the number of defects found in the first sample exceeds the acceptance number but is less than the rejection number, the second sample shall be inspected. Defects found in the first and second samples shall be combined and if the number of defects in the cumulative sample equals or exceeds the rejection number, the lot shall be rejected.

TABLE II. Product inspection 1/ 2/

Category	Defect
Major	
102	Drained weight of apples is less than 60.0 ounces. 3/
103	Sauce not glossy or not moderately thick.
104	Apple segments mushy, hard or rubbery.

1/ The presence of any foreign material (e.g., glass, dirt, insect parts, hair, wood, metal, etc.), foreign odor or flavor (e.g., burnt, scorched, moldy, rancid, sour, stale, etc.) or foreign color shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:44Z
Check the source to verify that this is the current version before use.

2/ Product not equal to or better than the approved preproduction sample (see 6.1) in palatability or overall appearance shall be cause for rejection of the lot. (This comparison shall be performed only when deemed necessary by the AMS agent.

3/ Procedure for the determination of washed drained weight: The contents of the tray pack can shall be poured into a 12-inch diameter U.S. Standard 1/4 inch sieve such as to distribute the product evenly in the sieve. The sieve and contents shall be immersed in 140°-160°F water, and the sieve shall be agitated with a vigorous swirling motion for 1 minute taking care to separate the product into individual segments. The sieve and contents shall be removed from the water and then reimmersed momentarily twice in succession. The sieve shall be tilted to an approximate 45° angle and allowed to drain 2 min. before determining the drained weight by subtracting the sieve tare weight from the gross weight. The drained weight shall be reported to the nearest 0.1 ounce.

4.6.3 pH testing. Three tray packs shall be selected at random from the lot and individually tested for pH in accordance with the applicable chapter for pH determination of the Association of Official Analytical Chemists. The results shall be reported to the nearest 0.01. If any pH reading is less than 3.0 or more than 4.0, the lot shall be rejected.

4.6.4 Salt content testing. Nine tray packs shall be selected from the lot and distributed as follows:

- Three for laboratory analysis.
- Three for submission to the contractor.
- Three for retention by the AMS agent as a reserve sample.

The three tray packs for laboratory analysis shall be individually tested for salt content in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists, except that preparation of the samples shall be as follows. The cans shall be opened and the entire contents of each can shall be separately blended in a Waring blender or equivalent. The lot shall be rejected if the salt content in any individual tray pack is greater than 0.25 percent. The result shall be reported to the nearest 0.01 percent. Analysis of reserve samples at the request of the contractor shall not be

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:44Z
Check the source to verify that this is the current version before use.

permitted unless the original laboratory analysis indicated that the involved lot will be rejected because of noncompliance with the salt content requirement. When the reserve sample is analyzed, the analyses for salt shall be made and will be considered final. Unused reserve samples shall be returned to the contractor for inclusion in subsequent lots.

4.7 Can condition examination. Examination of filled and sealed tray pack cans shall be in accordance with the United States Standards for Condition of Food Containers, except that inspection for labeling shall be in accordance with MIL-L-1497 (see 5.4).

4.8 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement (when applicable), in accordance with the appendix of PPP-B-636. In addition, the following defects shall be classified as follows: Major: National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible. Minor: (1) Other required markings missing, incorrect or illegible; (2) Interior packing with fiberboard liner or pads not as specified; (3) Reinforcement with nonmetallic strapping or tape is not used; (4) Height of box liner less than inside depth dimension of box by more than 1/8 inch or extends above top edge of box; (5) Length or width of pads less than box dimensions by more than 1/8 inch; (6) Arrangement or number of cans not as specified.

4.9 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

5. PREPARATION FOR DELIVERY

5.1 Packaging. The product shall be packaged in accordance with level A or C as specified (see 6.1).

5.1.1 Level A. A size 1001 by 1206 by 200 tray pack can shall be filled with 98 ounces of the food product, sealed, and thermoprocessed as specified in 3.4, 3.5 and 3.6. The base plate of the can shall be electrolytic chromium-coated steel and shall be of sufficient temper to protect the product during shipment and storage. The base plate weight of the body and end of each can shall be 90 pounds per base box. The entire inside area of the can shall be coated. Scratches or fractures shall not penetrate through the interior can coating. The interior can coating shall not peel or blister when in contact with the product. The interior can coating shall neither affect nor be affected by the packaged product. A certificate of conformance shall be furnished to certify the compliance with the interior can coating requirements. The can shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:44Z
Check the source to verify that this is the current version before use.

APPENDIX C

coated overall on the outside with a coating conforming to type I of TT-C-495.

5.1.2 Level C. The product shall be packaged as specified in 5.1.1, except that cans with commercial exterior coating will be acceptable.

5.2 Packing. The product shall be packed in accordance with level A, B, or C as specified (see 6.1).

5.2.1 Level A packing. Four cans of product, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L, grade V2s of PPP-B-636. The cans shall be packed flat, four in depth within the box. The inside of each box shall be provided with a box liner and five fiberboard pads. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). The pads shall be not less than 1/8 inch of the full length and width dimensions of the box and shall be fabricated of grade V3c fiberboard. The pads shall be placed between the cans and on the top and bottom of the stacked cans. Each fiberboard box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Four cans of product, packaged as specified in 5.1, shall be packed as specified in 5.2.1, except the box shall be constructed of grade V3c, V3s or V4s fiberboard.

5.2.3 Level C packing. Four cans of product, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L, class domestic, grade 275 of PPP-B-636. The cans shall be packed flat, four in depth within the box. The inside of each box shall be provided with a box liner and five fiberboard pads. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box and shall be fabricated of the same material as the box.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 and 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified. When unit loads are strapped, the strapping shall be limited to nonmetallic strapping.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:44Z
Check the source to verify that this is the current version before use.

5.4 Labeling. Each tray pack can shall be labeled in accordance with MIL-L-1497. In addition, the name of the product shall be marked, stamping is permitted, on one 1001 by 200 side of the can. The labeling shall be legible when examined in accordance with 4.7 after submerging the can in boiling water for 30 minutes. Paper labels are not permitted. Cans shall show the following statements:

Tray cans may be heated prior to serving or served at ambient temperature without heating. When heated, the following heating directions shall apply:

TO HEAT

a. To heat in water: Submerge unopened can in boiling water. Simmer gently 35 minutes. Remove from water and open lid for serving.

b. To heat in oven: Either punch several holes in lid of can or open can in usual manner leaving the loose lid in place to prevent moisture loss. Place in a 350°F oven for approximately 30 to 40 minutes until contents reach an internal temperature of 165°F. WARNING: Do not place closed can in oven as heating will increase internal pressure which may cause the can to burst.

YIELD

25 servings of approximately 1/2 cup each.

5.5 Marking.

5.5.1 Shipping containers. In addition to any special marking required by the contract, shipping containers shall be marked in accordance with MIL-STD-129.

5.5.2 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078. In addition, the following precautionary marking in capital letters larger than other markings shall be included: CAUTION: DO NOT STACK PALLETS IN TRANSIT OR MORE THAN TWO HIGH IN STORAGE.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:44Z
Check the source to verify that this is the current version before use.

(a) Title, number and date of this specification.
(b) When a first article is required (see 3.1, 4.3 and 6.3).
(c) Provisions for approved preproduction samples (see 3.6.1 and 6.3).
(d) Level of packaging and packing required (see 5.1 and 5.2).
(e) Type and class of unit load when unit loading is required (see 5.3).

6.2 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

6.3 First article inspection. When a first article sample is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should include specific instructions in all procurement documents regarding arrangements for selection, inspection and approval of the first article.

Preparing activity:

Army - GL

Project No. 8940-A504

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:44Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

US ARMY NATICK RESEARCH
and DEVELOPMENT CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research
and Development Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:44Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
EE-P-00 2152 A	

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 20 Nov 84

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:44Z
Check the source to verify that this is the current version before use.