INTERIM FEDERAL SPECIFICATION

SCREW CAP, CANTEEN; CHAIN AND GASKET, ASSEMBLED

This Interim Federal Specification was developed by the Federal Supply Service, General Services Administration, Washington, D. C. 20407, based upon currently available technical information. It has been partially coordinated with industry, but has not been coordinated with government agencies and is subject to modification. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers the requirements for a canteen screw cap with chain, rivet, stud and rubber gasket, assembled, for use with the 4 quart metal water canteen covered by Federal Stock Number 8465-205-3222.

1.2 Classification.

1.2.1 Type and grade. The screw cap shall be of one type and grade.

2. APPLICABLE SPECIFICATIONS, STANDARDS, AND OTHER PUBLICATIONS

2.1 Specifications and standards. The following specifications and standards, of the issues in effect on date of invitation for bids, form a part of this specification to the extent specified herein.

Federal Specifications:

PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-636 - Box, Fiberboard.
PPP-B-665 - Boxes; Paperboard, Metal Stayed (Including Stay Material).
PPP-B-676 - Boxes, Set-Up, Paperboard.

Federal Standards:

Fed. Std. No. 102 - Preservation, Packaging, and Packing Levels.
Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

FOR INSTRUCTIONS ON OBTAINING COPIES OF FEDERAL SPECIFICATIONS AND STANDARDS, SEE LAST PAGE.

Military Specification:

MIL-P-116 - Preservation, Methods of

Military Standard:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

American Society for Testing and Materials - ASTM-D-735 - Elastomer Compounds for Automotive Applications.

(Copies of the American Society for Testing and Materials Standards may be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia 3, Pa.).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:44Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Preproduction sample. When specified (6.1), before production is commenced, a preproduction sample of the screw cap with chain, rivet, stud and rubber gasket, completely assembled, shall be submitted to the contracting officer for approval.

3.2 Materials. Material shall be as hereinafter specified. Materials not specifically defined shall be as regularly used by the manufacturer.

3.2.1 Metal components. The cap, chain, rivet and stud shall be made of metal compatible with the metal used for the filler vent and body of the 4 quart metal canteen covered by Federal Stock Number 8465-205-3222. The rivet may be steel, cadmium plated and the stud may be spring steel, nickel plated. The cap shall be threaded to fit the canteen sufficiently tight to prevent overriding of the thread when screwed on hand tight and the metal shall be not less than .020 inch thick prior to "doming". The chain shall be approximately 3-3/4 inches long and shall be constructed with links of a type and in sufficient number to meet the requirements specified herein. The stud shall be a trimount stud.

3.2.2 Rubber gasket. The gasket shall be made of rubber conforming to ASTM-D-735, Grade SC 515Z or Grade R 515Z and shall be practically odorless and shall impart no noticeable taste to water when in use. The gasket shall be of proper diameter to fit snugly into the cap and shall be 1/8 inch ± 1/64 inch thick. The gasket shall not be split, cracked, torn or broken.

3.3 Construction. The cap shall have a free swinging chain attached at one end to a centrally located rivet in the cap. The chain shall swivel freely around the cap. The chain shall have a trimount stud inserted through the end link at the free end of the chain. The chain shall not be permanently kinked and the links shall not be bent out of shape. The cap shall be fitted with a rubber gasket conforming to 3.2.2. After assembly, the rivet shall not bear against the cap gasket. The screw cap with chain, fully assembled, shall be so constructed that when screwed on a canteen filled with water, there shall be no leakage of water when the canteen is placed in an inverted position.

3.4 Workmanship. The finished screw cap assembly shall be clean, well made and free from all burrs, rough spots and sharp edges or any other defects which may affect serviceability or appearance.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Preproduction sample inspection. When required, examination and testing of the preproduction sample shall be made of the completed screw cap assembly for all the provisions of this specification.

4.3 Inspection for acceptance. Except when otherwise specified, inspection shall be in accordance with the provisions set forth in MIL-STD-105.

4.3.1 Inspection of components. Inspection of components and materials shall be in accordance with subsidiary specifications or shall meet the requirements of this specification. This specification shall govern in the event of conflict.

4.3.2 Inspection of the end item. The defects found during examination shall be classified in accordance with table I. The lots shall be inspected in accordance with 4.3.2.1. The unit of product for this examination shall be one completed screw cap assembly. Acceptable quality levels shall be as listed in 4.3.2.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:44Z
Check the source to verify that this is the current version before use.

TABLE I.- Classification of defects

Examine	Defects	Classification	
		Major	Minor
Components	Missing.	X	
	Not of specified material.	X	
	Bent, cracked, malformed, broken or otherwise damaged affecting serviceability.	X	
	Bent, malformed, or otherwise damaged not affecting serviceability.		X
	Burrs or slivers that may cause injury.	X	
Finish	Not uniform, scratched or not clean.		X

4.3.2.1 Inspection level and acceptable quality levels (AQL's). Inspection levels and acceptable quality levels, expressed in defects per hundred units, shall be as follows. All completed units presented at one time for delivery shall be considered a lot for the purpose of acceptance, inspection, and tests.

	Inspection level	AQL
For examination applicable to table I:	II	Major - 2.5 Total - 6.5

4.3.3 Examination of preparation for delivery. An examination shall be made to determine that packaging, packing, and marking requirements of section 5 of this specification are complied with. Defects shall be scored as specified below. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 4.0 defects per hundred units.

Examine	Defect
Packaging	Not unit packaged as specified.
Packing	Any packing component or material missing, damaged or not as specified; closure not accomplished by specified or required method or materials.
Workmanship	Inadequate application of component or material such as incomplete closure of container flap, bulge or distortion of container.

5. PREPARATION FOR DELIVERY

(Federal Standard No. 102 shall be referred to for definitions and application of the various levels of packaging and packing for civilian procurements.)

5.1 Packaging shall be level A, B or C as specified (6.1).

5.1.1 Level A. The caps shall be packaged in accordance with MIL-P-116, method IC-2.

5.1.2 Level B. Unless otherwise specified, twelve (12) caps shall be packaged in a box conforming to PPP-B-566, style II, Type A, class a, pye lock; or to PPP-B-665, Style optional; or to PPP-B-676, Type optional. The boxes shall be closed in accordance with the applicable specification or appendix thereto.

5.1.3 Level C. The caps shall be packaged in accordance with the suppliers' commercial practice.

5.2 Packing. Packing shall be level A, B or C as specified (6.1).

5.2.1 Level A. The caps shall be packed in boxes conforming to PPP-B-636, Type I, class 1, V3c, style optional. Each box shall be closed, waterproof sealed with tape and reinforced with bands of filament tape in accordance with the appendix to the box specification.

5.2.2 Level B. Unless otherwise specified (6.1), ninety-six (96) caps shall be packed in a box conforming to PPP-B-636, Type I, class 1, style optional. The box shall be closed and sealed in accordance with the appendix to the box specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:44Z
Check the source to verify that this is the current version before use.

5.2.3 Level C. The caps shall be packed to insure carrier acceptance and safe delivery to destination in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 Marking (civil agencies). In addition to special markings required by the contract or order the packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) If preproduction sample required (3.1).
(c) Selection of applicable levels of packaging and packing (5.1 and 5.2).

6.2 Supersession data. This specification supersedes Purchase Description RR-l-75(GSA-FSS) prepared by the General Services Administration which covered requirements for the canteen screw cap assembly.

Notice.- (See last page).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:44Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS ON OBTAINING COPIES OF FEDERAL SPECIFICATIONS AND STANDARDS

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications, Standards and Handbooks and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington 25, D. C.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, and Auburn, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications, Standards and Handbooks from established distribution points in their agencies.)

NOTICE

When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:44Z
Check the source to verify that this is the current version before use.