INCH-POUND

MIL-C-70460A(AR)
AMENDMENT 2
15 October 1999
SUPERSEDING
AMENDMENT 1
29 May 1990

MILITARY SPECIFICATION

CARTRIDGE.56mm, BALL,
(HEAVY BULLET) REFERENCE

MIL-C-70460A was inactivated after 6 December 1995 For New Design.

This amendment forms a part of Military Specification MIL-C-70460A(AR), dated 5 October 1984, and is approved for use by the US Army Armament, Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.2 Delete:

"P9357841 Packaging and Marking, Cartridge, 5.56mm; Ball, (Heavy Bullet) Reference, Cartons; Box Ammunition, M2A1, Box, Wirebound"

Substitute:

"12551963 Packaging and Marking for Box, Wirebound for Cartridge 5.56mm"

PAGE 3

* 3.6 Velocity. Delete in its entirety and substitute the following:

"3.6 Velocity. The average velocity of the cartridges when conditioned at 70 degrees plus or minus 2 degrees Fahrenheit (F) shall be 3,020 feet per second (fps) plus or minus 40 fps at 78 feet from the muzzle of the weapon. The standard deviation of the velocities shall not exceed 20 fps."

* 3.7 Delete in its entirety and substitute the following:

"3.7 Chamber pressure. The average chamber pressure of the sample cartridges, conditioned at 70 degrees plus or minus 2 degrees F, shall not exceed 58,700 psi. Neither the chamber pressure of an individual sample test cartridge nor the average chamber pressure plus three standard deviations of chamber pressure shall exceed 64,700 psi."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:28Z
Check the source to verify that this is the current version before use.

* 3.8 Delete in its entirety and substitute the following:

"3.8 Port pressure. The mean port pressure minus three standard deviations shall not be less than 15,600 psi for sample cartridges conditioned at 70 degrees plus or minus 2 degrees f."

3.10 Delete in its entirety.

PAGE 5

4.2.1.2 Delete in its entirety and substitute the following:

"4.2.1.2 Component parts. Unless otherwise specified, component parts shall be homogeneous and of a quantity convenient to the contractor and inspected, tested and accepted by the contractor. The cartridge lot shall contain:

a. Cartridge cases from one unchanged process and one manufacturer.
b. Bullets from one unchanged process and one manufacturer.
c. Primers form one lot and one manufacturer.
d. Propellant from one lot and one manufacturer.

PAGE 10

4.2.3.1 Delete "Matching 4/, 90, 2/, 3.10"

PAGE 11

4.2.3.1 Delete Note 4/ in its entirety.

The margins of this amendment are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1305-0222)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:28Z
Check the source to verify that this is the current version before use.