NOTE: The document identifier and heading has been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

MIL-PRF-22684/8B
AMENDMENT 3
25 Mar 1994
SUPERSEDING
AMENDMENT 2
25 January 1985

PERFORMANCE SPECIFICATION SHEET

RESISTORS, FIXED, FILM, INSULATED, STYLE RL42...TX

This amendment forms a part of MIL-R-22684/8B dated 31 January 1978, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

FIGURE 1, Dimensions table, Dimension D, Minimum column: Delete ".300" and "7.62" and substitute ".280" and "7.11", respectively.

PAGE 4

After "Lead coating", add the following new requirement:

"Marking: At the option of the manufacturer, parts may be marked in accordance with method I of MIL-STD-1285. The military part number, FSCM, date and lot code, resistance value, and tolerance shall be marked on the part as in the example:

M22684/ 08-1239	- Military part number
12345	- FSCM
8401AA	- Date and lot code
910K 2%	- Resistance value and tolerance

If this type marking is used, then the green colored band for TX identification may be omitted. Marking shall remain legible after all tests."

PAGE 5

* Power conditioning, delete and substitute the following:

" Power conditioning

Measurement before conditioning: DC resistance measured in accordance with paragraph entitled "DC Resistance" of MIL-R-22684.

Conditioning procedures: Each resistors supplied under this specification shall be subjected to power conditioning for a period of 24 hours at 150 percent rated power. Mounting shall be such that 25, +10, -5°C ambient air can be circulated around the resistors by means of forced air with a velocity not exceeding 500 FPM. The maximum applied voltage shall not exceed 500 V rms.

Measurement after conditioning: After power conditioning, the resistors shall be stabilized at room conditions for a minimum of 2 hours before the dc resistance measurements are made. Resistors that are outside of the tolerance limit and those that have changed more than 0.5 percent due to the conditioning shall be removed from the lot. When the combined quantity removed exceeds 10 percent of the lot, the entire lot shall be rejected. The supplier shall have a complete record available of all test data obtained during power conditioning testing (see ordering data)."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:25Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR, AT, AV, ME
Navy - AS, CG, MC, OS
Air Force - 11, 17, 19, 99
DLA - ES

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project: 5905-1381)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:25Z
Check the source to verify that this is the current version before use.