INCH POUND

MIL-PRF-22710F
AMENDMENT 1
16 May 2000

PERFORMANCE SPECIFICATION

SWITCHES, CODE INDICATING WHEEL (PRINTED CIRCUIT),
THUMBWHEEL AND PUSH-BUTTON,
GENERAL SPECIFICATION FOR

This specification is approved for use by all Departments
and Agencies of the Department of Defense.

PAGE 7

3.4.3.3, delete last sentence and substitute:

"The walls of plated-through holes may be copper and overplated with the thickness to be not less than .001 inch (0.0254 mm)."

PAGE 16

Insert the following new paragraph,

"4.4.4.1.1.1 Group C suspension. At the request of the manufacturer, group C testing may be suspended with the qualifying activity's approval if it can be demonstrated that these test have been performed three consecutive times with zero failures. If the design, material, construction, or processing is changed or if there are any quality problems or failures, or at their discretion the qualifying activity may require resumption of the original testing requirement. Suspension of testing does not relieve the manufacturer from meeting the Group C test requirements."

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5930-1702)

Review activities:
Army - AV, CR4, MI
Navy - AS, MC, OS
Air Force - 99

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:29Z
Check the source to verify that this is the current version before use.