MIL-T-22691E(YD)
11 April 1986
SUPERSEDING
MIL-T-22691D(YD)
20 October 1981

MILITARY SPECIFICATION

TRACTOR, WHEELED, HIGH-SPEED, LOW CENTER OF GRAVITY, DED

This specification is approved for use by the Naval Facilities Engineering Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers a four-wheel, diesel-engine-driven tractor having a low center of gravity.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified (see 6.2), the following specification forms a part of this specification to the extent specified herein. Unless otherwise specified, the issue of this document shall be listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATION

MIL-T-3351 - Tractor, Full Tracked, Low-Speed, Tractor Wheeled, Agricultural, and Tractor Wheeled, Industrial, and Their Attachments, Packaging of.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

FSC 2420

AMSC N/A

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:26Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents. The following Government document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issue shall be those in effect on the date of the solicitation.

CODE OF FEDERAL REGULATIONS (CFR)

Title 29, Safety and Health Regulations for Construction.

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

(Copies of specifications and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of the documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE Handbook.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

TIRE AND RIM ASSOCIATION, INC. (TRA)

TRA Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 West Market Street, Akron, OH 44313.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:26Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Description. The tractor shall consist essentially of a power plant and power train, mounted on four wheels equipped with pneumatic tires. Shipping weight of the tractor shall be not less than 2,450 pounds (lbs). Tractor shall meet the dimensional requirements specified in Table I.

TABLE I. Dimensions.

Item	Dimensions (inches) Min	Max
Center of gravity, measured vertically from level ground surface.		30
Height, overall (without roll-over protection structure).		64
Wheelbase.		85
Ground clearance.	5	
Curb clearance radius, without brakes and conforming to SAE J695.		260

3.2 First article. When specified (see 6.2), the contractor shall furnish a tractor for first article inspection (see 4.2.1 and 6.4).

3.3 Interchangeability. All units of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to insure interchangeability of component parts, assemblies, accessories, and spare parts.

3.4 Ease of maintenance. Design of the tractor shall permit ready accessibility to all parts for maintenance and repair by the use of conventional general-purpose handtools. Replacement and adjustment of component parts and accessories shall be accomplished with minimum drainage requirements and disturbance to other elements on the tractor. Ease of maintenance provisions shall incorporate features insuring clearances between adjacent components to facilitate maintenance and servicing operation. Accessibility to lubrication fittings shall be provided without the removal or adjustment of accessories or parts.

3.5 Safety. Parts subject to high operating temperatures, moving or rotating parts, including rear wheels, and parts energized electrical which are of such a nature or so located as to become a hazard to operating and maintenance personnel shall be insulated, enclosed, or guarded to the extent necessary to eliminate the hazard. Protective devices shall not impair the operating functions. An electric horn shall be furnished. A rollover protection device conforming to 29 CFR 1926.1000 shall be furnished.

3.6 Performance. Tractor shall have a maximum travel speed of not less than 15 miles per hour (mph). The tractor shall be capable of:

a. Towing a 7-gang reel type mower.
b. Towing and operating a rotary mower.
c. Operating a sickle bar mower.
d. Performing the above functions while operating on a grade having a minimum slope of not less than 30 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:26Z
Check the source to verify that this is the current version before use.

3.7 Drawbar pull. The tractor shall have a maximum drawbar pull equivalent to not less than 70 percent of its weight when fully equipped including a 175 lb operator, but without ballast.

3.8 Frame. Frame design may be either farm type or industrial type. The industrial type frame shall be fabricated of structural steel sections or steel plates with members joined using one of the arc-welding processes. To withstand the stresses imposed, and to prevent permanent deformation or damage to the tractor, the frame shall be braced and reinforced wherever necessary. The farm type frame shall consist of the engine housing, transmission case, and the rear differential housing. Design and the method of mating each component shall be such as to assure structural integrity.

3.9 Axles. The tractor shall be equipped with a front located, steering type axle and a rear located axle. Both axles shall be equipped with wheels mounted on heavy-duty ball or roller-type bearings.

3.10 Rims, tires, and tubes. Tire and rim sizes shall conform to TRA recommendations for the type and size of tires furnished. Unless otherwise specified (see 6.2), tractor shall be equipped with wide base, rear tires. Rear tires shall be R-3 type (Diamond shallow tread) with ply rating of not less than 4. Front tires shall be either I-1 type of F-3 type (Multiple rib tread) with ply rating of not less than 4. Tires shall be of a rated capacity at least equal to the load imposed, measured at each wheel at the ground, when the tractor is fully loaded; When tube-type tires are furnished, tubes shall be of the heavy-duty type and of proper size for the tires furnished.

3.11 Brakes.

3.11.1 Service. Tractor shall be provided with individually operated rear wheel service brakes. Tractor shall also be equipped to provide simultaneous braking of rear wheels. When traveling on a relatively level, hard, smooth surface at a speed of 15 mph, service brakes shall be capable of stopping the tractor within a distance of 60 feet.

3.11.2 Parking. A mechanical parking brake which is part of the main braking system, or an independent mechanical parking brake shall be furnished. Mechanical service brakes which can be locked as parking brakes are acceptable. Parking brake shall be capable of holding the tractor stationary on a 30 percent slope.

3.12 Hitch. Tractor shall be equipped with a three-point hitch for attaching rotary mowers and a drawbar for attaching reel type mowers. The three-point hitch shall conform to the requirements of SAE J715. The drawbar shall withstand the maximum vertical load conditions as specified in SAE J721 without permanent distortion, and shall be designed to provide for each attachment of the reel type mowers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:26Z
Check the source to verify that this is the current version before use.

3.13 Powerplant. Tractor shall be powered by a diesel engine. The corrected net horsepower rating at the flywheel shall be not less than 40 when determined as specified in SAE J816. Engine shall be equipped with the following:

a. Air cleaner.
b. Full flow type oil filter.
c. Governor. When nonadjustable type is furnished it shall be set to limit engine speed at the maximum operating speed recommended by the engine manufacturer.
d. The operator's station shall be equipped with, but not necessarily limited to, the following instruments and controls:

(1) Lubricating oil pressure indicator.
(2) Cooling liquid temperature indicator.
(3) Battery-alternator or generator indicator.
(4) An engine hour meter capable of registering not less than 9,999 hours of engine operation.
(5) A start-stop control.
(6) Throttle control.

3.14 Powerplant systems.

3.14.1 Starting. Engine shall start in any ambient temperature above 20 degrees Fahrenheit (°F). The tractor shall have an electrical cranking system. Starting aids may be either electric glow plug or ether primer. When an ether priming system is furnished, it shall be of the measured shot type with storage capacity of not less than 12 fluid ounces.

3.14.2 Fuel. Fuel tank shall have sufficient capacity for not less than 4 hours normal operation. A fuel shutoff valve attached directly to the tank shall be provided. A fuel gage located at the tank or at the operator's station shall be furnished.

3.14.3 Exhaust. Tractor shall be equipped with a muffler and exhaust pipe. The exhaust pipe shall be located to assure expelled gases are directed away from the operator. Vehicle exhaust pipes shall be equipped with self-opening and closing rain caps or 90° bend.

3.14.4 Cooling. Tractor shall be furnished with a heavy-duty cooling system. The system shall maintain coolant at a temperature below the boiling point when the tractor is operating at 10,000 feet above sea level, or in an ambient temperature of not less than 125°F. Radiator core shall be protected against damage by a guard, capable of withstanding damage from brush, hanging tree limbs, or similar ground growth encountered in moving and general landscape maintenance.

3.15 Power train. The transmission shall have not less than three speeds forward and one speed reverse. Transmission shall permit smooth shifting in all gear ranges. Axles and transmission gear ratios shall be matched to provide a progressive shifting pattern through the complete range. Input torque capacity of transmission shall be at least equal to the maximum torque

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:26Z
Check the source to verify that this is the current version before use.

delivered by the engine. Drive line components shall transmit the maximum delivered torque of the engine, as developed through the maximum gear train reduction, without sustaining any damage or deformation.

3.16 Power takeoff. Tractor shall be equipped with a 540 revolutions per minute, independent power takeoff conforming to SAE J1170 and SAE J721.

3.17 Systems.

3.17.1 Electrical. Tractor shall have a 12-volt (V) electrical system. The battery shall be 12V potential, and have a capacity of not less than 70 ampere-hours at the 20-hour rate. A generator or alternator having not less than 26 ampere rating shall be furnished. All wiring shall be protected against weathering and wearing, and shall be supported or secured at intervals not exceeding 2 feet.

3.17.2 Lighting. When specified (see 6.2), the tractor shall be furnished with lighting and marking equipment for operation on public roads and rearward directed floodlamp conforming to SAE J598. Instrument panel lamps to illuminate all instruments shall be provided. Head, tail, and instrument panel lamp circuits shall be connected for actuation by a single control switch. Independent control switches shall be furnished for the floodlamp and warning lamp.

3.17.3 Hydraulic. A hydraulic system shall be provided for transmitting engine power to the mechanisms necessary for raising and lowering a towed rotary mower, gang reel mowers, and a sickle bar. The hydraulic system shall be complete with all operating accessories, including pump, reservoir, valves, filters, hoses, piping, fittings, and pressure relief valve(s). Pump shall have sufficient capacity to energize all hydraulically powered components. The system shall be capable of withstanding a bursting pressure of four times the working pressure and a maximum proof pressure of at least two times the working pressure. Hoses shall be suitable for operation at temperatures ranging from -20°F to 240°F. Hoses shall be protected against chafing through utilization of supports and protective devices. A wiper shall be provided on each hydraulic cylinder adjacent to the piston rod seal to prevent dirt and abrasives from damaging the seal or entering the cylinder. System shall be furnished with full flow filter(s) having a micron rating not greater than 25. The reservoir shall have sufficient capacity to allow maximum displacement of all cylinders at the same time, and to aid heat dissipation.

3.17.4 Steering. Tractor shall be equipped for front wheel steering utilizing an automotive type steering mechanism, with gears enclosed in a leakproof housing. Either full power steering or power assisted steering shall be furnished.

3.18 Operator's station. Operator's station shall be equipped with a seat and backrest, instrument panel, and operating controls. Seat and backrest shall be padded and covered with weatherproof material. The seat shall be horizontally and vertically adjustable. Instrument panel shall contain the instruments, controls, and switches specified in 3.13 and 3.17.2. All instruments shall be visible and all hand and foot operated controls, including brake, throttle, transmission, and steering wheel, shall be within

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:26Z
Check the source to verify that this is the current version before use.

easy reach of the operator while sitting in his normal operating position. Instruments, gages, switches, and controls shall be protected against moisture and inclement weather conditions. Each instrument, gage, switch, and control shall be provided with permanently affixed identification markings. Decalcomania shall not be used.

3.19 Sickle bar. When specified (see 6.2), a side mounted, power takeoff driven, hydraulically controlled sickle bar shall be furnished. Cutter bar length shall be not less than 5 feet. The sickle bar hydraulic system shall allow the operator to position the cutter bar in any location from 45° above to 45° below a horizontal plane from the operator's station. Sickle bar shall be furnished with a breakaway release to prevent damage for the cutter bar in the event an obstruction is encountered. Cutter bar shall be equipped with inboard and outboard glides and sickle guards. Ledger plates, sickle plates, and other wearing parts shall be replaceable.

3.20 Front bumper. Tractor shall be provided with a heavy-duty bumper extended forward of the steer wheel tires, having adequate strength to push a stalled tractor of similar weight and size.

3.21 Lubrication. Unless otherwise specified (see 6.2), means for lubrication shall be in accordance with the manufacturer's standard practice. The lubricating points shall be easily visible and accessible. Hydraulic lubrication fittings shall be in accordance with SAE J534. Where use of high pressure lubricating equipment, 1,000 pound-force per square inch or higher, will damage grease seals or other parts, a suitable warning shall be affixed to the equipment in a conspicuous location.

3.22 Identification plate. The contracting officer will furnish to the Government inspector the required identification plates. The contractor will be required to stamp the necessary data in the blank spaces thereon and securely affix said plates in a conspicuous place on each unit, assembly or subassembly, and parts as directed by the Government inspector. Nonferrous screws, rivets, or bolts of not less than 1/8-inch in diameter shall be used to affix the plates. Nomenclature shall be "TRACTOR, WHEELED, LOW CENTER GRAVITY, DED"

3.23 Cleaning, treatment, and painting. Surfaces normally painted in good commercial practice shall be cleaned, treated, and painted as specified herein. The color of the finish coat shall be as specified (see 6.2). Surfaces to be painted shall be cleaned and dried to insure that they are free from contaminants such as oil, grease, welding slag and spatter, loose mill scale, water, dirt, corrosion product, or any other contaminating substances. As soon as practicable after cleaning, and before any corrosion product or other contamination can result, the surfaces shall be prepared or treated to insure the adhesion of the coating system. The painting shall consist of at least one coat of primer and one finish coat. The primer shall be applied to a clean, dry surface as soon as practicable after cleaning and treating. Painting shall be with manufacturer's current materials according to manufacturer's current processes and the total dry film thickness shall be not less than 2.5 mils over the entire surface. The paint shall be free from runs, sags, orange peel, or other defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:26Z
Check the source to verify that this is the current version before use.

3.24 Workmanship.

3.24.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

3.24.2 Bolted connections. Boltholes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.24.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.24.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:26Z
Check the source to verify that this is the current version before use.

4.1.2 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. The first article inspection shall be performed on one tractor when a first article is required (see 3.2 and 6.2). This inspection shall include the examination of 4.3, the test of 4.4, and, when specified, the preproduction pack inspection of 4.5 (see 4.5 and 6.2). The first article may be either a first production item or a standard production item from the supplier's current inventory provided the item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.3, the test of 4.4, and the packaging inspection of 4.5.

4.3 Examination. Each tractor shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.4 Tests. The first article tractor shall be tested as specified in 4.4.1, and each production tractor shall be subjected to the operational test specified in 4.4.2 to verify compliance with the requirements of this specification.

4.4.1 First article tests. The first article tractor shall be completely assembled and weighed. Tractor shall be serviced, adjusted, and the engine shall be started and allowed to warmup for a period of time recommended by the manufacturer. The servicing of the tractor shall be observed to determine compliance with the requirements of 3.4 and 3.21. Tractor shall be subjected to the tests specified in 4.4.1.1 through 4.4.1.4. Failure to pass one or more tests shall be cause for rejection.

4.4.1.1 Center of gravity. Tractor's center of gravity shall be determined in accordance with SAE J874 to verify conformance to 3.1.

4.4.1.2 Performance test. Tractor shall operate for not less than 3 hours on undulating terrain with some of the slopes having grades of not less than 30 percent. When a sickle bar is furnished, 1 hour of the test shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:26Z
Check the source to verify that this is the current version before use.

conducted with sickle in operation; otherwise a power takeoff driven rotary mower shall be used for 2 hours. Sickle bar shall be tested to verify compliance with the requirements of 3.19. Tractor shall tow a 7-gang reel type mower for not less than 1 hour. Parking brakes shall be tested in one of the 30 percent slopes to demonstrate conformance to 3.11.2. The parking brake test shall be conducted with the tractor heading up and down slope. Throughout the test, tractor shall be observed to determine conformance to the requirements of 3.5, 3.6, 3.12, 3.16, 3.17.3, 3.17.4, and when applicable to 3.17.2.

4.4.1.3 Road test. Tractor shall be driven for not less than 1 1/2 hours, which shall include driving for 1/2 hour in each transmission gear. Curb clearance radius shall be verified in accordance with SAE J695 to ascertain conformance to 3.1. Tractor shall be driven on a relatively level, hard, smooth surface at not less than 15 mph to establish compliance with 3.6. Each individually operated rear wheel service brake shall be tested not less than 10 times to determine ease of operation, effectiveness, and responsiveness. Service brakes shall be tested not less than 5 times to demonstrate ability to comply with the simultaneous braking requirements of 3.11.1. Seat and backrest shall be adjusted; operating controls and instruments shall be operated and observed to ascertain conformance to the requirements of 3.18.

4.4.1.4 Drawbar test. To determine conformance to 3.7, the tractor shall be tested for maximum drawbar pull without ballast in accordance with SAE J708. The test shall be conducted on a clean, level concrete surface.

4.4.1.5 Production sample. Upon acceptance ot the first article, it shall remain at the manufacturing facility as a production sample, and be the last tractor shipped on the contract. The first article shall be reconditioned, including replacement of abnormally worn parts and paint touch-up or repainting, prior to delivery to enable it to be accepted as a contract item. The contractor shall maintain the first article in a serviceable condition for the duration of the contract.

4.4.2 Operational test. Each tractor shall be completely assembled, properly adjusted, and serviced for operation. Engine shall be started and subjected to a warmup period as recommended by the manufacturer. Each tractor shall be driven for not less than 1 hour. All controls and switches shall be operated as many times as necessary to determine ease of operation, effectiveness, responsiveness, and that mechanisms actuated by the controls operate promptly, fully, and without restriction, malfunction, or excessive vibration. The power train, power takeoff, hydraulic system, steering system, bearings, shafts, and other easily accessible moving parts shall be tactually examined for excessive heating or abnormal operation insofar as is practicable. Failure to pass any phase of this test shall be cause for rejection.

4.4 Packaging inspection. The preservation and packaging of the tractors shall be inspected to verify conformance to the requirements of section 5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:26Z
Check the source to verify that this is the current version before use.

4.5 Packaging inspection. The inspection of the preservation, packing, and marking shall be in accordance with the requirements of section 4 of MIL-T-3351. The inspection shall consist of the quality conformance inspection; and, when specified (see 6.2), a preproduction pack shall be furnished for examination and test within the time frame required (see 6.2).

5. PACKAGING

5.1 Preservation, packing, and marking. Preservation, packing, and marking shall be in accordance with the requirements of MIL-T-3351, type II (Mobile) with the level of preservation and the level of packing as specified (see 6.2).

6. NOTES

6.1 Intended use. Tractor is intended for use in general mowing operations using any one of the following mowers:

a. Side mounted, power takeoff driven sickle bar.
b. Rear mounted, power takeoff driven rotary type.
c. Towed, traction wheel driven, gang reel type.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. When specification shall be other than as specified (see 2.1.1).
c. When a first article is required for inspection and approval (see 3.2, 4.2.1, and 6.4).
d. When other than wide base type rear tires are required (see 3.10).
e. When a lighting system is required (see 3.17.2).
f. When a sickle bar is required (see 3.19).
g. When an alternate lubrication is required (see 3.21).
h. Color of finish coat (see 3.23).
i. When a preproduction pack is required and time frame required for submission (see 4.2.1 and 4.5).
j. Level of preservation and packing required (see 5.1).

6.3 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL) and invokes the provisions of DoD Federal Acquisition Regulations (FAR) Supplement 27.410-6, the data requirements will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL (DD Form 1423) incorporated into the contract. When the provisions of DoD FAR 27.410-6 are not invoked, the data shall be delivered in accordance with the contract requirements.

6.4 First article. When a first article inspection is required, the item will be tested and should be a first production item or it may be a standard production item from the contractor's current inventory as specified in 4.2.1. The first article should consist of one unit. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:26Z
Check the source to verify that this is the current version before use.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:

Navy - YD

Preparing Activity:

Navy - YD

(Project 2420-N048)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:26Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY
Commanding Officer (156)
Naval Construction Battalion Center
Port Hueneme,CA 93043-5000

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer (156)
Naval Construction Battalion Center
Port Hueneme, CA 93043-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:26Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-T-22691E(YD)	TRACTOR, WHEELED, HIGH-SPEED, LOW CENTER OF GRAVITY, DED

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil – Downloaded: 2026-10-19T13:26Z
Check the source to verify that this is the current version before use.

REPRODUCED AT GOVERNMENT EXPENSE