MILITARY SPECIFICATION

CARTRIDGE, PHOTOFLASH, M112A1 PARTS FOR, AND LOADING, ASSEMBLING AND PACKING

This specification is approved for use by the US Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

This specification covers the parts and the loading, assembling and packing for one type of photoflash cartridge designated as Cartridge, Photoflash, M112A1.

1.2 Classification. The photoflash cartridges shall be of the following classes:

Class 1 - 1 second delay
class 2 - 2 second delay
Class 3 - 4 second delay

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-116	- Preservation, Methods of
MIL-P-223	- Powder, Black
MIL-P-11329	- Primer, Electric, M59, LA & P
MIL-A-48078	- Ammunition, Standard Quality Assurance Provisions, General Specification For

FSC 1370

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn. DRSMC-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.

51 - Metals; Test Method

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1234 - Pyrotechnics; Sampling, Inspection and Testing

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

PRODUCT AND PACKAGING DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

8848546 - Cartridge, Photoflash, M112A1, 1, 2, and 4 Second Delay, Assembly
8860564 - Box, Packing for Cartridge, Photoflash M112A1
8860565 - Box, Packing for Cartridge, photoflash, M112A1
19-48-4116/106 - Unitization Procedures For Box Ammunition and Components on Four Way Entry Pellets - Cartridge, Photoflash M112

INSPECTION EQUIPMENT DRAWINGS

9278637 - Procedure for Light Output Measurement of Photoflash Cartridge

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Material. Materials and parts shall be in accordance with applicable drawings and specifications .

3.2 Assembly. The assembly shall comply with all requirements specified on Drawing (dwg.) 8848546 and with all requirements specified in applicable specifications.

3.3 Static illumination of charge case assemblies .

3.3.1 Dud. The charge case shall not fail to function.

3. 3.2 Integral light value. The average of the integral light values , during the first 0. 040 second of flash, of all the charge case assembli es tested for acceptance of each lot shall be not less than 1.150 million candle-seconds. In addition, the integral light value of each charge case assembly, during the first 0.040 second of flash, shall be not less than 0.70 million candle-seconds.

3.4 Functioning. The loaded cartridge shall comply with the foolowing requirements.

304.1 Dud. The cartridge shall not fail to function and eject the charge case assembly from the launcher.

3.4.2 Premature burst. The charge case loaded assembly shall not explode in the launcher or within a minimum (min.) distance of 50 feet from the launcher

3. 4.3 Delay time. The delay time for each class from iniat ion of the cartridge primer to charge case functioning , shall be as specified in Table I.

TABLE I - Delay Time

Class	Minimum (min.) seconds	Maximum (max.) seconds
1	0.85	1.15
2	1.80	2.20
3	3.60	4.40

3.4.4 Flash and report. After ejection, the cartridge shall not fail to explode with a brilliant flash and loud report .

3.5 Seal integrity. Each Cartridge, Photoflash, M112A1 Assembly (8848546) shall show no evidence of leakage when tested in accordance with 4.4.3.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.

3.6 Embrittlement of primer shunting clip. The clip shall not break when bent to the minimum point of permanent distortion.

3.7 First article inspection. This specification contains techni cal provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.8 Workmanship. All parts and assemblies shall be fabricated and loaded in a thorough , workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt , grease , rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provision of 4.3.2. The first article sample shall consist of the items in sample quantities as indicated.

4. 3.2 Inspections to be performed. See MIL-A-48078 and Table II specified herein.

4. 3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.

TABLE II. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-11233J(AR)

PARAGRAPH	TITLE		SHEET 1 OF 4		DRAWING NUMBER
	Cartridge, Photoflash, M112A1 Parts For, and Loading, Assembling and Packing				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cartridge Case (Dwg. 8848542) Examination for Defects	25		3.2	4.4.2.1
	Charge Case (Dwg. 8848541) Examination for Defects	25		3.2	4.4.2.2
	Cap (Dwg. 8848536) Examination for Defects	25		3.2	4.4.2.3
	Primer Shield (Dwg. 8848538) Examination for Defects	25		3.2	4.4.2.4
	Fuze Housing (Dwg. 8848543) Examination for Defects	25		3.2	4.4.2.5

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17 15:45Z
Check the source to verify that this is the current version before use.

TABLE II. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-11233J(AR)

PARAGRAPH	TITLE	SHEET 2 OF 4	DRAWING NUMBER
	Cartridge, Photoflash, M112A1 Parts For, and Loading, Assembling and Packing		See Below
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Closing Disc (Dwg. 8848540)				
	Examination for Defects	25		3.2	4.4.2.6
	Primer Shunting Clip (Dwg. 8848539)				
	Examination for Defects	25		3.2	4.4.2.7
	Embrittlement	15	0-1	3.6	4.5.8.2
	Relay Cup (Dwg. 8847501)				
	Examination for Defects	25		3.2	4.4.2.8
	Relay Assembly (Dwg. 8847512)				
	Examination for Defects	25		3.2	4.4.2.9
	Shield-Wad-Disc Assembly (Dwg. 8848535)				
	Examination for Defects	25		3.2	4.4.2.10

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.

TABLE II. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-11233J(AR)

PARAGRAPH	TITLE			SHEET 3 OF 4	DRAWING NUMBER
	Cartridge, Photoflash, M112A1 Parts For, and Loading, Assembling and Packing				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Fuze Assembly (Dwg. 8848544)				
	Examination for Defects	25		3.2	4.4.2.11
	Charge Case Assembly (Dwg. 8848545)				
	Examination for Defects	25		3.2	4.4.2.12
	Cartridge Assembly (prior to Inserting Propelling Charge) (Dwg. 8848546)				
	Examination for Defects	10 a		3.2	4.4.2.13
	Electrical continuity and resistance	10 a	0-1	4.4.3.5	4.5.5
	Cartridge Assembly (prior to Inserting Charge Case in Loaded Assy) (Dwg. 8848548)				
	Examination for Defects	25		3.2	4.4.2.14

NOTES:

a. To minimize sample quantities those inspections and test may be performed on the same test items after subsequent assembly operation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.

TABLE II. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-11233J(AR)

PARAGRAPH	TITLE		SHEET 4 OF 4		DRAWING NUMBER
	Cartridge, Photoflash, M112A1 Parts For, and Loading, Assembling and Packing				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cartridge Assembly (Dwg. 8848546)				
	Examination for Defects	35		3.2	4.4.2.15
	Functioning	25 a	0-1	3.4	4.5.2
	Seal integrity	10 a	0-1	3.5	4.5.3
	Static illumination	25a	0-1	3.3	4.5.1
	Box (Prior to Sealing) (Dwg. 8860564)				
	Examination for Defects	10 a		3.2	4.4.2.16
	Sealed Box (Dwg. 8860564)				
	Examination for Defects	10		3.2	4.4.2.17
	Leak test	10 a	0-1	3.2	4.5.9
	Packing Box (Prior to Closing) (Dwg. 8860565)				
	Examination for Defects	10 a		3.2	4.4.2.18
	Sealed Packing Box (Dwg. 8860565)				
	Examination for Defects	10 a		3.2	4.4.2.19

NOTES:

a. To minimize sample quantities these inspections and test may be performed on the same test items after subsequent assembly operation.

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of Simulator Assemblies shall contain:

a. parts of one interfix lot number from one manufacturer.

b. primers of one interfix lot number from one manufacturer

c. Composition ingredients from not more than one lot from one supplier.

d. Cartridge assemblies of not more than one class.

4.4.2 Examination. - See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105.

Source: https://assist.dla.mil - Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-11233J(AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.1	Cartridge Case		8848542
			NEXT HIGHER ASSEMBLY 8848546

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1.	Inside diameter, minimum (min.)		100%	3.2	Gage
Major					
101	Concentricity of outside diameter with thread		0.40%	3.2	Gage
102	Diameter of flash hole		0.40%	3.2	Gage
103	Crack or split		0.40%	3.2	Visual
Minor					
201	Total length		0.65%	3.2	Gage
202	Wall thickness, min		0.65%	3.2	Gage
203	Inside diameter, maximum, (max.)		0.65%	3.2	Gage
204	Pitch diameter of thread		0.65%	3.2	Gage
205	Minor diameter of thread, max		0.65%	3.2	Gage
206	Thickness between base and bottom of expelling charge cavity		0.65%	3.2	Gage
207	Diameter of expelling charge cavity, min		0.65%	3.2	Gage
208	Depth of primer cavity		0.65%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-11233J(AR)

PARAGRAPH	TITLE	SHEET 2 OF 2	DRAWING NUMBER
4.4.2.1	Cartridge Case		8848542
			NEXT HIGHER ASSEMBLY
			8848546

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
209	Thickness from base to forward end end of expelling charge cavity		0.65%	3.2	Gage
210	Length of thread, min		0.65%	3.21	Gage
211	Porous area or inclusion		0.65%	3.2	Visual
212	Chamfer missing		0.65%	3.2	Visual
213	Evidence of poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-11233J(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8848541
4.4.2.2	Charge Case				NEXT HIGHER ASSEMBLY 8848546
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1.	Crack or split		100%	3.2	Visual
Major	None defined				
Minor					
201	Length		0.65%	3.2	Gage
202	Inside diameter		0.65%	3.2	Gage
203	Pitch diameter of thread		0.65%	3.2	Gage
204	Minor diameter of thread		0.65%	3.2	Gage
205	Outside diameter		0.65%	3.2	Gage
206	Thickness through bottom		0.65%	3.2	Gage
207	Diameter of counterbore		0.65%	3.2	Gage
208	Depth of counterbore		0.65%	3.2	Gage
209	Evidence of poor workmanship		1.0%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-11233J(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Cap	1 OF 1	8848536
			NEXT HIGHER ASSEMBLY 8848546

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Crack or split		0.40%	3.2	Visual
Minor					
201	Thickness through bottom, min		0.65%	3.2	Gage
202	Length of side		0.65%	3.2	Gage
203	Bare spot in protective coating or coating missing		0.65%	3.2	Visual
204	Evidence of poor workmanship		1.0%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-04-17T16:49:07Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-11233J(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Primer shield				8848538
					NEXT HIGHER ASSEMBLY
					8848546
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Two or more holes missing		0.40%	3.2	Visual
Minor					
201	Diameter		0.65%	3.2	Gage
202	Thickness		0.65%	3.2	Gage
203	One hole missing		0.65%	3.2	Visual
204	Protective finish		0.65%	3.2	Visual
205	Evidence of poor workmanship		1.0%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-04-17 21:47:57
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-11233J(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Fuze housing	1 OF 1	8848543
			NEXT HIGHER ASSEMBLY: 8848546

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length		0.40%	3.2	Gage
102	Diameter of flash hole		0.40%	3.2	Gage
Minor					
201	Large outside diameter		0.65%	3.2	Gage
202	Small outside diameter		0.65%	3.2	Gage
203	Inside diameter		0.65%	3.2	Gage
204	Pitch diameter of thread, min		0.65%	3.2	Gage
205	Major diameter of thread, min		0.65%	3.2	Gage
206	Thickness of bottom		0.65%	3.2	Gage
207	Length from rear end to thread		0.65%	3.2	Gage
208	Length of thread undercut		0.65%	3.2	Gage
209	Length of large outside diameter		0.65%	3.2	Gage
210	Evidence of poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17 15:45Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-11233J(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Closing disc				8848540
					NEXT HIGHER ASSEMBLY
					8848546
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Crack or split		0.40%	3.2	Visual
Minor					
201	Diameter		0.65%	3.2	Gage
202	Thickness		0.65%	3.2	Gage
203	Length between top and bottom surfaces		0.65%	3.2	Gage
204	Protective coating missing or contains bare spot		0.65%	3.2	Visual
205	Evidence of poor workmanship		1.0%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assistdla.mil -- Downloaded: 2026-10-17 11:34:52
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-11233J(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.7	Primer shunting clip		8848539
			NEXT HIGHER ASSEMBLY 8848546

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Profile of ends		0.40%	3.2	Gage
102	Embrittlement	20	0-1	4.4.3.8	4.5.8.2
Minor					
201	Protrusion of center locking tabs from contact		0.65%	3.2	Gage
202	Length between contact surfaces		0.65%	3.2	Gage
203	Thickness		0.65%	3.2	Gage
204	Width		0.65%	3.2	Gage
205	Width over center contacts		0.65%	3.2	Gage
206	Thickness of center contact		0.65%	3.2	Gage
207	Protective coating missing or contains bare spot		0.65%	3.2	Visual
208	Evidence of poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-11233J(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Relay cup	1 OF 1	8847501
			NEXT HIGHER ASSEMBLY: 8848546

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1.	Crack or split		100%	3.2	Visual
Major	None defined				
Minor					
201	Diameter		0.65%	3.2	Gage
202	Thickness		0.65%	3.2	Gage
203	Length		0.65%	3.2	Gage
204	Evidence of poor workmanship		1.0%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-04-14 14:47:52
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-11233J(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Relay assembly				8847512
					NEXT HIGHER ASSEMBLY
					8848546
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Charge above flush or more than max below flush		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.0%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-11 19:19:52
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-11233J(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.10	Shield-wad-disc assembly	1 OF 1	8848535
			NEXT HIGHER ASSEMBLY: 8848546

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Adhesive over hole		0.40%	3.2	Visual
Minor					
201	Paper disc missing, perforated or torn		0.65%	3.2	Visual
202	Wad missing or insecure		0.65%	3.2	Visual/Manual
203	Evidence of poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17 11:34:52Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-11233J(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.11	Fuze assembly				8848544
					NEXT HIGHER ASSEMBLY
					8848546
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1.	Depth to igniting charge, max		100%	3.2	Gage
Major					
101	Relay assembly missing or inverted		0.40%	3.2	Visual
102	Delay marking incorrect		0.40%	3.2	Visual
Minor					
201	Relay assembly not seated		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.0%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-11233J(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8848545
4.4.2.12	Charge case assembly				NEXT HIGHER ASSEMBLY 8848546
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1.	Diameter after crimping, max		100%	3.2	Gage
2.	Crimp not full 360 degrees or not flat against closing disc		100%	3.2	Visual
3.	Fuze assembly loose		100%	3.2	Manual
Major					
101	Width of crimp, min		0.40%	3.2	Gage
102	Sealing cement missing or inadequate		0.40%	3.2	Visual
103	Teflon tape missing or inadequate		0.40%	3.2	Visual
104	Delay marking missing or incorrect		0.40%	3.2	Visual
Minor					
201	Marking, other than delay marking, missing or unidentifiable		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.0%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17 11:34:52
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-11233J(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.13	Cartridge assembly (prior to inserting propelling charge)				8848546
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1.	Primer above flush		100%	3.2	Visual
Major					
101	Depth to primer, max		0.40%	3.2	Gage
102	Sealing composition missing or where not required		0.40%	3.2	Visual
103	Electrical continuity and resistance		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.8	Visual

NOTES:

DRDIE-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17 13:45Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-11233J(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.14	Cartridge assembly (Prior to inserting Charge Case Loaded Assembly				8848546
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Loose explosive in case		0.40%	3.2	Visual
Minor 201	Evidence of poor workmanship		1.00%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17 03:45:52
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-11233J(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.15	Cartridge assembly	1 OF 1	8848546
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE / INSPECTION METHOD
Critical					
1.	Primer shunting clip missing, loose, or does not contact primer electrode		100%	3.2	Visual
2.	Cartridge case dented		100%	3.2	Visual
3.	X-Ray performance test symbol missing		100%	3.2	Visual
4.	Seal integrity		100%	3.5	4.5.1
Major					
101	Contents loose		0.40%	3.2	Manual
102	Crimp of cover not full 360 degrees		0.40%	3.2	Visual
103	Sealing compound missing, inadequate or present where not required		0.40%	3.2	Visual
104	Delay marking missing or incorrect		0.40%	3.2	Visual
105	Case O.D. oversize		0.40%	3.2	Gage
106	Functioning			3.4	4.5.2
107	Static Illumination			3.3	4.5.1
Minor					
201	Marking other than delay marking, misleading or unidentifiable		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.0%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-11233J(AR)

PARAGRAPH	TITLE			SHEET 1 OF 1	DRAWING NUMBER
4.4.2.16	Box (Prior to Sealing)				8860564
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Box cut, punctured or torn in any area		0.40%	3.2	Visual
Major					
201	Any packing material missing		0.65%	3.2	Visual
202	Incorrect number of cartridges		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17 15:45Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-11233J(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.17	Sealed box				8860564
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Bag punctured, torn or seal incomplete		0.40%	3.2	Visual
102	Quick leak test	10/ cart	1-2	4.4.3.9	4.5.9
Minor					
201	Contents loose		0.65%	3.2	Manual
202	Marking misleading or unidentifiable		0.65%	3.2	Visual
203	Label missing or only partially sealed (when applicable)		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-11233J(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.18	Packing box (prior to closing)				8860565
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Any packing material missing		0.65%	3.2	Visual
202	Incorrect number of boxes		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil - Downloaded: 2025-10-17 07:17:17
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-11233J(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.19	Sealed packing box				8860565
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1.	X-Ray performance test stamp with date missing		100%	3.2	Visual
Major					
101	Board broken or split so that contents are exposed or liable to become exposed		0.40%	3.2	Visual
102	Hardware or strapping broken or loose		0.40%	3.2	Visual/Manual
103	DOT nomenclature missing or incorrect		0.40%	3.2	Visual
Minor					
201	Hardware or strapping improperly engaged		0.65%	3.2	Visual
202	Metal seal missing unsealed, or mislocated		0.65%	3.2	Visual/Manual
203	Contents loose		0.65%	3.2	Manual
204	Marking misleading or unidentifiable		0.65%	3.2	Visual

NOTES:

DESC-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

PRECAUTION: This specification covers sampling and testing of toxic and hazardous materials. Accordingly, it is emphasized that all applicable safety rules regulations and procedures must be followed in handling and processing the item.

4.4.3.1 Static illumination of charge case loaded assembly (see 3.3) - Major defects. The charge case loaded assemblies shall be observed for duds, integral light value of each loaded charge case, and the average of the integral light values of all loaded charge case assemblies. Charge case loaded assemblies may be selected from cartridge assemblies that have been subjected to the seal integrity test except that charge cases shall not be used from cartridge assemblies that leaked.

4.4.3.1.1. First lot produced. Beginning with the first lot produced and continuing until three (3) consecutive lots have complied with the acceptance criteria specified, a sample of 50 charge case loaded assemblies shall be selected from each lot for this test. If the average of the integral light values of the 50 charge case loaded assemblies tested is less than the requirement specified, or if 3 or more charge case loaded assemblies tested fail to fire or exhibit a reading less than the minimum value specified, the lot shall be rejected. The test shall be performed as specified in 4.5.1. (Destructive test).

4.4.3.1.2 After three (3) consecutive lots. After three (3) consecutive lots have met the criteria of 4.4.3.1.1, a sample of 20 charge case loaded assemblies shall be selected from each lot for test . If the average of the integral light values of the 20 charge case loaded assemblies tested is less than the requirement specified, or if 2 or more assemblies tested, fail to fire or exhibit a reading less than the minimum value specified, the lot shall be rejected.

4.4.3.2 Functioning (see 3.4). The cartridge assemblies shall be submitted for testing to a Government proving ground designated by the Contracting Officer. Observation shall be made for the following defects:

a. Premature burst - Critical
b. Dud. - Major defect
c. Delay time not within tolerance - Major defect
d. Flash and report obviously inadequate - Major defect

4.4.3.2.1 First lot produced. Beginning with the first lot produced and continuing until three (3) consecutive lots have complied with the acceptance criteria specified, one hundred and

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.

twenty five (125) samples shall be selected for this test. The lot shall be rejected if a Critical defect occurs at any time, or if three (3) or inore samples show evidence of a Major defect. The test shall be performed as specified in 4.5.2. (Destructive test).

4. 4.3.2.2 After three (3) consecutive lots. After three (3) consecutive lots have met the criteria of 4.4.3.2.1, fifty (50) samples shall be selected from each lot for test. If two (2) or more samples exhibit a Major defect or if a Critical defect is observed at any time, the lot shall be rejected.

4.4.3.3 Seal integrity (see 3.5) - Critical defect. (Non-destructive Test) This test shall be specified in 4.5.3. Any assembly that fails to comply with the requirement shall be classed defective and removed from the lot.

4.4.3.4 Moisture content (see Table III) - Major defects

TABLE III - Moisture Content

Material
Delay composition
Lead azide
Ignitor composition
Lead styphnate
Black powder
Photoflash powder ingredients
Felt
Paper
Chipboard

(See dwgs. 8847512, 8848544, 8948545, and 8848546).

The contract or shall provide adequate controls to assure compli ante with the requirements , and shall test for verification, at least one sample of each charge, composition, and material from each eight (8) hours production of cartridges . Composite samples shall not be used. If the moisture content of a sample exceeds the requirement, and loading has not begun, that quantity of material represented by the sample, shall be rejected. If assemblies have been loaded with material containing excessive moisture, the remaining material that is represented by the sample together with all assemblies loaded with the non-conforming material shall be rejected. The tests shall be performed as specified in 4.5.4.

4. 4.3.5 Electrical continuity and resistance (see dwg. 8848546) - Major defect. This test shall be performed 100 percent in accordance wi th tile procedure specif ied in 4. 5.5. Any assembly that fails to comply with the requirement shall be classed defective and removed from the lot. (Non-destructive).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.

4.4.3.6 Cartridge assembly chamber gaging (see dwg. 8848546) - Major defect. Chamber gaging shall be performed 100 percent . Any assembly that binds, or otherwise fails to gage shall be classed defective and removed from the lot. The gaging shall be performed as specified in 4.5.6.

4.4.3.7 Determination of composition ingredients (see Table IV) - Major defects

TABLE IV - Determination of Cormposition

Material
Delay composition
Igniter composition
Photoflash composition

(See dwgs. 8848544 and 8848545).

A sample of not less than 5 grams of each composition shall be selected from each batch or mixture for the test specified in 4.5.7. If any composition fails to comply with the dwg. requirements, the lot shall be rejected. When blending is accomplished in individual charge cases rather than by batch blending, the adequacy of the composi tion may be checked by emptying one or more of the partially mixed charges from the charge cases before they have been closed, blending the ingredients and performing an analysis on the sample of the mixture.

4.4.3.8 Hardness and embrittlement of primer shunting clip (see dwg. 8848539) - Major defect. Twenty (20) primer shunting clips shall be selected from each lot for test. If any clip fails to comply with the requirements the lot shall be rejected. The test shall be performed as specified in 4.5.8.

4.4.3.9 Quick leak test - Major defect. Ten (10) cartons in sealed barrier bags shall be selected from each lot for this test. If two (2) or more packages show evidence of leakage, the lot shall be rejected. The test shall be performed as specified in 4.5.9.

4.4.3.10 Radiographic inspection of cartridge assemblies (see dwg 8048546). Each cartridge assembly in the lot shall be subjected to radiographic examination (100% radiography) in accordance with the provisions of 4.5.10. Each radiograph shall be exaini ned for evidence of the following defects, using the radiographic standards prepar ed by the cent ractor and submitted for approval:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.

Less than 80 percent of propelling charge present (Critical defect).

b. Delay column missing (Critical defect).
c. Primer shield missing (Critical defect).
d. Gas check wad missing (Critical defect).
e. Fuze gasket missing (Critical defect).
f. Crimp of closing disc less than 90 degrees (Critical defect).
g. Relay assembly missing (Major defect).

All assemblies containing any of the defects listed herein shall be classed defective and removed from the lot. If during radiographic examination more than two(2) percent of the lot is found to contain more than 80 percent but less than 90 percent of the propelling charge, the lot shall be rejected subject to segregation.

4.4.3.11 Check test for deterioration of Primer, Electric, (see MIL-P-11329). If the total elapsed time between original acceptance of the M59 Primer lot and the assembly of that lot into the cartridge assembly exceeds two years; or if the M59 primers have been subjected to adverse conditions , however brief, at any time since previous tests, the applicable lot shall be subjected to and must satisfactorily pass the check test for deterioration specified in MIL-P-11329. The test s-nail be performed by the contractor on assemblies selected by the Government inspector, at the facility assembling the item

4.4.4 Inspection Equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described i n the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract . See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of Inspection.

4.5.1 Static illumination of charge case assembly. The light out put of each assembly shall be mess ured at one end only with measurements alternately taken at the fuze end and the nose end. The procedure and equipment shall be as specified on dwg. 9278637.

4.5.2 Functioning (Proving Ground). The cartridges with primer end up shall be measured placed in a holding fixture so as to prevent any movement wi thin the fixture. The holding fixture shall be placed in a condi ti oning box and vibrated horizontally at 100 cycles per second and an amplitude of O. 020 in. at a temperature of minus 30 ± 5°F, (minus 34 ± 2°C) for 2 hours. Within 5 minutes of removal f rom the condi tioning chamber , the cartridge shall be fired from a ground launcher. The delay time shall be determined by a timing system accurate within plus or minus 0.01 seconds. The cartridges shall be observed for compl iance with the requirement. (Destructive Test)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.

4.5.3 Seal integrity. Each Cartridge Assembly (Dwg. 8848546) shall be placed in a cylindrical air tight chamber with the free space minimized. The air pressure within the chamber shall be raised to a minimum of 3 p.s.i.g. by means of a fixed volume of air. With the air supply shut off the pressure shall be maintained for 15 seconds min. Any Cartridge Assembly tested which fails to attain the minimum pressure specified or exhibits any leakage in excess of 0.05 p.s.i. shall be rejected.

4.5.4 Moisture content determinations.

4.5.4.1 Delay composition. Determine the moisture content of the delay composition in accordance with method 102.1 of MIL-STD-1234 using a five (5) g. sample of delay composition.

4.5.4.2 Lead azide. Determine the moisture content of the lead azide in accordance with method 102.2 of MIL-STD-1234 using a two (2) g. sample of lead azide.

4.5.4.3 Igniter composition. Determine the igniter composition moisture content as specified in 4.5.4.1.

4.5.4.4 Lead styphnate. Determine the moisture content of the lead styphnate as specified in 4.5.4.2 using a 2 gram sample of lead styphnate.

4.5.4.5 Black Powder. Determine the moisture content of the black powder shall be determined in accordance with method given in Specification MIL-P-223, using a sample weight of approximately 0.5 grams and heating thirty (30) minutes at 70 ± 2°C (158 ± 5°F).

4.5.4.6 Photoflash composition. Determine the moisture content of the photoflash composition as specified in 4.5.4.1 execpt that a 10 g. sample and a drying temperature of 100 ± 2°C (212 ± 5°F) shall be used.

4.5.4.7 Felt. Determine the moisture content of the felt as specified in 4.5.4.1 except that the sample size shall be 10 g. and the drying time until constant weight is attained.

4.5.4.8 Chipboard. Determine the moisture content of the chipboard as specified in 4.5.4.1, except that the sample size and drying temperature shall be as specified in 4.5.4.6.

4.5.5 Electrical continuity and resistance. The test for electrical continuity and resistance shall be conducted prior to inserting and the propelling charge. (Non-Destructive Test)

4.5.6 Chamber gaging of cartridge assembly. The cartridge assembly shall be inserted in the gage until the case flange seats on the gage. Any cartridge assembly that binds or fails to completely enter and seat shall be classed defective and removed from the lot. (Non-Destructive Test)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.

4.5.7 Determination of composition. (See 6.5)

4.5.7.1 Delay composition.

4.5.7.1.1 Procedure (Barium chromate).

4.5.7.1.1.1 Perchloric acid solution. Mix 500 milliliters (mL.) of perchloric acid (70 to 72 percent vacuum distilled with) 500 mL. of water.

4.5.7.1.1.2 Ortho-phenanthroline-ferrous sulphate indicator. Dissolve 1.487 grams of ortho-phenanthroline monohydrate in 100 mL. of an aqueous ferrous sulfate solution containing 0.695 grams of ferrous sulfate pentahydrate per 100 mL.

4.5.7.1.1.3 Standard ferrous perchlorate. Add 129 mL. of perchloric acid (70 to 72 percent vacuum distilled) to 871 mL. of water; add 12 grams of a pure grade of iron powder and stir the solution until the iron is completely dissolved. Filter the resultant solution through a 200 mL. medium porosity sintered glass crucible. pass a stream of nitrogen through the solution for 2 hours before using.

4.5.7.1.1.4 Standardization of ferrous perchlorate. Standardize the ferrous perchlorate solution against potassium bichromate of known purity, such as B.S., 136 in the following manner:

Transfer a portion of approximately 0.5 grams of the potassium bichromate to a 500 mL. Erlenmeyer flask, add 50 mL. of water and stir the mixture until the salt is completely dissolved. Add 50 ml. of perchloric acid solution and titrate the solution with the ferrous perchlorate solution, by adding the ferrous perchlorate solution until the solution being titrated acquires a greenish-blue color. Add 2 drops of ortho-phenanthroline-ferrous sulfate indicator and stir the solution until the pink color disappears. Continue the titration until the color of the solution changes from a greenish-blue to a pink color which lasts for approximately 2 minutes. Calculate the normality of the ferrous perchlorate solution as follows:

$$\text{Normality of the ferrous perchlorate solution} = \frac{AW}{4.904V}$$

where:

A = purity percentage of the potassium bichromate
W = weight of potassium bichromate used, g.
V = ferrous perchlorate used, mL.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.

4.5.7.1.1.5 Percentage of barium chromate. Transfer an accurately weighed portion of approximately 1 gram of the sample to a 300 mL. Erlenmeyer flask. Place the flask and contents on a cold hot plate, and carefully add 25 mL. of perchlorate acid by means of a pipette so that the acid runs down the side of the flask and does not spatter the sample, since boron adhering to the sides as a result of spattering does not give precise results. Heat the flask with medium heat until the boron is completely dissolved and fumes of perchloric acid are given off. Continue heating for 10 additional minutes after red chromic anhydride precipitates out of the solution. Remove the flask from the hot plate, add 75 mL. of distilled water and cool rapidly to room temperature in an ice bath. pass a stream of nitrogen through the solution for 5 minutes before titrating the solution with the standard ferrous perchlorate solution. Add the ferrous perchlorate solution rapidly stirring vigorously and titrate the solution until the latter solution assumes a greenish-blue color. Add 2 drops of ortho-phenanthroline-ferrous sulfate indicator and stir until the pink color disappears. Continue the titration until the color of the solution changes from a greenish-blue to a pink or red color. Calculate the percentage of barium chromate in the sample as follows:

$$\text{Percentage of barium chromate} = \frac{8.446VN}{WP}$$

where:

V = ml. of standard ferrous perchlorate solution used.
w = weight of the sample, g.
N = normality of the standard ferrous perchlorate solution.
P = Purity of barium chromate used. (The purity of barium chromate shall be determined for each lot of barium chromate used in delay compositions.)

4.5.7.1.1.6 Percentage of boron. Calculate the percentage of boron in the sample by subtracting the percentage of barium chromate from 100.

4.5.7.2 Igniter composition. The procedure for determining the igniter composition shall be as specified in 4.5.7.1.

4.5.7.3 Photoflash composition.

4.5.7.3.1 Aluminum. Transfer an accurately weighed portion of approximately two (2) g. of the sample to a tared medium porosity sintered glass crucible. Extract the sample with ten 25 mL. portions of distilled water at a temperature of 0 to 5 degrees C. using a filtering flask and suction (A Fisher Filtractor has been found satisfactory for this purpose). Stir the contents of the crucible with each portion of water for 1 minute before applying suction. Transfer the extract quantitatively to a 400 mL. beaker

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.

using approximately 50 mL. of wash water and reserve the extract and washings for the barium nitrate determinations. Rinse the undissolved residue with alcohol and ether, and aspirate until no further solvent odors are apparent. Place the crucible and contents in a drying oven at 100 ± 5°C, (212 ± 10°F) for 1 hour, cool in a desiccator and weigh. Calculate the increase in weight of the crucible to percent of aluminum powder on a moisture free basis as follows:

$$\text{Percentage of aluminum powder} = \frac{100\ A}{W\text{-}WM}$$

where:
A = increase in weight of Gooch crucible
w = weight of sample
M = percent moisture expressed as a decimal

4.5.7.3.2 Barium nitrate. To the extract reserved during the aluminum powder determination, add 1 mL. of 12N hydrochloric acid. Heat to boiling on a hot plate and add slowly from 50 mL. pipette, 50 mL. of 3N (1:8) sulfuric acid. Allow the mixture to boil gently for five minutes and finally to digest for at least 2 hours on a steam bath. Quantitatively transfer the precipitated barium sulfate into a tared Gooch crucible which has been previously heated in a muffle furnace at approximately 750 degrees C. for 30 minutes. Wash the precipitate 10 times with 25 mL. portions of hot water, dry in an oven at 100 plus or minus 5 degrees C. for 1 hour and in a muffle furnace at approximately 750 degrees C. for 30 minutes, cool in a desiccator and weigh. Calculate the percentage of barium nitrate in the sample on a moisture free basis as follows:

$$\textbf{Percentage of barium nitrate} = \frac{111.98A}{W\text{-}WM}$$

where:
A = increase in weight of Gooch crucible, g.
W - weight of sample, g.
M = percent moisture expressed as a decimal

4.5.7.3.3 Potassium perchlorate. Calculate the percentage of potassium perchlorate in the sample by subtracting from 100 the percentage of aluminum and barium nitrate found.

4.5.8 Primer shunting clip.

4.5.8.1 Hardness. The shunting clip shall be tested as specified in Method 243 of Federal Standard 151.

4.5.8.2 Embrittlement of primer shunting clip. The clip shall be bent to the min. point of permanent distortion by any method satisfactory to the procuring-activity. All shunting clips subjected to this test shall be scrapped. (Destructive Test)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.

4.5.9 Quick leak test. The test shall be performed in accordance with the procedure in Specification MIL-P-116, using the vacuum chamber or the pneumatic pressure technique.

4.5.10 Radiographic inspection of cartridge assembly. The cartridge assemblies shall be subjected to radiography and examination in accordance with the radiographic standards.

5. PACKAGING

5.1 Preservation and packaging.

5.1.1 Level A. The box shall be packed in accordance with dwg. 8860564.

5.2 Packing

5.2.1 Level A. The box shall be packed in accordance with dwg. 8860565.

5.3 Marking. Marking shall be as specified on dwg. 8860564 and 8860565.

5.4 Unitization. Unitization shall be in accordance with dwg. 19-48-4116/106 .

5.5 Lot integrity. Lots shall not be intermingled for shipment. Division between lots in a shipment shall be distinctly idefitified.

6. NOTES

6.1 Intended use. The components covered by this specification are intended for use on the Cartridge, Photoflash, M112A1.

6.2 Ordering data. See MIL-A-48078

6.3 Submission of inspection equipment for design approvals. See MIL-A-48078. Submit designs as required to Commander, US Army Armament Research and Development Center, ATTN: DRSMC-QAT-I(D), Dover, NJ 07801.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Center (ARDC) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or ARRADCOM drawings. Technical data originally prepared by these activities is now under the cognizance of ARDC.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.

6.5 Equivalent test methods. The test methods given in this specification are the official methods to be used. The contractor may request using other methods providing that the proposed method is equivalent (accuracy and precision) to the method given in this specification. Prior approval of the Contracting Officer is required for use of equivalent test methods. A description of the proposed method should be submitted through the Contracting Officer to: Commander, ARDC, ATTN: DRSMC-QAR-R(D), Dover, NJ 07801. This description should include, but not be limited to, the procedures used, the accuracy and precision of the method, test data to demonstrate the accuracy and precision and drawings of any special equipment required (see MIL-I-45208, paragraph 3.10).

6.6 Safety data. For safety data requirements refer to Safety Data Document Hazardous Component Safety Data Statement No. 1152.

6.7 Changes from Previous Issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

6.8 Identification of International Agreement. Certain provisions of this specification (identified by paragraph number or similar manner, if appropriate) are the subject of international standardization agreement (insert the ABCA and ASCC standard number, the NATO, STANAG, NETR or NEPR number, or other appropriate documentary reference). When amendment, revision, or cancellation of this specification is proposed which will modify the international agreement concerned, the preparing activity will take appropriate action through international standardization channels including departmental standardization offices to change the agreement or make other appropriate accommodations.

Custodian:
Army-AR

Preparing Activity:
Army-AR

(Project 1370-A155)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:45Z
Check the source to verify that this is the current version before use.