INCH-POUND

-


MIL-PRF-49142/10E
18 April 2005
SUPERSEDING
MIL-PRF-49142/10D
27 February 2002


PERFORMANCE SPECIFICATION SHEET

CONNECTORS, RECEPTACLE, ELECTRICAL, TRIAXIAL, RADIO FREQUENCY, UNCABLED (SERIES TRT, SOCKET CONTACT, JAMNUT MOUNTED, CLASS 2) HERMETIC AND NONHERMETIC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-49142.





Inches	mm	Inches	mm
.035	.88	.500	12.70
.045	1.14	.505	12.71
.104	2.64	.510	12.95
.114	2.90	.620	15.75
.215	5.46	.630	16.00
.218	5.54	.684	17.37
.221	5.61	.692	17.58
.250	6.35	.813	20.65
.493	12.52	.843	21.14
		1.343	34.11

FIGURE 1. General configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:51Z
Check the source to verify that this is the current version before use.

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Wrench flats are to accommodate standard wrench openings in accordance with FED-STD-H28, appendix 10.
4. All undimensioned pictorial representations are for reference purposed only.
5. Panel thickness, .045 (1.14 mm) minimum, .250 (6.35 mm) maximum.
6. Interface as specified in MIL-STD-348, series TRT, socket contact.
7. Unless otherwise specified, all tolerances are ±.005 inch (0.13 mm).
8. Only dash numbers-X003 and -X004 are supplied with braid termination lock washer rings. All previous dash numbers are supplied with standard lock washers (internal tooth .630 (16.00 mm) max dia. x .022 (0.56 mm) thick).

FIGURE 1. General configuration – Continued.

ENGINEERING DATA:

Nominal impedance: Non-constant.

Frequency range: 0 to 500 MHz minimum.

Voltage rating: 400 V rms maximum working voltage at sea level. 100 V rms maximum working voltage at 70,000 feet (4.437 kPa).

Temperature range: -65°C to +165°C.

REQUIREMENTS:

Dimensions and configuration: See figure 1 and MIL-STD-348.

Force to engage and disengage:

Longitudinal force: Not applicable.

Torque: 2.5 inch-pounds (0.28 Nm) maximum.

Coupling proof torque: Not applicable.

Inspection conditions: Coupling torque: 4-6 inch-pounds (0.45 Nm to 0.68 Nm).

Mating characteristics: See figure 1 and MIL-STD-348 for dimensions.

Center contact (socket):
Oversize test pin: .040 inch (1.02 mm) diameter minimum (on closed entry contacts only).
Insertion depth: .125 inch (3.17 mm) minimum.
Number of insertions: 1

Insertion force test:
Steel test pin finish: 16 microinches (0.406 μm).
Insertion force: 2 pounds (8.90 N), maximum.
Steel test pin diameter: .039 inch (0.99 mm) minimum +.001 inch (0.02 mm).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:51Z
Check the source to verify that this is the current version before use.

Withdrawal force test:
Steel test pin diameter: .037 inch (0.94 mm) maximum -.001 inch (0.02 mm).
Withdrawal force: 2 ounces (0.56 N) minimum.
Test pin finish: 16 microinches (0.406 μm).

Permeability: Applicable.

Hermetic seal: See table I.

Leakage: Not applicable.

Insulation resistance: 5,000 megohms.

Conductor retention: 6 pounds (26.69 N), minimum, axial force.

Dielectric withstanding voltage: At sea level, 1,200 V rms, between center conductor and intermediate conductor. 500 V rms, between intermediate conductor and outer conductor.

Salt spray (corrosion): Applicable.

Vibration: Applicable.

Shock: Applicable.

Thermal shock: Applicable.

Moisture resistance: Applicable.

Conductor resistance: In milliohms, maximum.

	Connector type	Initial	After environment
Center conductor:	All non-hermetic connectors	2.0	2.5
	All hermetic connectors	12.0	12.5
Intermediate conductor	All non-hermetic connectors	0.5	0.6
	All hermetic connectors	1.0	1.5
Outer conductor (Silver)	All non-hermetic connectors	0.2	0.3
	All hermetic connectors	0.5	0.6
Outer conductor (Nickel)	All non-hermetic connectors	0.4	0.6
	All hermetic connectors	1.0	1.2

Corona level:
Altitude: 70,000 feet (4.437 kPa).
Voltage: 200 V rms, minimum.

RF high potential withstanding voltage:
800 V rms, between center conductor and intermediate conductor.
200 V rms, between intermediate conductor and outer conductor at 5 to 7.5 MHz.

Leakage current: Not applicable.

Cable retention: Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:51Z
Check the source to verify that this is the current version before use.

Coupling mechanism retention force: Not applicable.

Rise time degradation: Not applicable.

Connector durability: 500 cycles minimum at 12 cycles per minute, maximum.

Part or Identifying Number (PIN): M49142/10- (dash number from table I). **CAUTION: A NICKEL PLATED BODY COMBINATION IS AVAILABLE. THIS COMBINATION IS NOT FOR USE IN APPLICATIONS WHERE PASSIVE INTERMODULATION GENERATION (PIM) MAY BE A CONCERN.**

Retention of qualification: See table II.

TABLE I. Cross reference of PIN.

Dash number ("X" in the dash number allows material options, refer to the basic document)	Superseding PIN
-X001 -X003 Non-hermetic	---
-X002 -X004 Hermetic	---

TABLE II. Retention of qualification. 1/

Subgroup	/3 & /8		/4 & /10	/5 & /9		/6 & /11	
1	/3-X008	---	/4-X004	---	---	---	---
2	/3-X008	/8-X006	/4-X004	---	---	---	/11-X006
3	/3-X008	/8-X006	---	---	---	---	---
4	/3-X008	/8-X006	---	---	---	/6-X007	/11-X006
5	/3-X008	---	/4-X004	---	---	---	---
Units	15	9	9	0	0	3	6

1/ Retention of qualification of connectors allows for retention of connectors of the same body material and finish only. "X" designates body material and finish.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:51Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-PRF-49142, this document references the following:

FED-STD-H28
MIL-STD-348

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 11
NASA - NA
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-4682-008)

Review activities:
Army - AR, AT, MI
Navy - AS, MC, OS, SH
Air Force – 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:51Z
Check the source to verify that this is the current version before use.