MIL-E-1/1349C
15 July 1969
SUPERSEDING
MIL-E-1/1349B
15 May 1964

MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 6792

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of MIL-E-1.

DESCRIPTION: Tetrode, HV control tube (voltage regulator)

Outline --- 12-21 (E1A)

Base --- B8-118

Envelope --- T-12

Cathode --- Coated unipotential

Top cap --- C1-34

Base connections:

Pin NO.:	1	2	3	4	5	6	7	8	Top cap
Elements:	k	h	g^2	nc	g1	g2	h	g2	a

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Unregulated DC supply	Ecl	Ec2	Ik	Pp	Pg2	Rgl	TE	Alt
Unit:	V	Kv	Kv	Vdc	Vdc	mAdc	W	W	meg	°C	ft
Maximum:	6.9	25.0	55	-125	350	10	25	1.0	3.0	165	60,000
Minimum:	5.7	---	--	----	---	--	--	---	---	---	---
TEST CONDITIONS:	6.3	25	--	---	---	--	--	---	---	---	---

GENERAL:

Qualification - Required

Source: https://assist.dla.mil -- Downloaded: 202610-15T14:33Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:33Z
Check the source to verify that this is the current version before use.

Method	Requirement or test	Conditions	AQL (percent defective)	Insp. level or code	Symbol	Limits Min	Limits Bogey	Limits Max	Unit
	Qualification								
© 1002	Barometric pressure reduced voltage breakdown	Pressure = 55± 5mm of Hg; Voltage = 500 Vdc							
	Quality conformance inspection, part 1								
1261	Grid voltage (1)	Ec1 = adjust for Ib = 1.0 mA; Ec2 = 100 Vdc; Zs = 2.5 meg ± 10%	0.65	II	Ec1	-7.5	-12.0	-16.5	Vdc
1261	Grid voltage (2)	Ec1 = adjust for Ib = 100 uA; Ec2 = 100 Vdc; Zs = 2.5 meg ± 10%	0.65	II	Ec1	---	-20.0	-30.0	Vdc
---	Gas	Ec1 = adjust for Ib = 1.0 mA; Ec2= 100 Vdc; Rg1 = 0.1 meg; Zs = 2.5 meg ± 10% (See note 1)	0.65	II	Δ Ib	---	---	150	μAdc
1201	Shorts and discon-- tinuity detection		0.4	II	---	---	---	---	---
	Quality conformance inspection, part 2								
1301	Heater current		6.5	II	If	415	450	485	mA
1336	Heater-cathode leakage	Ehk = +200 Vdc Ehk = -200 Vdc	6.5	II	Ihk Ihk	--- --	-- --	75 75	μAdc μAdc
1261	Grid voltage (3)	Ec1 = adjust for 1.0 mA; Ec2 = 100 Vdc; Eb = 20 Kv; Zs = 2.5 meg ± 10%	6.5	I	Ec1	-5.0	-9.0	-13.0	Vdc
1331	Direct interelec-trode capacitance	No shield No shield No shield	6.5	F	Cg1p Cin Cout	--- --- ---	--- --- ---	0.2 4.0 4.0	pF pF pF
1211	Insulation of electrodes	E(g-all) = -300 V	6.5	F	R	100	---	---	Meg
1041	Shock	G = 150; No voltages (note 2)	6.5	(Note 2)	---	---	---	---	---
1031	Vibration fatigue test	Frequency = 10 - 55 Hz; G = 10 Max. (See note 3) No voltage	6.5	(Note 2)	---	---	---	---	---
---	Post shock and vi-bration fatigue test end points	Grid voltage (1) Gas Heater-cathode leakage	--- --- ---	--- --- ---	Ec1 ΔIb Ihk	-5 --- ---	--- --- ---	-15 200 80	Vdc μAdc μAdc
1101	Secureness of base and cap		6.5	S3					

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:33Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:33Z
Check the source to verify that this is the current version before use.

Method	Requirement or Test	Conditions	AQL (Percent Defective)	Insp. Level or Code	Allowable Defectives Per Characteristic		Sym	LIMITS		Unit
					1st sample	Combined samples		Min	Max	
	Quality Conformance inspection, Part 3									
1501	Intermittent life-test operation	Group A; Ef = 6.3; Ic1 = 0; Eb = 25 Kv; Rk = adjust for Ib = 0.9 mA; Rg1 = 3.0 meg; RL = 5.0 meg; Cg = .01 µf; Ehk = 200 Vdc Cathode +; Ec2 = ground	---	---	---	---	---	---	---	---
---	Intermittent life-test and points (500 hours)	Gas	---	---	---	---	Ib	---	200	µAdc
		Grid voltage(1)	---	---	---	---	Ec1	5.0	---	Vdc

NOTES:

1. Conduct test under specified condition for 20 seconds and note Ib reading. Switch grid 1 resistor (Rg1) from 0.1 meg to 4.0 meg. Note Ib reading. The difference in the two readings shall be the Δ Ib value.

2. This test shall be conducted on the initial lot and thereafter on a lot approximately every 6 months. When one lot has passed, the 6 month rule shall apply. In the event of lot failure, the lot shall be rejected and the succeeding lots shall be subjected to this test until a lot passes. Standard MIL-STD-105, sample size code letter F, shall apply.

3. The tubes shall be vibrated for 90 cycles in each of three positions; X_1 X_2, and Y_1. Each cycle, from 10 to 55 to 10 Hz shall be covered in a period of 1 minute.

Custodians:

Army - EL
Navy - EC
Air Force - 85

Review Activities:
Army - EL
Navy
Air Force - 11, 17, 85

User activities:
Army - MU, ME
Navy - AS, OS, MC, CG, SH
Air Force - 19

Preparing activity:
Navy - EC
(Project 5960-2413)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:33Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:33Z
Check the source to verify that this is the current version before use.