MILITARY SPECIFICATION

CARTRIDGE, 40MM, PRACTICE, M407A1; BALL AND SKIRT ASSEMBLY AND OGIVE FOR METAL PARTS FOR

1. SCOPE

1.1 This specification cover the metal parts for the Ball and Skirt Assembly and Ogive for the M407A1 Cartridge.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-A-2550	-	Ammunition and Special Weapons, General Specification for
MIL-I-45607	-	Inspection Equipment, Supply and Maintenance of

STANDARDS

FEDERAL

FED-STD-151	-	Metals; Test Methods

1310

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109	-	Quality Assurance Terms and Definitions
MIL-STD-331	-	Fuze and Fuze Components, Environmental and Performance Test for
MIL-STD-1168	-	Lot Numbering of Ammuntion
MIL-STD-1169	-	Packaging, Packing and Marking for Shipment of Inert Ammunition Components
MIL-STD-1235	-	Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

US ARMY MUNITIONS COMMAND

8865604	-	Ball and Skirt Assembly
8840508	-	Ogive
9224169	-	Ogive

PUBLICATIONS

ARMY

ET-8865604	-	Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Material. -Materials shall be in accordance with the applicable drawings and specifications.

3.2 Parts. -The parts shall comply with all requirements specified on Drawings) 8865604, 8840508 and 9224169 and with all requirements specified in applicable specifications.

3.3 Skirt hardness and compression.

3.3.1 Hardness. -The hardness shall be 68 ± 10 on the Rockwell E scale when tested as specified in 4.4.3. This requirement is not applicable when skirt is made from tubing or bar stock.

3.3.2 Compression. -The skirt when compressed to 3/4 inch in a plane normal to its longitudinal axis, shall show no evidence of cracks when tested as specified in 4.4.4. This requirement is not applicable when skirt is made from tubing or bar stock.

3.4 Workmanship. -All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion productions, and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents.

3.5 Submission of results of contractor-conducted examinations and tests. -The contractor shall forward copies of the results of any of his examinations or tests to the designated address as required by the contract. (See 6.4)

3.6 First article testing. -This specification makes provisions for first article testing. Submission of first article quantity by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions. -Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 in order to define terms used herein. The provisions of MIL-A-2550 shall apply.

4.1.1 Submission of product. -At the time the completed lot of product is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all the quality assurance provisions specified within this specification.
b. Number of units of product inspected.
c. Results obtained, by code number, for all inspections performed:
d. Drawing, specification number and date, together with an identification and date of changes.
e. Certificates of conformance on all material purchased by the contractor when such material is controlled by Government or commercial specifications referenced in any of the contractual documents.
f. Number of items in the lot.
g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First article inspection.

4.2.1 Submission. -The contractor shall submit a first article quantity as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.2.2. The first article sample shall consist of the following:

a. Fifty (50) ball and skirt assemblies.
b. Fifty (50) balls.
c. Fifty (50) skirts.
d. Twenty (20) of each ogive.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

All parts and completed assemblies submitted shall have been produced by the contractor (or furnished by a supplier) using the same production processes, procedures and equipment as will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same sources of supply as will be used in regular production. The sample shall be accompanied by certificates of conformance. a first article quantity, or portion thereof, as directed by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days, or whenever a change occurs in manufacturing process, material used, drawing, specification or source of supply as to significantly affect product uniformity as determined by the Government. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample. A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer.

4.2.2 Inspections to be performed. -Assemblies and components will be subjected by the Government to any or all the examinations or tests specified in this specification and any or all requirements of the applicable drawings. In addition, any or all of the following examinations and tests will be performed.

4.2.2.1 Hardness of skirt. -The fifty (50) skirts shall be subjected to this test.

4.2.2.2 Inspection. -This paragraph provides guidelines for minimum first article inspection in cases where there is more than one source of supply for one or more components:

4.2.2.2 Balls (Dwg 8865603). -Inspect each ball for all drawing dimensions and requirements.

4.2.2.2.2 Skirt (Dwg 8840512).-Inspect each skirt for all dimensions in main view except inside spherical radius need not be gaged. Inspect ten (10) parts visually for other features. Test each skirt for hardness (See 3.3.1) and compression (See 3.3.2).

4.2.2.2.3 Ball and skirt assembly (Dwg 8865604). -Inspect each ball and skirt assembly in accordance with the provisions of 4.2.2.

The number of first article samples (70 assemblies each sample--See 4.2) to be submitted shall be equal to the greatest number of suppliers of any one component, and each supplier's components shall be included in at least one first article sample of ball and skirt assemblies.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

NOTE: In regular production, components which have passed first article inspection may be mixed in any combination regardless of source of supply to make ball and skirt assemblies.

4.2.3 Rejection. -If any assembly or component fails to comply with any the applicable requirements, the first article quantity shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an assembly or component in the sample to comply with any of the stated requirements. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new first article quantity or portion thereof. Until a first article quantity is accepted, the contractor is in no way authorized by the Government to resume regular production unless otherwise directed by the Contracting Officer.

4.3 Inspection provisions.

4.3.1 Lot formation. -The term "lot" as used throughout this specification refers to an inspection lot, which is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance of the lot with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the lot has been produced by one manufacturer, in one unchanged process using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions. Changes to the process, specificications, or drawings, not affecting safety, performance, interchangeability or storage, as determined by the Government, shall not be deemed to alter the homogeneity of the lot. Inspection lots shall comply with MIL-STD-105.

Unless otherwise approved by the Contracting Officer, the inspection lot size of end items deliverable under the contract shall be not less than the smallest weekly estimate of quantities contractually scheduled for production during the contract period, nor more than the largest monthly quantity contractually scheduled for delivery during the contract period. Inspection lots of components or subassemblies, other than the items of delivery, shall be homogeneous and of a size mutually convenient to both the contractor and the Government inspector. Lot numbering, as required, shall be in accordance with MIL-STD-1168.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

4.3.2 Examination. -Sampling plans and procedures for the following classifications of defects shall be in accordance with MIL-STD-105 (ABC-STD-105), except that, inspection for Critical defects shall be 100 percent. Contractor's sampling plans, if used shall be approved by the Government, and shall provide, as a minimum, the protection afforded the Government by the sampling plans In MIL-STD-105. Continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to the individual characteristics listed using an AQL of 0.40 percent for each Major defect and an AQL of 0.65 percent for each Minor defect except where 100% inspection is specified. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Ball (See Dwg 8865603 covering a detail of Dwg 8865604).-

Categories	Defects	Method of Inspection	Code No. (See 6.2)
Critical:	None defined		
Major	AQL 0.40 Percent		
101.	Weight	Balance	01001
Major	AQL 0.40 Percent (See 4.3.3.2)		
102.	Pitch diameter of thread, minimum	Gage	01002
Minor	AQL 2.50 percent (See 4.3.3.2)		
201.	Length of thread, min	Gage	01003
202.	Outside diameter, maximum (max)	Gage	01004
203.	Outside diameter, threaded end	Gage	01005
204.	Depth of cavity	Gage	01006
205.	Diameter of cavity	Gage	01007
206.	Evidence of poor workmanship (See 3.4)	Visual	01008

4.3.2.2 Ball and skirt assembly (See Dwg 8865604). -

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major	AQL 1.50 Percent		
101.	Hardness of skirt	Test (See 4.4.3)	02001
102.	Concentricity of bourrelet diameter with pitch diameter of thread including perpendicularity with fuze seating surface	Gage	02002

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:07Z
Check the source to verify that this is the current version before use.

103.	Bourrelet diameter	Gage	02003
104.	Concentricity of outside diameter for ogive on skirt with bourrelet diameter of skirt	Gage	02004
		Gage	02005
105.	Profile of rotating bands	Gage	02006
106.	Location of rotating bands	Gage	02007
107.	Profile ogive crimp groove on skirt	Gage	02008
108.	Location of ogive crimp groove on skirt	Gage	02009
109.	Diameter of rotating bands	Gage	02010
110.	Profile of cartridge case groove on skirt	Gage	02011
111.	Diameter of cartridge case groove On skirt	Gage	02012
112.	Diameter ogive crimp end on skirt	Gage	02013
113.	Distance from curved surface to rotating bands	Gage	02014
114.	Diameter of ball end	Gage	02015
115.	Height of ball, max		

AQL 1.50 Percent

Minor		Gage	02016
201.	Total length	Visual	02017
202.	Protective coating missing	Visual	02018
203.	Skirt color incorrect	Visual	02019
204.	Evidence of poor workmanship (See 3.4		

4.3.2.3 Ogive (See Dwg 8840508).-

Categories	Defects	Method of Inspection (See 4.3.3.1)	Code No.
Critical:	None defined		
	AQL 0.65 Percent		
Major		Gage	03001
101.	Total length	Gage	03002
102.	Inside diameter	Gage	03003
103.	Radius	Gage	03004
104.	Wall thickness, min for required distance		
	AQL 1.50 Percent		
Minor		Gage	03005
201.	Diameter of flat	Visual	03006
202.	Protective finish with bare spot	Visual	03007
203.	Color incorrect	Visual	03008
204.	Evidence of poor workmanship (See 3.4)		

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

4.3.2.4 Ogive (See Dwg 9224169). -

Categories	Defects	Method of Inspection (See 4.3.3.1)	Code No.
Critical:	None defined		
Major	AQL 0.65 percent		
101.	Total length	Gage	04001
102.	Inside diameter	Gage	04002
103.	Large outside radius	Gage	04003
104.	Depth of inside diameter	Gage	04004
Minor	AQL 2.50 Percent		
201.	Diameter of flat	Gage	04005
202.	Wall thickness through bottom	Gage	04006
203.	Wall thickness, open end	Gage	04007
204.	Height of inside protrusion	Gage	04008
205.	Color incorrect	Visual	04009
206.	Evidence of poor workmanship (See 3.4)	Visual	04010

4.3.3 Testing.

4.3.3.1 Dimensional control of stamped parts, Code No. 05001. - In place of the normal sampling associated with the classifications of defects, and with the approval of the Contracting Officer, a sample of at least ten (10) parts may be dimensionally inspected to qualify the tool used in the stamping process for use in production. In addition, a random sample of five (5) parts shall be selected from the last portion of each hour's production for dimensional inspection as a control of the tool during production.

If any defective parts are found during qualification of the tool, the tool producing the defective part shall not be used in production.

If any defective parts are found when inspection is performed for control of the tool, the tool producing the defective part shall be removed from production. Further, that portion of production since the last tool control check shall be returned to the contractor for corrective action.

All tools removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Officer to substantiate the request.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

4.3.3.2 Dimensional control of molded parts, Code No. 06001. - In place of the normal sampling associated with the classifications or defects, and with the approval of the Contracting Officer, and after a curing time for the parts has been approved (See Note 1), a sample of three (3) parts (as molded) from each cavity may be dimensionally inspected to qualify a new or reworked cavity for use in production or as a control of each cavity during production.

The inspection of the parts shall be performed only when the curing time for the parts has been reached. The inspection for control of each cavity during production shall be performed on the above quantities from each cavity after production of each 5000 parts or at the end of each shift, providing the number of parts produced during that shift is less than 5000 parts. Of the three (3) samples, one (1) sample shall be the last part produced. Parts that fail to comply with dimensional requirements after dimensional stability has been attained shall be classed defective.

If any defective parts are found during qualification of the cavity, the cavity producing the defective part will not be used in production. If any defective parts are found when inspection is performed for control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for corrective action.

All cavities formerly removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test as above. The contractor may request a change of inspection frequency providing he presents objective evidence to substantiate the request to the Contracting Officer.

(NOTE 1) - In establishing a curing time, dimensionally check ten (10) parts from each cavity at fifteen (15) minute intervals until dimensional stability is attained. The curing time will be from the time the part comes out of the mold until dimensional stability is attained. The inspection data used in determining the curing time shall be sent to Picatinny Arsenal, SMUPA-ND3. If any new change in material cycle time, a reworked cavity, or new cavity is used, a new curing time shall be established and approved.

4.3.3.3 Torque of thread in ball and skirt assembly (See Dwg 8865604) Major Defect, Code No. 07001. -Fifty (50) ball and skirt assemblies shall be selected from each shift's production and subjected to this test. If any assembly fails to comply with the requirement specified on the applicable drawing, the shift's production represented by the sample shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

4.3.3.4 Torque of sphere of ball and skirt assembly (See Dwg 8865604) Major Defect, Code No. 08001. -Fifty (50) ball and skirt assemblies shall be selected from each shift's production and subjected to this test. If any assembly fails to comply with the requirement specified on the applicable drawing, the shift's production represented by the sample shall be rejected.

4.3.3.5 Compression of skirt (See Paragraph (Para) 3.3.2) Major Defect, Code No. 09001. -Fifty (50) skirts shall be selected from each shift's production and subjected to this test. If any skirt fails to comply with the applicable requirement, the shift's production represented by the sample shall be rejected.

4.3.4 Inspection equipment. -Equipment Tabulation (ET) number 8865604 and Equipment Lists (EL) referenced thereon identify the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in 6.3.

4.3.4.1 Government rights to documentation. -Inspection equipment drawings and lists provided and revised in accordance with the requirements of this specification may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.3.4.2 Supply and maintenance. -Supply and maintenance of the equipment listed on the EL's shall be in accordance with MIL-I-45607.

4.3.4.3 Government use of contractor's inspection and test equipment. -The contractor shall, when required by the Government, make available all inspection and test equipment necessary for determining conformance with the contract requirements. Personnel for operating the equipment, and verification of its accuracy shall be supplied by the contractor for the performance of examination or test by the Government.

4.4 Test methods and Procedures.

4.4.1 Torque of threads in ball and skirt assembly. -The ball and skirt assembly shall be placed in the fixture shown on the Equipment List and the torque specified on Dwg 8865604 shall be applied. This test is a non-destructive test. Parts so tested may be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

4.4.2 Torque of sphere on ball and skirt assembly. -The ball and skirt assembly shall be placed in the fixture shown on the Equipment List and the torque specified on Dwg 8865604 shall be applied. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.4.3 Hardness of skirt. -This test shall be conducted in accordance with Standard FED-STD-151, Method 243. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.4.4 Compression of skirt. -The skirt shall be placed in a fixture and a load shall be applied in a plane normal to its longitudinal axis to compress the skirt to the dimension specified in paragraph 3.3.2. Any equipment considered satisfactory to the Contracting Officer may be used in performing this test. This test is a destructive test. Parts so tested shall not be returned to the lot.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 Level C - Minimum military package. -See 5.2.1

5.2 Packing.

5.2.1 Level C - Minimum military pack. - Packing shall be in accordance with the provisions of MIL-STD-1169.

5.3 Shipping. -When shipments of more than one lot are made as a carload, each lot must be kept separate, and the division between lots clearly indicated, to prevent mixing in transit.

5.4 Marking. -Marking shall be in accordance with MIL-STD-1169.

6. NOTES

6.1 Ordering data. -Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Data cards shall be prepared for each lot in accordance with the information specified in MIL-STD-1167.
c. Provisions for submission of first article samples.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

6.2 Inspection code numbers, -The five-digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment. -The contractor shall design inspection equipment as required by the referenced Equipment Lists (EL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.6.

6.3.1 Equipment lists. -Equipment lists indicate the availability of inspection equipment designs by showing in the "Part Number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings of Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the "part Number" column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.6. Action required by the contractor with respect to the use of commercial equipment is detailed in 6.3.5.

6.3.2 Equipment list codes. -The inspection equipment as defined in 6.3.3, 6.3.4 and 6.3.5 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

6.3.3 Army designs. -Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications; mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, and with the approval of the Government, design alternate inspection equipment to facilitate his operations. Such contractor-prepared designs (See 6.3.4) or commercial equipment selections (See 6.3.5) must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

6.3.4 Contractor designs. -Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finishes, notes, and operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category E, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high-contrast reproductions. Contractors shall submit one copy of final designs as a rolled set. Designs shall be submitted for approval as specified in 6.3.6.

6.3.5 Commercial equipment. -Commercial equipment is inspection equipment that has universal application for a specific function. It is comprised of items commonly used by industry and Government. Contractors, normally, are not required to furnish drawings of commercial inspection equipment, but a list of such equipment must be approved by the Government. When commercial inspection equipment requires the use of special fixturing, the design of this fixturing shall be considered as part of the total design, and 6.3.4 shall apply. In the latter case, only those portions of the commercial equipment need be detailed in the designs as are necessary to completely fabricate, calibrate, and operate the total item of inspection equipment. Lists and fixturing designs shall be submitted for approval as specified in 6.3.6.

6.3.6 Submission of contractor designs.-All submitted designs shall contain a reference to the applicable 5 digit code number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as Critical and Major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-NDIC. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract. Submission shall be as directed by the Contracting Officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished, normally, within one month after receipt.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

6.4 Submission of results of contractor-conducted examinations and tests. -Unless otherwise specified by the Contracting Officer, the contract shall forward requested records of examinations or tests to Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND3.

Custodian:
Army-MU

Preparing activity:
Army-MU

Project Number: 1310-A062

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
PICATINNY ARSENAL
DOVER, NEW JERSEY 07801

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

COMMANDING OFFICER
United States Army
Picatinny Arsenal
ATTN: SMUPA-ND
Dover, New Jersey 07801

FOLD

GPO 303-224/Z 849

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 61 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.