MILITARY SPECIFICATION

MICROCIRCUIT, DIGITAL, CMOS (FINAL LOGIC)

This Amendment forms a part of Military Specification MIL-M-63321A(AR) dated 8 April 1981, and is approved for use within the US Army Armament Munition and Chemical Command and is available for use by all the Departments and Agencies of the Department of Defense.

PAGE 3

3.4: Mechanical shock, Conditions: Delete "D" and substitute "C".

* Delete "Method 2015.1" and substitute "Method 2015".

PAGE 5

3.5.4., (a) and (b): Delete (-45° C to +85°C) and substitute (-40° C to +70° C).

PAGE 8

4.3.1 Submission: Delete last sentence and substitute "The first article sample, after screening, shall consist of the quantities needed for double samplings stipulated in Table III."

4.3.4: Add "e. A lapse in production for a period exceeding 90 days or as stipulated in the contract".

PAGE 9

TABLE III, Subgroups a, b, c, d: Delete "25" and substitute "note 8";

Subgroup b, Mechanical shock: Delete condition "D" and substitute condition "C";

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:38Z
Check the source to verify that this is the current version before use.

* Subgroup c, Resistance to solvent: Delete "Method 2015.1" and substitute "Method 2015".

PAGE 10

TABLE III, Subgroup g: Delete "25" and substitute "note 9";

NOTES: Delete present content of note 1 and substitute "Devices which fail any test criteria in the screening sequence shall be removed from the first article sample. The contractor should choose a first article sample that will provide, after screening, the quantities stipulated in notes 8 and 9.

Notes: Delete content of note 8 and substitute:

A double sampling plan shall be used as follows: 25-0-2, 38-1-2. For group b replace fallouts from subgroup a.

Add "note 9. A double sampling plan shall be used as follows: 45-0-2, 77-1-2.

PAGE 13

4.4.2.2, AGL or 100% Column: Delete "All LTPD's" and substitute "LTPD's of 10%, 10%, 10% and 10%".

PAGE 14

* 4.4.2.3: Subgroup 2, Resistance to solvents: Delete "Method 2015.1" and substitute "Method 2015".

Delete "Bond strength (bond pulls 1/), ---, LTPD 15%". and substitute "Bond strength (bond pull 1/, 5, 1-2".

Delete Notes "1/" in its entirety and substitute: " 1/ Pull all bond wires on each device - reject for two (2) or more bond failures".

PAGE 15

4.4.2.4, Subgroup 2, Mechanical shock: change Condition "D" to Condition "C".

PAGE 19

* 4.5.16, Burn-in screen, line 6: Delete "7.5 volts DC" and substitute "8.0 volts DC".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:38Z
Check the source to verify that this is the current version before use.

* 4.5.17, Steady state life, line 3: Change "Test duration shall be 100 hours minimum at 125° C ± 5° C." to "Test duration shall be 1000 hours minimum at 125° C ± 5° C or equivalent per Method 1005 of MIL-STD-883B. Temperature in excess of 135° C + 8°C and test duration less than 496 hours shall not be allowed".

PAGE 20


6.3 and 6.5: Delete "QAA" amd substitute "QAT".

PAGE 30

FIGURE 11: Delete present and substitute revised FIGURE 11 included to this amendment.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:38Z
Check the source to verify that this is the current version before use.



V_H = 8.0 - .5 volts

V_L = 0.5 ± 0.15 volts

T = 40 ± 4μs period, 50% duty factor.

All R(s) = 51K ohms max.

FIGURE 11. Burn-in and steady state of life test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:38Z
Check the source to verify that this is the current version before use.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A378)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:38Z
Check the source to verify that this is the current version before use.