MIL-P-60818C (AR)
AMENDMENT 2
22 NOVEMBER 1983
SUPERSEDING
AMENDMENT 1
22 November 1977

MILITARY SPECIFICATION

PROJECTILE, 4.2 INCH, ILLUMINATING, M335A2
METAL PARTS ASSEMBLY

This amendment forms a part of Military Specification MIL-P-60818C (AR) dated 22 February 1977, and is approved for use by the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 8

* 4.3.2.2.1:

Delete: Major defects 101, 102, 103 and 104.

Add: Major defects:

"108 Outside diameter forward of shoulder Gage

109 Length of outside diameter forward of shoulder Gage".

Delete: Minor defect 208.

PAGE 11

* 4.3.2.7.1: Delete Major defects 101 and 102.

PAGE 12

* 4.3.2.7.1:

Delete: Major defect 105.

FSC 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:58Z
Check the source to verify that this is the current version before use.

Add: Major defects.

"108 Diameter of through hole Gage

109 Run-out of through hole diameter with bourrelet Gage"

PAGE 13

* 4.3.2.9: Add new Major defect and note:

"110. Swaging of spacer improper (less than 360°) Visual (see note).

NOTE: This inspection to be performed 100 percent."

* 4.3.3.2.2.2.1, line 3:

Delete "nor" substitute "not".

Delete "each".

Delete "hours for" substitute "bars from".

PAGE 16

* Add new paragraph:

"4.3.3.5 Disassembly test of spacer. The sampling for this test shall be in accordance with MIL-STD-105, Special Inspection Level S-4 and an AQL of 0.65%. The test shall be performed as specified in 4.4.4."

PAGE 17

4.4.1.2.1, line 3: Delete "R" add "T".

PAGE 19

* Add new paragraph:

"4.4.4 Disassembly test of spacer. The projectile shall be held in a fixture and a disassembly force shall be applied to the spacer. The spacer must withstand a

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:58Z
Check the source to verify that this is the current version before use.

specified minimum force. The equipment shall be capable of indicating the applied force and the force shall be recorded. The assembly that withstand the specified requirement may be returned to the production lot."

NOTE: The margins of this amendment are marked with an asterisk or vertical line to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1315-A495)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:58Z
Check the source to verify that this is the current version before use.