MILITARY SPECIFICATION

TELESCOPES, ELBOW, M99 AND M99C

1. SCOPE

1.1 This specification covers one basic type of telescope known as Telescope, Elbow, M99 hereinafter referred to as telescope (see 6.1). The additional designation identifies reticle design and application differences.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-O-13830	Optical components for Fire Control Instruments; General Specification Governing the Manufacture, Assembly and Inspection of
MIL-F-13926	Fire Control Materiel; General Specification Governing the Manufacture and Inspection of
MIL-P-14232	Parts, Equipment and Tools for Ordnance Materiel, Packaging of
MIL-I-45607	Inspection Equipment, Supply and Maintenance of

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	Quality Assurance Terms and Definitions

DRAWINGS

U.S. Army, Frankford Arsenal

F8206215	Telescope, Elbow, M99 and M99C
F8565556	Pressure Tester - Two Station

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:00Z
Check the source to verify that this is the current version before use.

PACKAGING DATA SHEET

8206215	Packaging of Telescope, Elbow, M99
8242617	Packaging of Telescope, Elbow, M99C

(Copies of specifications, standards, drawings and packaging data sheets required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Fabrication. - The telescope shall be manufactured in accordance with Drawing F8206215 and all drawings pertaining thereto.

3.23 General specification. - The contractor shall be responsible for compliance with the following requirements of MIL-F-13926:

a. Order of precedence
b. Dimensions and tolerances
c. Inorganic protective surface finishes
d. Part identification and marking

3.3 Temperature conditions. - Except as Specified in 3.5.1 and 3.5.2, the following requirements shall be met at a temperature between 60° and 90°F.

3.4 Workmanship. - The workmanship of MIL-F-13926 shall be met. The exterior protective surface finishes shall be free of defects which may affect their protective qualities or appearance. Optical surfaces shall be free of scratches and blemishes which may affect their optical qualities or appearance.

3.5 Environmental.

3.5.1 Extreme storage temperatures. - The telescope shall show no evidence of physical failure and shall meet the applicable requirements of this specification at a standard ambient temperature of 60° to 90° after having been exposed and thermally stabilized at -80° and +160°F.

3.5.2 Extreme operating temperatures. - The telescope shall meet the applicable requirements of 3.8 while exposed and thermally stabilized at -40° and +150°F.

3.5.3 Vibration. - The telescope shall be capable of meetijg all requirements of this specification after having been vibrated at 30 cycless per second at an amplitude of 0.06 inch (0.12 total excursion) for a period of 5 minutes plus or minus 15 seconds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:00Z
Check the source to verify that this is the current version before use.

3.5.4 Sealing. - The telescope shall be capable of maintaining a seal for a period of 2 hours when subjected to an internal pressure of dry nitrogtrn at 5 ± 0.1 pounds per square inch gage (psig) without loss of pressure in excess of .2 lbs. The interior atmosphere of the accepted telescope shall contain nitrogen with a dew point at least as low as -25°F.

3.6 Cleanliness. - The telescope shall meet the cleanliness requirements of MIL-O-13830 when viewed through the eyepiece. the telescope shall show no more than five particles of dirt 0.2 mil maximum real diameter in the outer 35 degrees and four particles of dirt 0.05 mil maximum real diameter in the central 25 degrees of the apparent field. There shall be no other dirt which adversely affects observation and image quality.

3.7 Accuracy.

3.7.1 Orientaiton. - The telescope shall meet the requirements of 3.7.2 to 3.7.10 inclusive while positioned as follows:

a. The geometric axis of the objective tube and the eyepiece locating surface horizontal and the vial bubble centered.

3.7.2 Collimation.

3.7.2.1 Elevation. - The line of sight through the boresight cross of the reticle pattern shall be 40 mils ± 1.0 mil above the geometric axis of the objective tube.

3.7.2.2 Azimuth. - The line of sight through the boresight cross of the reticle pa-hall be in coincidence with a vertical plane that passes through the geometric axis of the objective tube within 0.50 mil.

3.7.2.3 Collimation change (due to vibration). - An original line of sight shall not deviate more than 0.10 mil due to vibration.

3.7.3 Image tilt. - The image of a vertical target line shall be vertical within 1 degree of arc with the eyepiece orientation as in 3.7.1.

3.7.4 Parallelism of reticle and image. - The vertical line of the reticle pattern shall be parallel to the image of a vertical target line within 30 minutes of arc with the eyepiece oriented as in 3.7.1.

3.7.5 Patallax. - Parallax at the center of the field shall not exceed 0.12 mil when viewing a target at 300 yards.

3.7.6 Resolution. - The resolution on the optical axis shall be 12 seconds of arc or less when using an auxiliary telescope of at least 3 power having an entrance pupil of at least 0.4 inches. Resolution shall consist of detectable line structure and proper line count in all four meridians. Variations in focus between meridians shall not exceed 0.25 diopters as measured at the telescope eyepiece.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:00Z
Check the source to verify that this is the current version before use.

3.7.7 Reticle accuracy. - The angular value between the boresight cross and the maximum range mark shall be as indicated on the reticle drawing within plus or minus 1.0 mils

3.7.8 Boresight shift. - Any movement of the horizontal and vertical boresight adjustment locking levers shall not cause the target image to shift with respect to the reticle more than 0.1 mil.

3.7.9 Circular field of view. - With the aximuth and elevation boresight knobs at zero index, the fields of view in azimuth and elevation shall be equal within 1 degree.

3.7.10 Eyepiece focus. - Eyepiece focus shall be fixed between the limits of minus 0.75 and minus 1.0 diopter at which setting the reticle shall appear in sharp focus.

3.8 Operability.

3.8.1 Eoresight knob travel. - The azimuth and elevation knobs shall be capable of moving the image plus or minus 10 mils in azimuth and elevation respectively from the zero setting of the knobs as defined under 3.7.2.

3.8.2 Reticle rotation. - The line of sight shift shall not exceed 4.0 mils including backlash, when the reticle is rotated 300 mils each side of central position.

3.8.3 Reticle rotation knlb. - The running torque required to rotate the reticle rotation knob shall not exceed 11 pound inches when checked at standard ambient temperatures and shall not be exceeded by more than 11 pound inches when checked at extreme temperatures of 3.5.2.

3.8.4 Boresight knobs. - The running torque required to rotate the boresight knobs with locks fully released shall not exceed 12 pound inches when checked at standard ambient temperatures and shall not be exceeded by more than 12 pound inches when checked at extreme temperatures of 3.5.2.

3.9 Illumination. - With the reticle and level vial lamps-energized with three volts, the reticle markings and level-vial-shall be visible when observed in a darkened area.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. - Unless otherwise specified in the contract or purchase order, the supplier is responsible ror the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:00Z
Check the source to verify that this is the current version before use.

specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 General provisions. - The component and subassembly inspection requirements of MIL-F-13926 form a part of the Quality Assurance Provisions of this specification. Definitions of inspection terms shall be as listed in MIL-STD-109.

4.2 First article (initial production) submission. - When required by the contract, an initial production sample shall be submitted to a Government approved facility for test and evaluation in accordance with the contract schedule. The sample shall consist of three telescopes. The sample shall be manufactured in the same manner, using the same materials, equipment, processes and procedures as used in regular production. All parts and materials, including packaging and packing, shall be the same as used for regular production and shall be obtained from the same source of supply. After inspection and provisional acceptance at source, the initial production sample shall be inspected at a Government approved facility for all requirements of the drawings, and specifications. The Government reserves the right to require new initial production samples until such time as an acceptable sample is submitted.

4.3 Inspection provisions.

4.3.1 Submission of product.- 4.3.1 Submission of product. - Unless Otherwise specified by the contracting officer, inspection lot size, lot formation and presentation lot formation and presentation of lots shall be in accordance with "Submission of Product" provisions of MIL-STD-105.

4.3.2 Examination and tests.

4.3.2.1 Components and subassemblies. - All components and subassemblies shall be inspected in accordance with the inspection provisions contained in Supplementary Quality Assurance Provisions (SQAP) listed in the List of Inspection Documents (IEL), when provided with the technical data package (TDP). In the absence of SQAP'S the applicable Quality Assurance Provisions of MIL-F-13926 shall apply.

4.3.2.2 Final acceptance inspection. - Subsequent to first article approval, examination and tests related to Section 3 herein shall be performed on a single defect (individual characteristic) basis in accordance with MIL-STD-105 and the sampling plans specified in Table I herein. Examination and tests for Packaging, Packing and Marking shall be in accordance with MIL-P-14232 and Section 5 herein. The tabulated classification of defects in Table I shall constitute the minimum inspection to be performed by the supplier after first article approval and prior to Government acceptance or rejection by item or lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:00Z
Check the source to verify that this is the current version before use.

TABLE I - CLASSIFICATION OF DEFECTS

CLASS	CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
MAJOR:	AQL 1.0 Defective		
101.	Physical failure (Post vibration)	3.5.3	4.6.1.3
102.	Cleanliness	3.6	4.6.2
103.	Collimation (Post vibration)	3.7.2.1	4.6.4.3
104.	Elevation	3.7.2.2	4.6.4.1
105.	Azimuth	3.7.2.3	4.6.4.2
106.	Image tilt	3.7.3	4.6.5
107.	Parallelism of reticle and image	3.7.4	4.6.6
108.	Parallax	3.7.5	4.6.7
109.	Resolution	3.7.6	4.6.8
110.	Reticle accuracy	3.7.7	4.6.9
111.	Boresight shift	3.7.8	4.6.10
112.	Circular field of view	3.7.9	4.6.11
113.	Eyepiece focus	3.7.10	4.6.12
114.	Boresight knob travel	3.8.1	4.7.1
115.	Reticle rotation	3.8.2	4.7.2
116.	Reticle rotation knob (60° - 90°F)	3.8.3	4.7.3
117.	Boresight knobs (60° - 90°F)	3.8.4	4.7.4
118.	Illumination	3.9	4.7.5

4.3.3 Acceptance and rejection. - Rejected lots shall be screened for all defective characteristics. Removal or correction of defective units and resubmittance of rejected lots shall be in accordance with "Acceptance and Rejection" as specified in MIL-STD-105.

4.4 Special sampling. - Three (3) telescopes shall be selected at random from each 50 produced as special samples. The samples shall meet the requirements of Table II.

TABLE II

	CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
301.	Fabrication	3.1	Applicable drawings - Visual
302.	General specification	3.2	MIL-F-13926 - Visual
303.	Storage temperatures	3.5.1	4.6.1.1
304.	Operating temperatures	3.5.2, 3.8.3, 3.8.4	4.6.1.2, 4.7.3, 4.7.4
305.	Workmanship	3.4	MIL-F-13926 - Visual
306.	Sealing	3.5.4	4.6.1.4

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:00Z
Check the source to verify that this is the current version before use.

4.4.1 Failure of sample. - Should any one item of a special sampling fail to meet the specified test requirements, acceptance of the represented inspection lot will be suspended by the Government until necessary corrections have been made by the contractor and the resubmitted samples have been approved (see 4.3.3).

4.5 Inspection equipment. - Except as otherwise provided for by the contract, the contractor shall supply and maintain inspection equipment in accordance with the applicable requirements of MIL-I-45607.

4.5.1 Government furnished inspection equipment. - Where the contract provides for Government furnished test equipment, supply and maintenance of test equipment shall be in accordance with the applicable requirements specified in MIL-I-45607.

4.5.2 Contractor furnished inspection equipment.

4.5.2.1 Government design. - Unless otherwise specified in the contract, all inspection equipment specified by drawing number in specifications or SQAP forming a part of the contract shall be supplied by the contractor in accordance with technical data listed in the List of Inspection Documents when provided with the Technical Data Package (TDP).

4.5.2.2 Contractor design. - The contractor shall design and supply inspection equipment compatible with the "Test Methods and Procedures" specified in 4.6 of this specification and with the component inspection procedures specified in "Examination" and "Test Facilities" requirements of MIL-F- 13926. Since tolerance of test equipment is normally considered to be within 10% of the product tolerance for which it is intended, this inherent error in the test equipment design must be considered as part of the prescribed product tolerance limit. Thus, concept, construction, materials, dimensions and tolerance used in the design of test equipment shall be so selected and controlled as to insure that the test equipment will reliably indicate acceptability of a product which does not exceed 90% of the prescribed tolerance limit, and permit positive rejection when non-conforming. Construction shall be such as to facilitate routine calibration of test equipment.

4.6 Test methods and procedures.

4.6.1 Environmental.

4.6.1.1 Storage temperatures. - This test shall be performed as outlined in MIL-F-13926, Procedure II (temperature cycling) at the extreme temperatures specified in 3.5.1. After exposure, the telescope shall be visually inspected for damage, then tested as specified in 3.5.1.

4.6.1.2 Operating temperautes. - This test shall be performed as outlined in MIL-F-13926, Procedure I (temperature cycling) at the temperatures specified in 3.5.2. During exposure, the telescope shall be tested as specified in 3.5.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:00Z
Check the source to verify that this is the current version before use.

4.6.1.3 Vibration. - The telescope shall be mounted on a vibration table in its normal position and vibrated at the frequency, amplitude and duration specified in 3.5.3. The test ewuipmetn shall vbonform to the "Test wFacilities" requirement of MIL-F-13926 and visually inspected for damage then tested as specified in 3.5.3.

4.6.1.4 Sealing. - This test shall be performed using testing equipment the accuracy of which shall conform to the accuracy depicted on Drawing F8565556. The fixture shall be set-up as outlined in set-up instructions shown on Drawing F8565556, Sheet 1. The gas used shall be dry nitrogen having a sew point of -25°F. After connecting the test fixture to the telescope, adjust testing pressure to the pressure specified in 3.5.4 and maintain the pressure for time specified. At the completion of this test connect a dew point tester to the exit post and purge the telescope until -25°F is recorded and seal the unit.

4.6.2 Cleanliness. - The telescope shall be inspected for cleanliness as outlined in MI8L-O-13830. The allowable dirt particles shall not exceed the limits specified in 3.6.

4.6.3 Orientaion. - Special testing equipment shall be utilized to position the telescope as specified in 3.7.1. The telescope shall be positioned on a surface plate, leveled within 20 seconds of arc. The telescope's spherical mounting rings shall be secured by means of an adapter. The eyepiece locating surface shall be supported by means that will align the geometric axis of the telescope tube in a horizontal position with the bublle of the level vial centered. A target projector collimator shall be positioned in front of the telescope's objective. The collimator's reticle shall contain tolerance marks for measuring the telescope's optical requirements.

4.6.4 Collimation.

4.6.4.1 Elevation. - With the telescope positioned as specified in 4.6.3 with the-n boresight scale on zero, observe the position of the telescope's boresight cross with respect to the target collimator's reticle. The line of sight through the boresight cross shall be within the limits specified in 3.7.2.1. The position shall be recorded.

4.6.4.2 Azimuth. - With the azimuth scale on zero, the line of sight through the boresight cross reticle pattern shall be coincident with the vertical plane through the geometric axis of the objective tube and shall be within the limits specified in 3.7.2.2 as measured on the target. The position shall be recorded.

4.6.4.3 Collimation (post-vibration). - The telescope shall be removed from the test fixture and tested as specified in 4.6.1.3. Upon successful completion of the vibration test, the telescope shall be repositioned on the test fixture as specified in 4.6.3. The tests outlined in 4.6.4.1 and 4.6.4.2 shall be repeated. The positions of the boresight cross shall be noted then compared with the recorded positions observed In 4.6.4.1 and 4.6.4.2. The line of sight shall not deviate from the original recorded positions by more than the tolerance specified in 3.7.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:00Z
Check the source to verify that this is the current version before use.

4.6.5 Image tilt. - The telescope shall be oriented in accordance with 4.6.3. Using an adjustable auxiliary telescope and a flat surface to position the auxiliary telescope at the eyepiece of the telescope under test, adjust the auxiliary telescope to the height of the telescope eyepiece. Adjust the auxiliary telescope's vertical reticle line in conincidence with a plumb. Sight through the auxiliary telescope and the eyepiece of the telescope to the target. The verical target line image shall be parallel to the vertical reticle line of the auxiliary telescope within the tolerance specified in 3.7.3.

4.6.6 Parallelsim of reticle and image. - This test can be performed concurrently with the test specified in 4.6.5. The vertical reticle line of the telescope shall not deviate from the image of the vertical target line by more than the tolerance specified in 3.7.4. The vertical reticle line of the auxiliary telescope shall again be used as the index to measure the error in the telescope.

4.6.7 Parallax. - Parallax shall be determined by viewing a target at the distance specified in 3.7.5. Parallax can be distingusidhed by adjusting the vertical and horizontal lines of the telescope reticle parallel to the image of the target lines without touching, leaving a minimum of space or light between the lines. The observer shall move his head from side to side or up and down. Any movement of the target in either direction (the space getting wider or narrower) is considered parallax. The amount of parallax observed shall not exceed the tolerance requirements of 3.7.5.

4.6.8 Resolution. - This test shall be performed in accordance with the resolution test specified in MIL-O-13830. The telescope shall permit resolution of a target within the limit specified in 3.7.6.

4.6.9 Reticle accuracy. - Position the telescope as specified in 4.6.3. Reticle accuracy shall be checked by alining the lines of the telescope's boresight cross with the reference lines of the target reticle. View through the eyepiece of the telescope and using the level vial and reticle adjustment knob and boresight knobs, aline the boresight cross of the telescope on the reference lines of the target reticle. The angular value between the boresight cross and maximum range mark shall be within the limit specified in 3.7.7.

4.6.10 Boresight shift. - Position the telescope as specified in 4.69.3. Place the boresight locking levers to their locked position. View through the eyepiece of the telescope. The position of the telescope reticle with respect to the target reticle shall be noted. Apply normal Apply normal hand pressure to rotate the boresight knobs. Any movement of the knobs shall not shift the position of the boresight image previously observed by more than the tolerance specified in 3.7.8.

4.6.11 Circular field of view. - With the telescope positioned as specified in 4.6.3, set the elevation and azimuth boresight knobs at zero.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:00Z
Check the source to verify that this is the current version before use.

Center the telescope level vial bubble. Repeat the tests of 4.6.4.1 and 4.6.4.2. The line of sight in both azimuth and elevation shall be noted. The field of view shall be circular with respect to each position within the limits specified in 3.7.9.

4.6.12 Eyepiee focus. - The telescope eyepiece shall be set between the tolerances specified in 3.7.10 to detemine the correct setting of the eyepiece, a dioptometer of three power (3X) shall be used that has been adjusted to the individual eye. This can be accomplished by sighting through the dioptometer at a white background and adjusting the eyepiece of the dioptometer until the reticle is at the sharpest point obtainable. Position the barrel of the dioptometer to set the index at zero. When this has been accomplished, sight through the dioptometer and the eye-piece of the telescope. Observe the reticle of the telescope and compare it with the reticle of the dioptometer. Adjust the barrel of the dioptometer to make the reticle of the telescope go out of focus; then re-adjust the barrel to bring the telescope reticle into focus at the sharpest point. Read the error on the scale on the barrel of the dioptometer. Several repeat readings in both directions should be made to detemnine conformance to requirements specified in 3.7.10.

4.7 Operability.

4.7.1 Boresight knob travel. - Perform this test with the telescope exposed to the temperatures specified in 3.3. Repeat the tests specified in 3.7.2 as outlined in 4.6.4.1 and 4.6.4.2. With the azimuth and elevation knobs set on zero, observe the position of the boresight cross image with respect to the target image. Rotate the boresight azimuth knob in both clockwise and counterclockwise directions while sighting through the eye-piece. The image shall move horizontally 10 mils on either side of the zero setting. Rotate the elevation knob and observe the movement of the image. The image shall elevate and depress vertically 10 mils on either side of the zero setting.

4.7.2 Reticle rotation. - View through the eyepiece and using the level vial reticle adjustment knob and boresight knobs, aline the bore-sight cross with the reference lines of the target collimator projector. Position the adjustment knob to indicate zero cant position. Rotate the knob from zero position 300 mils in each direction while observing the position of the boresight cross with respect to the target. The line of sight of the telescope shall not exceed the tolerance specified in 3.8.2.

4.7.3 Reticle rotation knob. - The torque shall be applied to the knob by means of a torque wrench and an adapter. The running torque required to rotate the knob shall be within the limits specified in 3.8.2. This test shall be performed at temperatures specified in 3.3 and 3.5.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:00Z
Check the source to verify that this is the current version before use.

4.7.4 Boreshght knobs. - The torque shall be applied to boresight knobs, with locks fully released, by means of a torque wrench and an adapter. The torque required to rotate each knob shall be within the limits specified in 3.8.4. This test shall be performed at temperatures specified in 3.2 and 3.5.2.

4.7.5 Illumination. - Apply the voltage specified in 3.9 to the reticle lamp. The reticle markings shall appear clearly defined and easily read when viewed through the telescope eyepiece. Apply the voltage to the level vial lamp. The reflected image of the level bubble and graduations shall appear sharply defined.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing and marking. - Packaging, packing and marking shall be in accordance with MIL-P-14232 and Packaging Data Sheet PDS8206215 or PDS8242617. The level of protection shall be as specified in the procurement document.

6. NOTES

6.1 Intended use. - The Elbow Telescope M99 is intended for use as a direct fire telescope on the 155MM Gun M53. The M99C is intended for use as a direct fire telescope on the 8in. Howitzer M55.

6.2 Field of view. - Rotation of one boresight knob moves the image relative to the reticle in a generally horizontal direction. Rotation of the other boresight knob moves the image in a generally vertical direction. Due to the mechanical arrangement of the boresight mechanism, image movement resulting from operation of each knob will have both a horizontal and verttical component. Operation of one knob results in a large horizontal component and a small vertical component of movement while operation of the other knob results in a large vertical and small horizontal component.

6.3 Ordering data. - Procurement documents should specify the following:

a. Title, number and date of this specification.
b. Selection of applicable levels of preservation, packaging and packing.
c. Applicable stock number.

Custodian:

Army - MU

Preparing activity:

Army-MU

Project No. 1240-A034

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:00Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

Frankford Arsenal
Philadelphia, Pa. 19137

OFFICIAL BUSINESS

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-M1100
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:00Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:00Z
Check the source to verify that this is the current version before use.

NOTICE
OF VALIDATICN

MIL-T-60834 (AR)
NOTICE 1
16 MAY 1988

MILITARY SPECIFICATICN

TELESCOPE, ELBOW, M99 AND M99C

MIL-T-60834 (AR), dated 3 November 1967, has been reviewed and determined to be valid for use in acquisition.

Prepaing activity:
Army - AR

AMSC N/A FSC 1240

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:00Z
Check the source to verify that this is the current version before use.