
INCH-POUND
MIL-DTL-9395/10H
12 August 2024
SUPERSEDING
MIL-DTL-9395/10G
24 September 2018

DETAIL SPECIFICATION SHEET

SWITCHES, PRESSURE, (GAGE), TYPE II

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the switches described herein shall consist of this document and MIL-DTL-9395.




Configuration 1

FIGURE 1. Switches.

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

FSC 5930

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:13Z
Check the source to verify that this is the current version before use.









CONFIGURATION	ELECTRICAL CONNECTOR TO MATE WITH	SCHEMATIC	KEY LOCATION (VIEW LOOKING INTO CONNECTOR)
2	AMPHENOL 115-5035 OR EQUIL		
5	MS3106R-10SL-3S		
6	AMPHENOL 115-5035 OR EQUIV		
7	MS3106R-10SL-3S		

FIGURE 1. Switches - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:13Z
Check the source to verify that this is the current version before use.



Configuration 3

NOTES:
1. Dimensions are in inches.
2. Unless otherwise specified, tolerances are XX ±.03 and XXX ±.010.
3. All "O" ring grooves 32 rms maximum surface finish.
4. Contour of switches optional provided maximum dimensions specified are not exceeded.
5 MS3106-10SL-35 details are found in SAE-AS31061 and MS3108-10SK-3S details are found SAE-AS31081

FIGURE 1. Switches - Continued.

REQUIREMENTS:

Dimensions and electrical schematic: See figure 1.

Weight (maximum):

.7 lb (configuration 1).
.2 lb (configuration 2, 3, 5, 6, 7).

Proof pressure: 800 lb_f/in^2.

System pressure: 500 lb_f/in^2.

Burst pressure: 1,200 lb_f/in^2.

Dead band: 25 lb_f/in^2.

Electrical ratings:

Operating voltage - 28 V dc.
Current rating - 10 amperes inductive (configuration 1) or 2 amperes inductive (configuration 2, 3, 5, 6, 7).
5 amperes lamp load (configuration 1).
10 amperes resistive (configuration 1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:13Z
Check the source to verify that this is the current version before use.

Seal:

Electrical chamber: Watertight.
Pressure chamber: Watertight.
Reference chamber: Watertight.

Electrical connector, electrical connector mating, and key location: See figure 1.

Pressure port: See figure 1.

Media: Oil IAW MIL-PRF-7808.

High temperature (operating): B (+275°F) for configuration 1; or C (+350°F) for configuration 2, 3, 5, 6, 7.

Low temperature (operating and nonoperating): D (-65°F).

Altitude: D (100,000 feet).

Shock: A (50 G).

Vibration: S (test condition D, of MIL-STD-202-204, except 10 - 2000 Hz, 40 G).

Life (mechanical): A (100,000 cycles).

Life (electrical): C (50,000 cycles).

Acceleration: C (8 G) for configuration 1; or D (12 G) for configuration 2, 3, 5, 6, 7.

Pulsation amplitude: E (10 percent) for configuration 1; or 50 percent of system pressure for configuration 2, 3, 5, 6, 7.

Pulsation frequency: C (200 ±20 Hz) for configuration 1; or D (500 ±50 Hz) for configuration 2, 3, 5, 6, 7.

Pulsation rise: E (250,000 lb_f/in^2/sec) for configuration 1 or G (1,000,000 lb_f/in^2/sec for configuration 2, 3, 5, 6, 7.

Connector torque: Applicable (15 ft lb - both directions).

QUALIFICATION:

Single submission: Restricted to switch submitted.
Group submission: See table IV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:13Z
Check the source to verify that this is the current version before use.

PART NUMBER: The part number shall consist of the prefix "M9395/10-" followed in turn by a character from table I, a character from table II and a character from table III denoting the high pressure setting, and a character from table II and a character from table III denoting the low pressure setting. Part number M9395/10-AJKGE identifies a pressure switch of configuration 1 which actuates at 85 ±20 lb_f/in^2, and deactuates at 60±10 lb_f/in^2.

EXAMPLE:




TABLE I. Code character for combination of configuration and setting mode.

	Code character Pressure setting mode		
Configuration	High pressure: At Low pressure: At	High pressure: At Low pressure: Differential	High pressure: Differential Low pressure: At
1	A	B	C
2	D	E	F
3	G	H	J
4 (unused)	---	---	---
5	K	L	M
6	N	P	Q
7	R	S	T

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:13Z
Check the source to verify that this is the current version before use.

TABLE II. Code character for coarse pressure setting (within 10 lb_f/in^2).

Code character	Coarse Setting (lb_f/in^2)	Code character	Coarse Setting (lb_f/in^2)	Code character	Coarse Setting (lb_f/in^2)
A	0	M	110	Y	220
B	10	N	120	Z	230
C	20	P	130	1	240
D	30	Q	140	2	250
E	40	R	150	3	260
F	50	S	160	4	270
G	60	T	170	5	280
H	70	U	180	6	290
J	80	V	190	7	300
K	90	W	200		
L	100	X	210		

TABLE III. Code character for combination of fine pressure setting addition and tolerance.

Fine pressure setting (to be added to coarse pressure setting) (lb_f/in^2)	Code character												
	Tolerance (lb_f/in^2)												
	Min	±5	±10	±15	±20	±25	±30	±40	±50	±60	±80	±100	Max
0	A	C	E	G	J	L	N	Q	S	U	W	Y	1
5	B	D	F	H	K	M	P	R	T	V	X	Z	2

TABLE IV. Extent of qualification.

Part number	Number of samples required	Tests	Qualifies
MS9395/10-AECBC	1 each lamp	Complete per qualification inspection of MIL-DTL-9395	All configurations
MS9395/10-GECBC	1 each inductive		
MS9395/10-A7LYE	1 each inductive		
MS9395/10-G7LYE	1 each inductive		

SUPERSESSION AND USAGE DATA: See table V.

TABLE V. Supersession and usage data.

New part number	Old part number	Used on
MS9395/10-AJKGE	MIL-DTL-9395/10-01	KC-135, B-52F F-101, F-102
MS9395/10-DRIFA	MIL-DTL-9395/10-02	F-4, B-57
MS9395/10-GRIFA	MIL-DTL-9395/10-03	EC/RC 135
MS9395/10-KRIFA	MIL-DTL-9395/10-05	B-52G
MS9395/10-NRIFA	MIL-DTL-9395/10-06	C-141
MS9395/10-RRIFA	MIL-DTL-9395/10-07	C-5A

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:13Z
Check the source to verify that this is the current version before use.

The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Referenced Documents:

- MIL-S-7742
- MIL-PRF-7808
- MIL-DTL-9395
- MIL-PRF-81329
- MIL-STD-202-204
- SAE-AS31061
- SAE-AS31081

Custodians:
- Army - CR
- Navy - EC
- Air Force - 85
- DLA - CC

Review activities:
- Navy - MC, SH

Preparing activity:
- DLA - CC

(Project 5930-2024-048)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:13Z
Check the source to verify that this is the current version before use.