INCH-POUND
MIL-DTL-9395/29E
12 August 2024
SUPERSEDING
MIL-DTL-9395/29D
24 September 2018

DETAIL SPECIFICATION SHEET

SWITCHES, PRESSURE, (DIFFERENTIAL) (TYPE III), 4 AMPERES

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the switches described herein shall consist of this document and MIL-DTL-9395.





FIGURE 1. Dimensions and configurations.


Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:15Z
Check the source to verify that this is the current version before use.



Configuration 2

FIGURE 1. Dimensions and configurations. - continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:15Z
Check the source to verify that this is the current version before use.



NOTES:
1. Dimensions are in inches.
2. DELETED
3. Unless otherwise specified, tolerance is ±.005.
4. A minimum of two wrench flats is needed.
5. Ports permanently marked as shown.
6. MS33656-4 details are found in SAE-AS4395.

Configuration 3

FIGURE 1. Dimensions and configurations. - continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:15Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions, weight and electrical schematic: See figure 1.

Calibration: See tables I, II, III, and IV.

Proof pressure: 250 psig high over low and simultaneously.

System pressure: 125 psig high over low and simultaneously.

Burst pressure: 500 psig high over low and simultaneously.

Electrical ratings:
Operating voltage: 28 V dc.
Current rating: 4 amperes resistive.
2 amperes inductive.

Seal:
High pressure chamber: Media proof. During this test the low pressure chamber shall be open to atmosphere. Subject switches to proof pressure for 2 minutes using a hydraulic fluid per MIL-PRF-6083 with chamber pressure continuously being monitored. Isolate the chamber at proof with the chamber disconnected from the pressure source. Under that condition, the pressure shall not drop more than 1 psig for the first 30 seconds to allow stabilization of test equipment; no pressure loss is allowed thereafter.

Low pressure chamber: Media proof. Test as above except low pressure port is connected to high pressure port.
Electrical chamber: See table I.

Electrical connector: See figure 1.

Pressure port: See figure 1.

Media: Dry air; nitrogen; fuel IAW MIL-DTL-5624; oil IAW MIL-PRF-7808; or hydraulic fluid IAW MIL-PRF-6083.

High temperature (operating and nonoperating): D (-65°F).

Altitude: D (100,000 feet).

Shock: C (100 G).

Vibration: S (test condition D of MIL-STD-202-204).

Life mechanical: A (100,000 cycles).

Life electrical: C (50,000 cycles).

Acceleration: C (8 G).

Pulsation amplitude: A (0%).

Pulsation frequency: A (0 Hz).

Pressure surge: B (more than 1,000 psi/sec).

Dielectric withstanding voltage (at reduced barometric pressure): Applicable.

Connector torque: Applicable.

Flame test: Applicable.

Explosion: Applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:15Z
Check the source to verify that this is the current version before use.

QUALIFICATION:

Single submission: Restricted to switch submitted.
Group submission: See table V.

PART NUMBER: Consists of "M" prefix followed by specification sheet number; a dash (-); and a five-letter code. The five-letter code identifies the configuration and pressure setting mode (code from table I); high-pressure setting (coarse value code from table II) followed by fine value with applicable tolerance (code from table III); and low-pressure setting (coarse value code from table II) followed by fine value with applicable tolerance (code from table III). The five-letter code used in the following example identifies a switch of configuration 1 which actuates on increasing pressure at 1.5 ±.5 psid, and deactuates on decreasing pressure at .5 ±.5 psid.

EXAMPLE:

M9395/29- A A D A B

"M" PREFIX AND SPECIFICATION SHEET NUMBER

CONFIGURATION AND PRESSURE SETTING MODE= Code "A" of table I.

HIGH-PRESSURE SETTING = Code "A" of table II (coarse value of 0 psid) and Code "D" of table III (fine value of 1½ ±½ psid).

LOW-PRESSURE SETTING = Code "A" of table II (coarse value of 0 psid) and Code "B" of table III (fine value of .5 ±.5 psid).

NOTE: Design limitations (actuation values and tolerances, deadband and deactuation values and tolerances) should be coordinated with manufacturer(s) listed on the QPL for this specification sheet before specifying a particular "M" number. The fact that operating characteristics can be coded does not necessarily mean that it can be manufactured or acquired.

TABLE I. Codes for combinations of configurations and pressure setting modes.

	Configuration 1		Configuration 2		Configuration 3		Pressure setting mode	
	Electrical chamber		Electrical chamber		Electrical chamber		High	Low
	Hermetic	Unsealed	Hermetic	Unsealed	Hermetic	Unsealed	setting	setting
Code	A	D	G	K	N	R	At (or max) 1/	At (or min) 1/
Code	B	E	H	L	P	S	At (or max) 1/	Differential 2/
Code	C	F	J	M	Q	T	Differential 2/	At (or min) 1/

1/ Setting values are designated by codes from table II and III.
2/ Setting values are designated by codes from table IV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:15Z
Check the source to verify that this is the current version before use.

TABLE II. Codes for coarse settings.

Code	Coarse value (in psid)	Code	Coarse value (in psid)	Code	Coarse value (in psid)
A	0	L	30	W	80
B	2.5	M	35	X	85
C	5	N	40	Y	90
D	7½	P	45	Z	95
E	10	Q	50	1	100
F	12.5	R	55	2	105
G	15	S	60	3	110
H	17.5	T	65	4	115
J	20	U	70	5	120
K	25	V	75	6	125

TABLE III. Codes for combinations of fine settings and tolerance values.

	Fine value (in psid) for settings below 20 psid					Tolerance
	0	.5	1	1.5	2	
Code	A	B	C	D	E	±.5 psid
Code	F	G	H	J	K	±1 psid
Code	L	M	N	P	Q	±2 psid
Code	R	S	T	U	V	±3 psid
Code	W	X	Y	Z	1	±5 psid
Code	2	3	4	5	6	±8 psid
Code	7	8	9	0	I	Min or Max
	Fine value (in psid) for settings of 20 psid and above					Tolerance
	0	1	2	3	4	
Code	A	B	C	D	E	±1 psid 1/
Code	F	G	H	J	K	±2 psid 2/
Code	L	M	N	P	Q	±3 psid 3/
Code	R	S	T	U	V	±5 psid
Code	W	X	Y	Z	1	±8 psid
Code	2	3	4	5	6	±15 psid
Code	7	8	9	0	I	Min or Max

1/ Not applicable for pressure settings above 33 psid.
2/ Not applicable for pressure settings above 66 psid.
3/ Not applicable for pressure settings above 100 psid.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:15Z
Check the source to verify that this is the current version before use.

TABLE IV. Codes for differential settings.

Code	Differential value (in psid)	Code	Differential value (in psid)
A	0	T	11
B	.5	U	12
C	1	V	13
D	1.5	W	14
E	2	X	15
F	2.5	Y	16
G	3	Z	18
H	3.5	1	20
J	4	2	22
K	4.5	3	24
L	5	4	26
M	5.5	5	28
N	6	6	30
P	7	7	35
Q	8	8	40
R	9	9	45
S	10	0	50

TABLE V. Extent of qualification.

Part number	No. of samples required	Tests	Qualifies
M9395/29-ABAAC -GBAAC -A6R3S -N6R3S	2 each resistive 2 each resistive 2 each inductive 2 each inductive	Complete IAW qualification inspection of MIL-DTL-9395	ALL

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:15Z
Check the source to verify that this is the current version before use.

The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Referenced Documents:

MIL-DTL-5624
MIL-PRF-6083
MIL-PRF-7808
MIL-DTL-9395
MIL-STD-202-204
MS3476
SAE-AS4395

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing Activity:
DLA - CC

(Project 5930-2024-051)

Review Activities:
Army - AT
Navy - AS, MC, SH
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:15Z
Check the source to verify that this is the current version before use.