MILITARY SPECIFICATION

DISCHARGERS, ELECTROSTATIC

GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-D-9129D, dated 30 September 1986, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

3.6.6, delete and substitute:

"3.6.6 Direct current resistance. The resistance of dischargers measured from discharge points to discharger mounting base shall be at 25°C (see 4.7.4).

a. Trailing edge mounted = 6 to 200 megohms.

b. Tip mounted = 6 to 120 megohms.

c. Resistance shall be measured with a 500 volt minimum megohmmeter."

PAGE 9

TABLE III, delete and substitute:

"TABLE III. Group B inspection.

Inspection	Requirement paragraph	Test method paragraph
(4 sample units)		
Direct current resistance	3.6.6	4.7.4
High discharge current	3.6.4	4.7.2.4
Discharge current	3.6.1	4.7.2.1
Radio frequency discharge noise	3.6.2	4.7.2.2

"

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:58Z
Check the source to verify that this is the current version before use.

4.6.3.1.2, delete and substitute:

"4.6.3.1.2 Failures. If one or more sample units fails to pass group C inspections, the sample lot shall be considered to have failed. In that event the cognizant inspection activity and the qualifying activity shall be notified immediately (see 4.4.4)."

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - AS
Air Force - 85

Review activities:
Army - CE, MI
Air Force - 17, 99
DLA - ES

User activities:
Navy - MC
Air Force - 14, 19

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5920-0462)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:58Z
Check the source to verify that this is the current version before use.