
MILITARY SPECIFICATION SHEET


DISCHARGER, ELECTROSTATIC, WING TIP,
NON-INTEGRAL BASE, GREATER THAN 600 KNOTS

This specification is approved for use by all Departments and Agencies of the Department of Defense.


The requirements for acquiring the dischargers described herein shall consist of this specification and the latest issue of MIL-D-9129.



CONFIGURATION A



CONFIGURATION B



CONFIGURATION C

FIGURE 1. Dimensions and configurations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:59Z
Check the source to verify that this is the current version before use.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Part number M9129/08- 2/	Overall length max A	Length of holder max B	Thread length min D	Thread size E	Dia max H	Bracket width max J	Length of discharge area max K	Dia of body or sleeve max L	Height on angle type dischargers max M	Configuration	Holder 1/ figure from MIL-D-9129/9 see note 5
01--	5 0	1.62	-	-	-	.53	1.35	.42	3.2	A	10
02--	3.80	1.50	.31	.25-28	.35	-	.75	.29	-	B	N/A
03--	4.70	2.10	.45	.25-28	.35	-	.75	28	-	C	9

1/ For applications requiring lightning survivability, only holder 10 shall be used with the appropriate P type discharger.
2/ Part numbers shall include additional symbols to indicate magnetism and lightning survivability (See part number example)

Inches	mm	Inches	mm
.005	0.13	.625	15.88
.25	6.4	.75	19.1
.28	7.1	1.35	34.1
.31	7.9	1.50	38.1
.35	8.9	1.62	41.2
.42	10.5	2.10	53.34
.45	11.4	3.80	96.5
.53	13.5	4.70	119.4
		5.00	127.00

NOTES
1. Dimensions are in inches.
2 Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ±.02 (0.51 mm) for two place decimals and ± 010 (0 25 mm) for three place decimals.
4. An international orange band, .625 ±.25 (15.88 ±6.4 mm) inches long, shall encircle diameter L to visually indicate the tip fail point dimensioned by K.
5. Dischargers must interface with holder shown in this column.

FIGURE 1 Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:59Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Design and construction See figure 1.

Weight (in grams): 20 grams maximum.

Magnetism Nonmagnetic dischargers shall be designated with "A", and magnetic dischargers shall be designated with "M".

Lightning survivability. Electrostatic dischargers with lightning survivability characteristics shall be designated "P", and dischargers without lightning survivability characteristics shall be designated "U".

Part number (example)	M9129/08-	01	M	P
Military designator and specification number				
Physical dimensions (see figure 1)				
Magnetism				
Lightning survivability				

Revision letters are not used to denote changes due to the extensiveness of the changes.

Custodians:
Army - ER
Navy - AS
Air Force - 85

Review activities
Army - CE, MI
Air Force - 11, 17, 99

User activities
Navy - MC
Air Force - 14, 19

Preparing activity
Air Force - 85

Agent
DLA - ES

(Project 5920-0409-8)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:59Z
Check the source to verify that this is the current version before use.