MIL-T-9146A(USAF)
2 September 1954
Superseding:
MIL-T-9146(USAF)
20 November 1953

MILITARY SPECIFICATION

TRANSMITTER, TRUE HEADING, BOMBING NAVIGATIONAL COMPUTER, TYPE B-1

1. SCOPE

1.1 This specification establishes the requirements for one type of True Heading Transmitter, designated as Type B-1.

2. APPLICABLE SPECIFICATIONS, STANDARDS, AND DRAWINGS

2.1 The following specification, standard, and drawing, of the issue in effect on the date of invitation for bids, shall form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-B-5935	Bombing Navigational Systems, Type K-Series, General Specification For

STANDARDS

Military

MIL-STD-129	Marking of Shipments

DRAWINGS

Sperry Gyroscope Company

662219	Transmitter, True Heading, B.N.C., Type B-1

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General.- The requirements of Specification MIL-B-5935 shall be applicable as general requirements of this specification.

3.1.1 Where the requirements of Specification MIL-B-5935 and this specification conflict, the requirements of this specification shall govern.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:00Z
Check the source to verify that this is the current version before use.

3.2 Design.- The Type B-1 True Heading Transmitter shall consist of the necessary mechanism for integrating the inputs of magnetic heading and magnetic variation, and producing output selsyn signals of true heading when used in conjunction with a periscopic stabilizer of the applicable system.

3.3 Construction.- The transmitter shall be constructed so as to conform to the dimensions and configuration shown on Sperry Drawing No. 662219. Housing required for this unit, shall mount electrical connectors and contain the necessary sub-assemblies to provide heading information to the rest of the system.

3.4 Electrical Requirements.- The electrical characteristics of the true heading transmitter shall be such that it operates on the following primary voltages:

115 ±5 volts, 380 to 420 cycles regulated A.C.
27.5 ±1.5 volts D.C.
+300 ±15 volts D.C.

3.5 Weight.- The total weight of the true heading transmitter shall not exceed 19.5 pounds.

3.6 Identification of Product.- The specific identification data applied to the transmitter shall be as follows:

Transmitter: True Heading
Type B-1
Bombing Navigational Computer
Specification MIL-T-9146
Stock No. *
Mfr's Part No. *
Serial No. *
Contract or Order No. *
(Mfr's Name or Trademark)
U.S. Property

* Applicable data to be entered by the contractor.

4. SAMPLING, INSPECTION AND TEST PROCEDURES

4.1 General.- The true heading transmitter shall be subjected to sampling, inspection, and tests as specified in Specification MIL-B-5935 and herein.

4.2 Preproduction Tests.- One true heading transmitter will be required as preproduction sample and subjected to the Preproduction Tests.

4.3 Inspection Tests:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:00Z
Check the source to verify that this is the current version before use.

4.3.1 Individual Tests.- Each true heading transmitter shall be subjected to the following tests:

4.3.1.1 Bench Functional Tests:

4.3.1.1.1 Each true heading transmitter shall have a complete continuity test conducted on it to determine that all interconnecting wiring is correct.

4.3.1.1.2 Each true heading transmitter shall be interconnected with a complete applicable Bombing Navigational System or suitable simulator and a sufficient number of simulated transmitter problems shall be run to insure that the transmitter is functioning correctly with respect to the overall system or simulator.

4.3.2 Sampling Tests.- One true heading transmitter shall be selected at random from each lot of 100 or 6 months production whichever quantity is greater and subjected to the Sampling Tests. These tests shall be in addition to the individual tests specified herein.

5. PACKAGING, PACKING, AND MARKING FOR SHIPMENT

5.1 Preservation, packaging, and packing requirements shall be as specified in Specification MIL-B-5935.

5.2 Marking of Shipment.- Interior packages and exterior shipping containers shall be marked for shipment in accordance with Standard MIL-STD-129. The nomenclature shall be as follows: Transmitter, True Heading, Bombing Navigational Computer, Type B-1, (*Mfr's Part No.), Specification MIL-T-9146A.

* Applicable data to be entered by the contractor.

5.2.1 Precautionary Marking.- In addition to the above marking, each interior container shall bear the following precautionary marking:

FRAGILE
HANDLE WITH CARE

6. NOTES

6.1 Use.- The true heading transmitter covered by this specification is one component of a bombing navigational computer and automatically integrates magnetic variation and magnetic heading to transmit true heading data to other components of the applicable system.

6.2 Ordering Data.- Invitation for bids, contracts, and purchase orders should state the connections for the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:00Z
Check the source to verify that this is the current version before use.

6.2.1 Preproduction Tests.- It is expected that the contract or purchase order will specify that one true heading transmitter will be required as a preproduction sample and that this preproduction sample will be subjected to the Preproduction Tests to determine compliance with the requirements of the specification. The invitations for bids and the contract should specify the point of inspection for these tests.

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication, or otherwise, as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

JLM/ejb
WCLC

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:00Z
Check the source to verify that this is the current version before use.