[INCH-POUND]
A-A-3030
October 7, 1996
SUPERSEDING
GGG-C-751D
February 1, 1966

COMMERCIAL ITEM DESCRIPTION

CUTTER, GLASS, WHEEL TYPE

The General Services Administration has authorized the use of this Commercial Item Description for procurement of Type I, Classes 1 and 3 glass cutters, specified in GGG-C-751 for all federal agencies.

1. SCOPE.

1.1 Scope. This Commercial Item Description covers single-fixed wheel and turret head glass cutter.

1.2 Intended use. The glass cutter is used for cutting glass.

2. CLASSIFICATION.

2.1 Classification. The glass cutters covered by this Commercial Item Description shall be of the following classes:

Class 1 - Single Fixed Wheel
Class 2 - Turret Head

3. SALIENT CHARACTERISTICS.

3.1 Illustration. Except for the technical requirements (e.g., design, dimensions), the illustration herein is descriptive and is not intended to preclude the purchase of items otherwise conforming to the requirements of this document.

3.2 Class 1, single-fixed wheel glass cutter. The class 1 single-fixed wheel glass cutter consists of a handle, head, cutting wheel, and axle. The turret head glass cutter consists of a handle, head, cutting wheel, and axle. The overall length of the glass cutter shall be not less than 5 inches. The glass cutter shall be similar to Figure 1.



Figure 1. Cutter, glass, single-fixed, wheel.

3.2.1 Handle. The handle shall be of high grade metal formed integral with the head. The flat portion of the handle adjacent to the head shall be between 7/16 and 9/16 in width to provide a comfortable rest for the finger. The smallest portion of the straight or tapered handle glass cutter shall be not less than 1/8 inch in diameter. Handle ends shall be furnished straight, tapered or ball shaped at the option of the manufacturer. The handle shall have a suitable corrosion-resistant coating of paint, enamel, or lacquer, or nickel plating.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any other data which may improve this document should be sent to: General Services Administration, Federal Supply Service, Tools and Appliances Commodity Center, Kansas City, MO 64131.

Distribution Statement A. Approved for public release; distribution is unlimited. FSC 5110

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

3.2.2 Head. The head shall be of metal and have three grips or breaker notches. Advancing from the cutting end of the head, each of the grips or notches shall have an approximate width of 1/8, 5/32, and 3/16 inch, ± 1/64 inch, respectively and a depth of 7/32 inch, ± 1/4 inch. The corners and edges of the grips and notches shall have not more than a 1/64 inch radius. The edges and outer corners of the head shall be beveled or slightly rounded to prevent abrasion of straight edges, rules, or similar cutter guides.

3.2.3 Cutting wheel. The cutting wheel shall be of hardened tool steel capable of cutting ordinary glass. The wheel shall be between 5/32 and 1/4 inch in diameter and shall rotate freely without binding on the axle or head.

3.2.4 Axle. The axle shall be of steel or bronze and be of uniform quality as to insure proper and efficient operation of the cutter throughout the useful life of the cutting wheel. The axle shall be securely retained in the head to prevent it from falling out.

3.2.5 Coating. Cutting wheels, axles, and other metal surfaces having a ground, buffed, or polished finish shall be coated with oil or grease in order to provide adequate rust prevention.

3.3 Class 2, turret head glass cutter. The class 2 turret head glass cutter shall consist of a handle, head, turret, cutting wheels, and axles, and/or ferrule shall be similar to Figure 2. The overall length of the glass cutter shall be not less than 5 inches.



Figure 2. Cutter, glass, turret head.

3.3.1 Handle. The handle shall be either of high grade material integral with the head or an individual member of wood or other suitable material. If the handle is other than integral construction, a metal ferrule shall be provided at the junction of the handle and the head and secured in such a manner as to prevent the handle from becoming loose. The handle shall be straight, tapered, or provided with a breaker ball at the end. The handle shall have a suitable corrosion-resistant coating of paint, enamel, or lacquer.

3.3.2 Head. The head shall be of metal and have two glass grips or breaker notches having a width of 1/8 ± 3/64 and 7/32 inch ± 3/64 inch and a depth of 7/32 inch, ± 1/4 inch.

3.3.3 Turret. The turret shall be of metal with six cutting wheels each mounted on its individual axle. The turret shall be fastened to the head by means of a single countersunk slotted head retaining screw. When in the tightened position, the head of the screw shall not protrude above the face of the turret head. Changing the cutter wheels shall be accomplished by loosening the retainer screw and revolving the turret. The turret shall be securely locked or clamped in any position by tightening the retaining screw. Numbers 1 to 6 shall be engraved or stamped on the exposed face of the turret with each number appearing opposite a cutting wheel. An alternative design turret may be brass with hardened steel ball axles 1/16-inch diameter.

3.3.4 Cutting wheels. Cutting wheels shall be of hardened tool steel capable of cutting ordinary glass. Cutting wheels shall be not less than 5/32 inch in diameter and means provided for their removal and replacement without damage to the turret.

3.3.5 Axles. The axles shall be of steel or bronze, be of uniform quality, and secured in such a manner as to prevent their loss and permit their removal without damage to the turret. The axles may be of die-cast zinc when used as an integral part of the turret.

3.3.6 Coating. All unpainted surfaces shall be coated with oil or grease in order to provide adequate rust prevention. The frame and ferrule may be nickel plated, nickel or chrome plated.

3.4 Performance. The glass cutter shall show no sign of axle wear or malfunction when it is subjected to 100 6-inch strokes applied with a vertical pressure of not less than 8 pounds on a sheet of clear unpolished, double-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

strength glass. The cutting wheel bearing shall show no wear of malfunction in the same groove for not more than 20 strokes. At the end of 100 strokes, the glass cutter shall cut, by hand, using an approximate pressure of 10 pounds, a clean continuous cut to determine if failure of the cutting wheel has occurred. When cutters are furnished with more than one wheel, only one wheel and its axles need to be subjected to this test. Cutting wheels shall be lubricated at the beginning of the test.

3.5 Identification marking. The glass cutter shall be marked with the manufacturer's name or identifying symbol and the state or country of manufacture, unless otherwise specified. All identification markings shall be engraved, etched, molded, or indented directly on the item's surface in such a manner that it remains clearly legible throughout the life of the item.

3.6 Workmanship. Details of workmanship shall be in accordance with the best commercial practice. Paints, coatings, platings, and finishes shall be smooth, adherent, continuous, and not stained or discolored. External surfaces shall be free of tool and gouge marks, nicks, or other surface imperfections. The item shall be free from manufacturing workmanship defects (e.g., sharp or rough external edges, corners, or surfaces) and material workmanship defects (e.g., pits, rips, fins, burrs, tears, nodules, cracks, blisters) which may adversely impact the item's serviceability, durability, safety, or appearance.

4. REGULATORY REQUIREMENTS.

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.2 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified (using conversion tables contained in the latest revision of Federal Standard 376) and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

5. QUALITY ASSURANCE PROVISIONS.

5.1 Product conformance. The product provided to the Government shall conform to the contractually specified requirements. For product characteristics and requirements which are not contractually specified, the provided product shall conform to the producer's own drawings, standards, specifications, and quality assurance practices for the highest quality product commercially offered by the producer. If the product is not commercially offered by the producer, the best commercial practices shall apply. The Government reserves the right to require proof of such conformances prior to first delivery and thereafter as provided for under the provisions of the contract.

5.2 Responsibility for inspection. Unless otherwise specified, the contractor is responsible for the performance of all inspection requirements and may use any commercial facilities (including the contractor's own facilities) suitable for performance of the inspection requirements, unless disapproved by the Government. The Government reserves the right to perform any inspections deemed necessary to assure the item conforms to the specified requirements.

5.3 Bid sample(s). When a bid sample requirement is specified in the solicitation, the bid sample(s) shall be inspected for all salient characteristics by the Government. A failure of any bid sample to meet the salient characteristics shall be cause for rejection.

5.4 First article sample(s). When a first article requirement is specified in the contract, the first article sample(s) shall be inspected for all salient characteristics. A failure of any first article sample to meet the salient characteristics shall be cause for rejection.

6. PACKAGING.

6.1 Packaging. Requirements of preservation, packing, packaging, and marking of packages shall be as specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

7. NOTES.

(This section contains information of a general or explanatory nature that is not mandatory.)

7.1 Addresses for obtaining copies of referenced documents:

Federal Specifications and Standards: Federal Supply Service Bureau, Specification Section, Suite 8100, 470 L'Enfant Plaza, SW, Washington, DC 20407.

Federal Acquisition Regulations (FAR): Government Printing Office, Superintendent of Documents, Washington, DC 20402-9371.

ANSI/ASQC Z1.4: American Society for Quality Control, P.O. Box 3005, 611 East Wisconsin Avenue, Milwaukee, WI 43201-4606.

7.2 Ordering data. Purchasers should select the preferred options permitted herein and should include the following information in procurement documents:

(a) Title, number, and date of this Commercial Item Description.
(b) When applicable, the appropriate NSN(s).
(c) When applicable, the specific classes, as specified in the Commercial Item Description.
(d) If bid samples are required, the number of samples required, and the subjective inspection requirements.
(e) If first article samples are required and the number of samples required.
(f) If lot sampling inspection is required and the applicable lot sampling requirements.

For example:

Sampling for inspection. Sampling for inspection (both examinations and testing) shall be in accordance with ANSI/ASQC Z1.4.

Inspection. Each sample tool shall be examined and tested for all salient characteristics. The Inspection Level shall be Level II with an Acceptable Quality Level of 4.0, expressed in terms of defects per hundred units.

Testing. Each sample shall be tested for all salient characteristics. The Inspection Level shall be S-2, with an Acceptable Quality Level (AQL) of 1.0, expressed in terms of defects per hundred units.

(g) What preservation, packing, packaging, and marking of packages are required.

7.3 National Stock Numbers (NSNs). The following list of NSNs corresponds to the classes specified in this CID. This list may not be indicative of all possible NSNs associated with this CID.

NSN	TYPE
5110-00-222-4400	Single, fixed wheel
5110-00-222-4401	Turret, head, six wheels

MILITARY INTERESTS:

NONE: DoD has no registered interest in revisions or notices to this Commercial Item Description until further notice.

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.