NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/200B
26 October 1998
SUPERSEDING
MIL-DTL-11484/200A
27 September 1996

DETAIL SPECIFICATION SHEET

# LAPEL BUTTON, MERITORIOUS CIVILIAN SERVICE AWARD, DEFENSE LOGISTICS AGENCY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-11484 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.



MATERIAL: Red Brass

FINISH:

BASE: Gold Plated, Rose Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 20.
DEVICE: Nickel Plated, Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.

DIMENSIONS:

DIAMETER: 9/16 inch (1.43 cm) (REF)

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.


Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:20Z
Check the source to verify that this is the current version before use.

THICKNESS:
BASE (Over Arrows): 0.050 inch ± 0.005 inch (0.127 cm ± 0.012 cm)
DEVICE (Wing Tips): 0.040 inch ± 0.005 inch (0.102 cm ± 0.012 cm)
ASSEMBLED THICKNESS (Eagle's Breast): 0.100 inch ± 0.005 inch (0.254 cm ± 0.012 cm)

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Lapel button shall be lacquered.

3. Attaching device shall be prong with pick and flat ball clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0959)


Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:20Z
Check the source to verify that this is the current version before use.