NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/202B
4 March 1999
SUPERSEDING
MIL-DTL-11484/202A
27 September 1996

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, DISTINGUISHED CAREER SERVICE AWARD, DEFENSE LOGISTICS AGENCY

Inactive for new design after 20 January 1999.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-11484 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.



MATERIAL: Red Brass

FINISH: (Base and Device): Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 4.

DIMENSIONS:

DIAMETER: 9/16 inch (1.43 cm) (REF)

THICKNESS:
BASE (Over Arrows): 0.050 inch ± 0.005 inch
DEVICE (Wing Tips): 0.040 inch ± 0.005 inch
ASSEMBLED THICKNESS (Eagle's Breast): 0.100 inch ± 0.005 inch

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:21Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Attaching device shall be prong with pick and flat ball clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0969)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:21Z
Check the source to verify that this is the current version before use.