INCH-POUND

MIL-DTL-11484/202C
19 October 2015
SUPERSEDING
MIL-DTL-11484/200B
4 March 1999

DETAIL SPECIFICATION SHEET

# LAPEL BUTTON, DISTINGUISHED CAREER SERVICE AWARD, DEFENSE LOGISTICS AGENCY

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-11484.



MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: BASE AND DEVICE: Brass, Oxidized, Buffed Relieved, and shall match The Institute of Heraldry Metal Finish Chip Number 4.

DIMENSIONS:
HEIGHT:
BASE: 9/16 inch (REF)
DEVICE: 15/32 inch (REF)
WIDTH:
BASE: 27/64 inch (REF)
DEVICE: 13/32 inch (REF)
THICKNESS:
BASE (at thickest point, horizontal arrows): 0.050 inch ± 0.005 inch
DEVICE (at wing tips): 0.040 inch ± 0.005 inch
ASSEMBLED (at eagle's breast): 0.100 inch ± 0.005 inch



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:21Z
Check the source to verify that this is the current version before use.

ATTACHING DEVICE:

1. Attaching device shall be prong with pick and flat ball clutch.

2. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Lapel button shall be lacquered.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2015-616)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.


Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:21Z
Check the source to verify that this is the current version before use.