MIL-C-426B
23 February 1968
SUPERSEDING
MIL-C-426A
11 October 1954

MILITARY SPECIFICATION

CARRIER, TIMBER, HAND

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers a timber carrier suitable for handling logs and timbers from 3 inches to 16 inches in thickness or diameter.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

FF-B-571	- Bolts, Nuts, Studs, and Tap-Rivets (and Material for Same).
NN-H-93	- Handles, Hickory, Striking-Tool.
QQ-I-666	- Iron Castings, Malleable.
QQ-S-637	- Steel Bar, Carbon, Cold Finished, (Standard Quality, Free Machining).
PPP-T-97	- Tape, Pressure-Sensitive Adhesive, Filament Reinforced.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.

Military

MIL-P-116	- Preservation, Methods of.

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.

FSC 5120

Source: https://assist.dla.mil -- Downloaded: 202640-16T07:24Z
Check the source to verify that this is the current version before use.

MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-130 - Identification Marking of U. S. Military Property.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification Rules.

(Application for copies should be addressed to the Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

AMERICAN TRUCKING ASSOCIATIONS, INC.

National Motor Freight Classification Rules.

(Application for copies should be addressed to the American Trucking Associations, Inc., 1616 P Street NW, Washington, D. C. 20036.)

3. REQUIREMENTS

3.1 Description. The timber carrier shall consist of a pair of hinged lug hooks swivel-connected to a clasp. The clasp shall be mounted on the center of a wood carrying handle. The handle shall be neither cut nor drilled for mounting the clasp. The carrier shall weigh approximately 8-1/2 pounds and shall be suitable for handling timbers from 3 to 16 inches in thickness or diameter.

3.2 Material. Material shall be as specified herein. Material not specified shall be selected by the supplier and shall be subject to all provisions of this specification. Material shall be free from all defects and imperfections that might affect the serviceability of the finished product.

3.3 Lug hooks. Lug hooks shall be fabricated of steel conforming to QQ-S-637, composition and condition optional, and shall be hammer-forged to shape. The points of the hooks shall be chisel-billed, and shall be tempered and ground to give long service.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:24Z
Check the source to verify that this is the current version before use.

3.4 Clasp. The clasp shall be malleable iron casting conforming to QQ-I-666, class C, or a steel forging. The upper side of the clasp shall be provided with lugs, and a bolt conforming to FF-B-571, type C-2, with mating nut and lockwasher, shall be furnished to fit the lugs. The lower side of the clasp shall be provided with a swivel connection for the hinged lug hooks.

3.5 Handle. The hickory handle shall conform to NN-H-93, grade A. The handle shall be circular in cross-section, 48 inches in length, and 2-1/2 inches in diameter at the center. The handle shall be tapered toward each end to a size convenient for a hand hold.

3.6 Identification marking. The carrier shall be identified in accordance with MIL-STD-130.

3.7 Finish and painting. The metal parts shall be finished and painted in accordance with the manufacturer's standard practice.

3.8 Workmanship. All parts, components, and assemblies of the carrier including castings, forgings and machined parts shall be clean and free from sand, dirt, fins, pits, sprues, scale and other harmful extraneous material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection.

4.2.1 Sampling. Sampling for examination and test shall be in accordance with MIL-STD-105, inspection level II. All carriers submitted for acceptance at one time shall be considered a lot. Acceptable Quality Level (AQL) shall be 2.5 percent defective.

4.3 Examination. Samples selected in accordance with 4.2.1 shall be examined for conformance to design, material, finish, construction, workmanship, and marking.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:24Z
Check the source to verify that this is the current version before use.

4.4 Tests. Samples selected in accordance with 4.2.1 shall be able to handle timbers of from 3 to 16 inches in diameter. Inability to handle 3-inch and 16-inch diameter timbers shall be cause for rejection.

4.5 Inspection of preparation for delivery.

4.5.1 Quality conformance inspection of pack.

4.5.1.1 Inspection stages. Inspection shall be in two stages as follows:

(a) The first stage shall include inspection of preservation, packaging, and packing within the shipping container.
(b) The second stage shall include inspection of packing and marking after closing of the container.

4.5.1.2 Unit of product. For the purpose of inspection, a unit of product for the first stage of inspection shall be a pack completely prepared for closing. For the second stage of inspection, a unit of product shall be a completed pack ready for shipment.

4.5.1.3 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.5.1.4 Examination. Samples selected in accordance with 4.4.1.3 shall be examined for the following defects. AQL shall be 2.5 percent defective.

101. Containers or materials not as specified for level A or B. Each incorrect container or material shall constitute one defect.
102. Metal surfaces not coated as specified for level A.
103. Hooks not secured as specified for level A.
104. Gross weight of packed boxes exceeds 200 lbs for level A or B.
105. Marking illegible, incorrect, incomplete or missing.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C, as specified (see 6.2).

5.1.1 Level A. Unpainted metal surfaces of the carrier shall be coated with type P-1 preservative in accordance with MIL-P-116. The hooks shall be fully opened and secured to the handles with a double wrap of pressure-sensitive tape conforming to PPP-T-97.

Source: https://assist.dla.mil -- Downloaded: 202640-16T07:24Z
Check the source to verify that this is the currentversion before use.

5.1.2 Level C. The carriers shall be packaged to afford adequate protection against deterioration and damage from the supplier to the initial destination for immediate use or controlled humidity storage.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. The carriers, preserved and packaged as specified in 5.1, shall be packed in close-fitting boxes conforming to PPP-B-601, overseas type, style optional. Gross weight of packed boxes shall not exceed 200 pounds. Cushioning and blocking shall be provided to prevent damage to the carrier handles. Closure and strapping shall be in accordance with the appendix to the box specification. Strapping shall be zinc coated.

5.2.2 Level B. The carriers, preserved and packaged as specified in 5.1, shall be packed as specified in 5.2.1 for level A, except boxes shall be domestic type and strapping is not required to be zinc coated.

5.2.3 Level C. Carriers preserved and packaged as specified in 5.1 shall be packed to assure carrier acceptance and safe delivery to destination at lowest rates in containers complying with Uniform Freight Classification Rules or National Motor Freight Classification Rules.

5.3 Marking. Marking shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The carrier is intended for use in handling logs and timbers.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Level of preservation and packaging and level of packing required (see 5.1 and 5.2).

Custodians:

Army - ME
Navy - None
Air Force - 84

Review activities:

Air Force - 85, 84

User activities:

Army - CE
Navy - YD

Preparing activity:

Army - ME

Project No. 5120-0524

Source: https://assist.dla.mil -- Downloaded: 202610-16T07:24Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:24Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Mobility Equipment Research & Development Command
ATTN: SMEFB-RDE-KX
Fort Belvoir, VA 22060

Source: https://assist.dla.mil -- Downloaded: 202640-16T07:24Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 202640-16T07:24Z
Check the source to verify that this is the current version before use.