ADOPTION NOTICE

SAE-AS5176 , " FITTING, SLEEVE, FLARED", was adopted on 28 September 1999 for use by the Department of Defense (DoD). Proposed changes by DoD Activities must be submitted to the DoD Adopting Activity: Defense Supply Center, Columbus, DSCC-VAI, 3990 East Broad Street, Columbus, OH 43218-3990 or fluidflow@.dla.mil. Copies of this document are available from the SAE INTERNATIONAL, available online at http://www.sae.org or from the SAE World Headquarters, 400 Commonwealth Drive, Warrendale, PA 15096-0001.

MS20819G for aluminum was canceled on August 16, 2000. Subsequently aluminum was not carried over to SAE-AS5176. See SAE-AS3220 for aluminum application.

SAE-AS5176 (for non- aluminum metals) is a suitable replacement. Table l provides a detailed cross reference of Part or Identifying Numbers (PIN) and replacement SAE- AS5176 PINs. Users are cautioned to evaluate replacements for their particular application.

.

CONCLUDING MATERIAL

Custodians:
Army - AV
Navy - AS
Air Force - 99

Preparing activity:
DLA - CC

(Project 4730-2008-106)

Review activities:
Army - AR
Navy - MC, SA
Air Force - 71

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T16:30Z
Check the source to verify that this is the current version before use.

TABLE I. MS20819G to SAE-AS5176 cross-reference data.

| Canceled MS PIN | Tube Size | Replacement AS PIN | Canceled MS PIN | Tube Size | Replacement AS PIN |
|---|---|---|---|---|---|
| MS20819-2 | .125 | AS5176-02 | MS20819-16 | 1.000 | AS5176-16 |
| MS20819-2B | .125 | AS5176B02 | MS20819-16B | 1.000 | AS5176B16 |
| MS20819-2J | .125 | AS5176J02 | MS20819-16J | 1.000 | AS5176J16 |
| MS20819-2K | .125 | AS5176K02 | MS20819-16K | 1.000 | AS5176K16 |
| N/A | .125 | AS5176R02 | N/A | 1.000 | AS5176R16 |
| N/A | .125 | AS5176T02 | N/A | 1.000 | AS5176T16 |
| MS20819-3 | .188 | AS5176-03 | MS20819-20 | 1.250 | AS5176-20 |
| MS20819-3B | .188 | AS5176B03 | MS20819-20B | 1.250 | AS5176B20 |
| MS20819-3J | .188 | AS5176J03 | MS20819-20J | 1.250 | AS5176J20 |
| MS20819-3K | .188 | AS5176K03 | MS20819-20K | 1.250 | AS5176K20 |
| N/A | .188 | AS5176R03 | N/A | 1.250 | AS5176R20 |
| N/A | .188 | AS5176T03 | N/A | 1.250 | AS5176T20 |
| MS20819-4 | .250 | AS5176-04 | MS20819-24 | 1.500 | AS5176-24 |
| MS20819-4B | .250 | AS5176B04 | MS20819-24B | 1.500 | AS5176B24 |
| MS20819-4J | .250 | AS5176J04 | MS20819-24J | 1.500 | AS5176J24 |
| MS20819-4K | .250 | AS5176K04 | MS20819-24K | 1.500 | AS5176K24 |
| N/A | .250 | AS5176R04 | N/A | 1.500 | AS5176R24 |
| N/A | .250 | AS5176T04 | N/A | 1.500 | AS5176T24 |
| MS20819-5 | .312 | AS5176-05 | MS20819-28 | 1.750 | AS5176-28 |
| MS20819-5B | .312 | AS5176B05 | MS20819-28B | 1.750 | AS5176B28 |
| MS20819-5J | .312 | AS5176J05 | MS20819-28J | 1.750 | AS5176J28 |
| MS20819-5K | .312 | AS5176K05 | MS20819-28K | 1.750 | AS5176K28 |
| N/A | .312 | AS5176R05 | N/A | 1.750 | AS5176R28 |
| N/A | .312 | AS5176T05 | N/A | 1.750 | AS5176T28 |
| MS20819-6 | .375 | AS5176-06 | MS20819-32 | 2.000 | AS5176-32 |
| MS20819-6B | .375 | AS5176B06 | MS20819-32B | 2.000 | AS5176B32 |
| MS20819-6J | .375 | AS5176J06 | MS20819-32J | 2.000 | AS5176J32 |
| MS20819-6K | .375 | AS5176K06 | MS20819-32K | 2.000 | AS5176K32 |
| N/A | .375 | AS5176R06 | N/A | 2.000 | AS5176R32 |
| N/A | .375 | AS5176R06 | N/A | 2.000 | AS5176R32 |
| MS20819-8 | .500 | AS5176-08 | MS20819-40 | 2.500 | AS5176-40 |
| MS20819-8B | .500 | AS5176B08 | MS20819-40B | 2.500 | AS5176B40 |
| MS20819-8J | .500 | AS5176J08 | MS20819-40J | 2.500 | AS5176J40 |
| MS20819-8K | .500 | AS5176K08 | MS20819-40K | 2.500 | AS5176K40 |
| N/A | .500 | AS5176R08 | N/A | 2.500 | AS5176R40 |
| N/A | .500 | AS5176T08 | N/A | 2.500 | AS5176T40 |
| MS20819-10 | .625 | AS5176-10 | MS20819-48 | 3.000 | AS5176-48 |
| MS20819-10B | .625 | AS5176B10 | MS20819-48B | 3.000 | AS5176B48 |
| MS20819-10J | .625 | AS5176J10 | MS20819-48J | 3.000 | AS5176J48 |
| MS20819-10K | .625 | AS5176K10 | MS20819-48K | 3.000 | AS5176K48 |
| N/A | .625 | AS5176R10 | N/A | 3.000 | AS5176R48 |
| N/A | .625 | AS5176T10 | N/A | 3.000 | AS5176T48 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T16:30Z
Check the source to verify that this is the current version before use.

TABLE I. MS20819G to SAE-AS5176 cross-reference data – Continued.

| Canceled MS PIN | Tube Size | Replacement AS PIN |
|---|---|---|
| MS20819-12 | .750 | AS5176-12 |
| MS20819-12B | .750 | AS5176B12 |
| MS20819-12J | .750 | AS5176J12 |
| MS20819-12K | .750 | AS5176K12 |
| N/A | .750 | AS5176R12 |
| N/A | .750 | AS5176T12 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T16:30Z
Check the source to verify that this is the current version before use.