INCH-POUND
MIL-PRF-3098/103F
w/AMENDMENT 1
7 October 2019
SUPERSEDING
MIL-PRF-3098/103F
7 January 2010

PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR101/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-3098.

Pertinent characteristics: 7 MHz to 20 MHz; fundamental; noncontrolled; antiresonance.




FIGURE 1. Crystal unit – CR101/U.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:50Z
Check the source to verify that this is the current version before use.

Ltr	Inches		mm	
	Min	Max	Min	Max
A	---	.420	---	10.67
B	---	.326	---	8.28
C	---	.265	---	6.73
D	.600	---	15.24	---
E	.016	.020	0.41	0.51
F	.192	.208	4.88	5.28

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with MIL-PRF-3098.

FIGURE 1. Crystal unit – CR101/U.

REQUIREMENTS:

Dimensions, marking, and configuration: See figure 1.

Frequency range: 7 MHz to 20.0 MHz, inclusive.

Frequency tolerance: ±50 parts per million (ppm).

Equivalent resistance: 7 MHz to 10 MHz: 30 ohms.

10+ MHz to 20 MHz: 25 ohms.

Antiresonance: load capacitance: 30 pF ±0.5 pF.

Mode of oscillation: Fundamental.

Operating temperature range (noncontrolled): -55°C to +105°C, inclusive.

Rated drive level: 1.0 mW maximum.

Capacitance, shunt: 7 pF, maximum.

Shock (specified pulse):

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:50Z
Check the source to verify that this is the current version before use.

Thermal shock:

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Vibration: MIL-STD-202-204, test condition B.

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Aging:

Frequency change permitted: ±5 ppm.

Part or Identifying Number (PIN): CR101/U (followed by specified frequency), see 1.2 of MIL-PRF-3098.

Reference documents. In addition to MIL-PRF-3098, this document references the following:

MIL-STD-202-204

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Review activities:
Army - AR, MI, SM
Navy - AS, CG, MC, OS, SH
Air Force - 19

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5955-2019-026)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:50Z
Check the source to verify that this is the current version before use.