INCH-POUND
MIL-PRF-3098/106D
w/AMENDMENT 1
24 June 2019
SUPERSEDING
MIL-PRF-3098/106D
7 August 2009

PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR127/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-3098.

Pertinent characteristics: 10 MHz to 61 MHz; third mechanical overtone; noncontrolled; series resonance.




FIGURE 1. Crystal unit - CR127/U.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:51Z
Check the source to verify that this is the current version before use.

Ltr	Inches		mm	
	Min	Max	Min	Max
A	---	.352	---	8.94
B	---	.725	---	18.42
C	.223	.248	5.66	6.30
D	.030	.037	0.76	0.94
E	.460	.476	11.68	12.09
F	---	.757	---	19.23
G	.030	.040	0.76	1.02
H	.015	.025	0.38	0.64
J	---	.317	---	8.05
K	---	.775	---	19.68
L	.015	.025	0.38	0.64
M	.075	.141	1.90	3.58
N	.048	.052	1.22	1.32

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with MIL-PRF-3098.

FIGURE 1. Crystal unit - CR127/U - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:51Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions, marking, and configuration: See figure 1.

Frequency range: 10 MHz to 61 MHz, inclusive.

Capacitance, shunt: 7 pF, maximum.

Frequency tolerance:

Operating temperature range: ±0.0025 percent.

Mode of oscillation: Third mechanical overtone.

Rated drive level: 1.0 mW, maximum.

Resonance: Series.

Operating temperature range (noncontrolled): -55°C to +90°C, inclusive.

Equivalent resistance: 40 ohms, maximum.

Shock:

Frequency change permitted: ±0.0005 percent.

Equivalent-resistance change permitted: ±10 percent.

Vibration: MIL-STD-202-201.

Frequency change permitted: ±0.0005 percent.

Equivalent resistance change permitted: ±10 percent.

Temperature cycling: ±0.0025 percent.

Aging:

Frequency change permitted: ±0.0005 percent.

Reference documents. In addition to MIL-PRF-3098, this document references the following:

MIL-STD-202-201

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:51Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy – EC
Air Force - 84
DLA - CC

Review activities:
Air Force - 19

Preparing activity:
DLA - CC

(Project 5955-2019-004)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:51Z
Check the source to verify that this is the current version before use.