INCH POUND

MIL-C-3098/108B
5 May 1993
SUPERSEDING
MIL-C-3098/108A
2 November 1983


MILITARY SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR128/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirement for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-C-3098.

Pertinent characteristics: 17 to 61 MHz; third mechanical overtone; noncontrolled; series resonance.



INCHES	mm
.002	.05
.008	.20
.017	.43
.150	3.81
.183	4.65
.192	4.88
.402	10.21
.435	11.05
.50	12.7
.530	13.46

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with MIL-C-3098.

FIGURE 1. Crystal unit - CR128/U.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:52Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Holder: HC-18/U (MIL-H-10056/9) or HC-43/U.

Dimensions, marking, and configuration: See figure 1.

Frequency range: 17 to 61 MHz, inclusive.

Capacitance, shunt: 7 pF, maximum.

Mode of oscillation: Third mechanical overtone.

Rated drive level: 2.0 ±0.4 mW.

Resonance: Series.

Operating temperature range (noncontrolled): -55°C to +105°C, inclusive.

Operable temperature range: +105°C to +125°C, inclusive.

Frequency tolerance (operating temperature range): ±50 ppm.

Equivalent resistance: 40 ohms, maximum.

Unwanted modes: Method II.

Shock (specified pulse):

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±15 percent, or 2 ohms, whichever is greater.

Vibration: Method 204 of MIL-STD-202, test condition A, 0.015 inch (0.03 inch total excursion) 10 to 55 Hz; or an amplitude to produce 10 gravity units, 55 to 500 Hz, whichever is the limiting value.

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±15 percent, or 2 ohms, whichever is greater.

Thermal shock: ±50 ppm.

Aging:

Frequency change permitted: ±10 ppm.

NOTE: These crystal units are for use in the AN/ARN-52 equipment.

Revision letters are not used to denote changes due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:52Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Air Force - 85
DLA - ES

User activities:
Air Force - 17, 19, 84

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5955-0678-05)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:52Z
Check the source to verify that this is the current version before use.