MIL-C-3098/111A
23 June 1975
SUPERSEDING
MIL-C-3098/111
29 May 1969


MILITARY SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR-8A/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the crystal unit described herein shall consist of this document and the latest issue of Specification MIL-C-3098.

Pertinent characteristics: 1 to 10 MHz; fundamental; noncontrolled; series



INCHES	MM	INCHES	MM	INCHES	MM
.002	.05	.050	1.27	.486	12.34
.008	.20	.093	2.36	.725	18.42
.017	.43	.317	8.05	.757	19.23
.018	.46	.352	8.94	.775	19.69
.030	.76	.448	11.38		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
Ⓐ 3. The pin undercut may be omitted.

Ⓐ denotes change

Source: https://assist.dla.mil -- Downloaded: 2026-10-16 16:56:52
Check the source to verify that this is the current version before use.

TABLE I. Requirements.

Requirements	Specified value or condition
Holder	HC-17/U (MIL-H-10056/8)
Dimensions, marking, and configuration	See figure
Frequency range	1.0 to 10 MHz, inclusive
Frequency tolerance (operating temperature range)	±50 PPM
Equivalent resistance	See table III
Mode of oscillation	Fundamental
Operating temperature range (noncontrolled)	-40° to +70° C, inclusive
Test set, calibration values, and rated drive level	See table II
Shock (specified pulse):	
Frequency change permitted	±5 PPM
Equivalent resistance change permitted	±10 percent
Vibration: 1/	
Frequency change permitted	±5 PPM
Equivalent resistance change permitted	±10 percent
Temperature run:	
Frequency change permitted	±5 PPM
Equivalent resistance change permitted	±10 percent

1/ Method 201 of MIL-STD-202.

TABLE II. Test set, calibration values, and rated drive level.

Government reference standard test set	Band of specified frequencies, inclusive	Calibration values		Rated drive level
		Resistance	Crystal current	
	MHz	Ohms	mA	mW
TS-330/TSM	1.0 to 1.5	170	10	40±5
	1.5+ to 3.4	40	10	
	3.4+ to 5.1	40	10	
	5.1+ to 10.0	40	10	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:53Z
Check the source to verify that this is the current version before use.

TABLE III. Equivalent resistance.

Frequency range, inclusive	Maximum resistance
MHz	Ohms
1.0 to 2.0	450
2.0+ to 3.0	250
3.0+ to 4.0	150
4.0+ to 5.0	100
5.0+ to 6.0	75
6.0+ to 7.0	55
7.0+ to 10.0	50

NOTES:

1. Socket. This unit has oversize pins and does not use same socket as preferred types of crystal units.

2. This crystal-unit type is to be used for special applications and for replacement purposes only. Specific approval of the Government is required prior to each intended use. See MIL-STD-683.

Custodians:
Army - EL
Navy - EC
Air Force - 84

Review activities:
Army - EL, MI, MU, SG, SM
Navy - EC
Air Force - 11, 85
DSA - ES

User activities:
Army -
Navy - AS, MC, SH
Air Force - 17, 19

Preparing activity:
Army - EL

Agent:
DSA - ES

(Project 5955-0408-46)

☆U.S. GOVERNMENT PRINTING OFFICE: 1975-603-766/360

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:53Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION MIL-C-3098/111A CRYSTAL UNIT, QUARTZ, CR-8A/U

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD. FORM 1 JAN 68 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

ESC-PM 1068-68

To detach this form, cut along this line

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:53Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Army
Headquarters
U.S.Army Electronics Command
Fort Monmouth, New Jersey 07703

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding General
U.S.Army Electronics Command
ATTN: AMSEL- RD-TS
Fort Monmouth, New Jersey 07703

To detach this form, cut along this line

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:53Z
Check the source to verify that this is the current version before use.